

Surface Mount Schottky Barrier Rectifier  
Reverse Voltage - 20 to 200V Forward Current - 2.0A

## FEATURES


- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

## MECHANICAL DATA

- Case : SMB
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.055g / 0.002oz

## PINNING

| PIN | DESCRIPTION |
|-----|-------------|
| 1   | Cathode     |
| 2   | Anode       |



## Absolute Maximum Ratings and Electrical characteristics


Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

| Parameter   | Symbols         | SS22BG     | SS24BG | SS26BG | SS28BG   | SS210BG | SS212BG | SS215BG | SS220BG | Units |
|---|-----------------|------------|--------|--------|----------|---------|---------|---------|---------|-------|
| Maximum Repetitive Peak Reverse Voltage   | $V_{RRM}$       | 20         | 40     | 60     | 80       | 100     | 120     | 150     | 200     | V     |
| Maximum RMS voltage   | $V_{RMS}$       | 14         | 28     | 42     | 56       | 70      | 84      | 105     | 140     | V     |
| Maximum DC Blocking Voltage   | $V_{DC}$        | 20         | 40     | 60     | 80       | 100     | 120     | 150     | 200     | V     |
| Maximum Average Forward Rectified Current   | $I_{F(AV)}$     | 2.0        |        |        |          |         |         |         |         | A     |
| Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)         | $I_{FSM}$       | 55         |        |        |          | 45      |         |         |         | A     |
| Max Instantaneous Forward Voltage at 2 A  | $V_F$           | 0.55       | 0.70   |        | 0.85     |         | 0.95    |         | V       |       |
| Maximum DC Reverse Current $T_a = 25^\circ\text{C}$ at Rated DC Reverse Voltage $T_a = 100^\circ\text{C}$ | $I_R$           | 0.5<br>5   |        |        | 0.3<br>3 |         |         |         | mA      |       |
| Typical Junction Capacitance <sup>(1)</sup>   | $C_j$           | 220        |        |        | 110      |         |         |         | pF      |       |
| Typical Thermal Resistance <sup>(2)</sup>   | $R_{\theta JA}$ | 60         |        |        |          |         |         |         |         | °C/W  |
| Operating Junction Temperature Range  | $T_j$           | -55 ~ +125 |        |        |          |         |         |         |         | °C    |
| Storage Temperature Range   | $T_{stg}$       | -55 ~ +150 |        |        |          |         |         |         |         | °C    |


( 1 ) Measured at 1 MHz and applied reverse voltage of 4 V D.C

( 2 ) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Reverse Characteristics**




**Fig.3 Typical Forward Characteristic**




**Fig.4 Typical Junction Capacitance**



**Fig.5 Maximum Non-Repetitive Peak Forward Surge Current**




**Fig.6- Typical Transient Thermal Impedance**



## PACKAGE OUTLINE

Plastic surface mounted package; 2 leads


SMB



SMB mechanical data

| UNIT |     | A    | E    | D    | E <sub>1</sub> | A <sub>1</sub> | L   | C     | b   |
|------|-----|------|------|------|----------------|----------------|-----|-------|-----|
| mm   | max | 2.44 | 4.70 | 3.94 | 5.59           | 0.20           | 1.5 | 0.305 | 2.2 |
|      | min | 2.13 | 4.06 | 3.3  | 5.08           | 0.05           | 0.8 | 0.152 | 1.9 |
| mil  | max | 96   | 185  | 155  | 220            | 7.9            | 59  | 12    | 87  |
|      | min | 84   | 160  | 130  | 200            | 2.0            | 32  | 6     | 75  |

### The recommended mounting pad size



### Marking

| Type number | Marking code |
|-------------|--------------|
| SS22BG      | SS22         |
| SS24BG      | SS24         |
| SS26BG      | SS26         |
| SS28BG      | SS28         |
| SS210BG     | SS210        |
| SS212BG     | SS212        |
| SS215BG     | SS215        |
| SS220BG     | SS220        |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Schottky Diodes & Rectifiers](#) category:*

*Click to view products by [Shikues](#) manufacturer:*

Other Similar products are found below :

[CUS06\(TE85L,Q,M\)](#) [MA4E2039](#) [D1FH3-5063](#) [MBR0530L-TP](#) [MBR10100CT-BP](#) [MBR30H100MFST1G](#) [MMBD301M3T5G](#) [PMAD1103-LF](#) [PMAD1108-LF](#) [RB160M-50TR](#) [RB520S-30](#) [RB551V-30](#) [DD350N18K](#) [DZ435N40K](#) [DZ600N16K](#) [BAS16E6433HTMA1](#) [BAS 3010S-02LRH E6327](#) [BAT 54-02LRH E6327](#) [IDL02G65C5XUMA1](#) [NSR05F40QNXT5G](#) [NSVR05F40NXT5G](#) [JANS1N6640](#) [SB07-03C-TB-H](#) [SB1003M3-TL-W](#) [SBAT54CWT1G](#) [SBM30-03-TR-E](#) [SBS818-TL-E](#) [SK32A-LTP](#) [SK33A-TP](#) [SK34A-TP](#) [SK34B-TP](#) [SMD1200PL-TP](#) [ACDBN160-HF](#) [SS3003CH-TL-E](#) [STPS30S45CW](#) [PDS3100Q-7](#) [GA01SHT18](#) [CRS10I30A\(TE85L,QM\)](#) [MBR1240MFST1G](#) [MBRB30H30CT-1G](#) [BAS28E6433HTMA1](#) [BAS 70-02L E6327](#) [HSB123JTR-E](#) [JANTX1N5712-1](#) [VS-STPS40L45CW-N3](#) [DD350N12K](#) [SB007-03C-TB-E](#) [SB10015M-TL-E](#) [SB1003M3-TL-E](#) [SK110-LTP](#)