



一般回路用、SW電源用コンデンサ
GENERAL PURPOSE, SWITCHING POWER SUPPLY



FNS
(135)

ポリプロピレン
POLYPROPYLENE



特徴

- 耐熱性向上PPフィルムを採用し、使用温度範囲を拡大。-40~110℃(電圧軽減により125℃まで使用可能)
- 周波数特性が良好。
- 低損失。

用途

- 一般回路
- 共振型SW電源(CTV PDP LCDTV、その他)
- オーディオ機器(ビュアンプ、AVアンプ、DVD、CD、楽器)

電気特性

使用温度範囲 -40℃~110℃(電圧軽減により125℃まで使用可能)
 定格電圧 100VDC・200VDC・400VDC・630VDC
 静電容量範囲 0.0003μF~0.47μF
 静電容量許容差 ±2%(G) ±3%(H) ±5%(J)
 誘電正接 ≤0.08%(at 1kHz 20℃)
 耐電圧 定格電圧×175%(1~5秒)
 絶縁抵抗 30,000MΩ ≤ (≤0.33μF at 20℃)
 10,000MΩ μF ≤ (0.33μF < at 20℃)

CHARACTERISTICS

- High temperature proof PP film used to expand temperature range.
-40 to 110℃ (Can be used max 125℃ by rated voltage derating)
- Excellent frequency characteristics.
- Low Dissipation Factor.

APPLICATIONS

- General purpose
- Resonance Switching power supply (CTV PDP LCDTV etc.)
- Audio & visual equipment (Pure Amp, AV Amp, DVD, CD, Music Instrument)

ELECTRIC CHARACTERISTICS

Operation Temperature -40℃~110℃ (Can be used max 125℃ by rated voltage derating)
 Range Voltage 100VDC・200VDC・400VDC・630VDC
 Capacitance range 0.0003μF~0.47μF
 Capacitance tolerance ±2%(G) ±3%(H) ±5%(J)
 Dissipation factor
 Withstand voltage ≤0.08%(at 1kHz 20℃)
 Dielectric strength Rated voltage×175%(1~5sec)
 30,000MΩ ≤ (≤0.33μF at 20℃)

FNS (135) VDC

Capacity (μF)	DIMENSIONS (mm) 100VDC							DIMENSIONS (mm) 200VDC							DIMENSIONS (mm) 400VDC							DIMENSIONS (mm) 630VDC									
	L	H	T	F	d	Style		L	H	T	F	d	Style		L	H	T	F	d	Style		L	H	T	F	d	Style				
301 (0.0003)	10.5	9.0	6.0	5.0	0.6	1																									
331 (0.00033)	10.5	9.0	6.0	5.0	0.6	1																									
361 (0.00036)	10.5	9.5	6.0	5.0	0.6	1																									
391 (0.00039)	10.5	9.5	6.0	5.0	0.6	1																									
431 (0.00043)	11.0	9.0	6.0	5.0	0.6	1																									
471 (0.00047)	11.0	9.5	6.0	5.0	0.6	1																									
511 (0.00051)	11.0	9.0	6.0	5.0	0.6	1																									
561 (0.00056)	11.0	9.5	6.0	5.0	0.6	1																									
621 (0.00062)	11.0	10.0	6.0	5.0	0.6	1																									
681 (0.00068)	11.0	9.0	6.0	5.0	0.6	1																									
751 (0.00075)	11.0	9.5	6.0	5.0	0.6	1																									
821 (0.00082)	11.0	9.5	6.0	5.0	0.6	1																									
911 (0.00091)	11.0	10.0	6.0	5.0	0.6	1																									
102 (0.001)	10.0	9.5	6.0	5.0	0.6	1	13.5						1	13.5	10.0	6.0	10.0	0.7	1	13.5	9.5	6.0	10.0	0.7	1	13.5	9.5	6.0	10.0	0.7	1
112 (0.0011)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
122 (0.0012)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
132 (0.0013)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
152 (0.0015)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
162 (0.0016)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
182 (0.0018)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
202 (0.002)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
222 (0.0022)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
242 (0.0024)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
272 (0.0027)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
302 (0.003)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
332 (0.0033)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
362 (0.0036)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
392 (0.0039)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
432 (0.0043)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
472 (0.0047)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
512 (0.0051)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
562 (0.0056)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
622 (0.0062)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
682 (0.0068)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
752 (0.0075)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	2	
822 (0.0082)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	2	
912 (0.0091)	10.0	9.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	2	
103 (0.01)	10.0	10.0	6.0	5.0	0.6	1	13.5	9.5	6.0	10.0	0.7	1	13.5	10.0	6.5	10.0	0.7	1	13.5	10.0	6.5	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	2	
113 (0.011)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.5	6.5	10.0	0.7	1	13.5	10.5	6.5	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	2	
123 (0.012)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	10.5	7.0	10.0	0.7	1	13.5	10.5	7.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	2	
133 (0.013)	10.0	10.5	6.0	5.0	0.6	1	13.5	10.0	6.5	10.0	0.7	1	13.5	11.0	7.0	10.0	0.7	1	13.5	11.0	7.0	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
153 (0.015)	10.0	10.5	6.0	5.0	0.6	1	13.5	10.0	6.5	10.0	0.7	1	13.5	11.0	7.5	10.0	0.7	1	13.5	11.0	7.5	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
163 (0.016)	10.0	10.0	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	11.5	7.5	10.0	0.7	1	13.5	11.5	7.5	10.0	0.7	1	13.5	10.0	6.0	10.0	0.7	1	
183 (0.018)	10.0	10.5	6.0	5.0	0.6	1	13.5	9.5	6.0	10.0	0.7	1	13.5	11.0	6.0	10.0	0.7	2	13.5	11.0	6.0	10.0	0.7	2	13.5	10.0	6.0	10.0	0.7	1	
203 (0.02)	10.0	10.5	6.0	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1	13.5	11.0	6.0	10.0	0.7	2	13.5	11.0	6.0	10.0	0.7	2	13.5	10.0	6.0	10.0	0.7	1	
223 (0.022)	10.0	11.0	6.5	5.0	0.6	1	13.5	10.0	6.0	10.0	0.7	1																			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Film Capacitors](#) category:

Click to view products by [SHINYEI](#) manufacturer:

Other Similar products are found below :

[F339X134748MIP2T0](#) [F450KG153J250ALH0J](#) [750-1018](#) [FKP1-1500160010P15](#) [FKP1R031007D00JYSD](#) [FKP1R031507E00JYSD](#)
[FKP1U024707E00KYSD](#) [82DC4100CK60J](#) [82EC1100DQ50K](#) [PFR5101J100J11L16.5TA18](#) [PME261JB5220KR19T0](#) [A451GK223M040A](#)
[A561ED221M450A](#) [QXJ2E474KTPT](#) [QXL2B333KTPT](#) [R49AN347000A1K](#) [EEC2G505HQA406](#) [B25668A6676A375](#) [B25673A4282E140](#)
[BFC233868148](#) [BFC2370GC222](#) [C3B2AD44400B20K](#) [C4ASWBU3220A3EK](#) [CB027C0473J--](#) [CB177I0184J--](#) [CB182K0184J--](#) [23PW210](#)
[950CQW5H-F](#) [SBDC3470AA10J](#) [SCD105K122A3-22](#) [2N3155](#) [A571EH331M450A](#) [FKP1-2202KV5P15](#) [FKS3-680040010P10](#)
[QXL2E473KTPT](#) [445450-1](#) [B25669A3996J375](#) [46KI322000M1M](#) [46KR415050M1K](#) [4BSNBX4100ZBFJ](#) [MKP383510063JKP2T0](#)
[MKPY2-.02230020P15](#) [MKT 1813-368-015](#) [4055292001](#) [46KN410000N1K](#) [EEC2E106HQA405](#) [EEC2G205HQA402](#) [EEC2G805HQA415](#)
[P409CP224M250AH470](#) [82EC2150DQ50K](#)