



深圳市首韩科技有限公司

SHENZHEN SHOUHAN TECHNOLOGY CO., LTD

Tel: 0755-27597601 Fax: 0755-27597491

承 认 书

SPECIFICATION FOR APPROVAL

客 户 Customer:

产品名称 Project:

磁环

规格型号 Part No:

SHKJ 1325 0330A

贵公司承认印 Approval signatures

料 号/Part No.	签 章/Signatures

日期 Date:

拟制/Drawn	李春风	
审核/Check	张栋	
批准/Approved	罗孝金	




承 認 書

SPECIFICATION FOR APPROVAL

客户名稱 CUSTOMER				日期 DATE	2020.05.08.																																										
規 格 ITEM	SHKJ 1325 0330A			編 號 SERIAL NO.	20050830015																																										
<p>1.1. 形狀尺寸(單位/毫米): SHAPE & DIMENSION(unit/mm):</p> <p>1.2. 實物圖: The Sample: :</p> <p>外殼尺寸:</p>  <p>磁芯尺寸:</p>  				A	13.0 ± 1.0 mm																																										
				B	11.8 ± 1.0 mm																																										
				C	3.5 ± 0.8 mm																																										
				D	25.2 ± 1.0 mm																																										
				E	2.5 ± 1.0 mm																																										
				F	10 ± 0.5 mm																																										
				G	20 ± 0.6 mm																																										
				H	3.5 ± 0.5 mm																																										
				I	4.6 ± 0.5 mm																																										
				<p>2. 電氣性能檢測項目: ELECTRICAL REQUIREMENTS:</p>				<p>測試儀器 TEST INSTRUMENTS</p> <p>1. Q-METER: ○ HP 4342A ○ MQ-172</p> <p>2. L.C.R. METER: ○ HP 4284A</p> <p>3. IMPEDANCE ANALYZER: ○ HP 4396B ○ HP 4191A ○ E4991A ○ Agilent 16194A-TESTFIXTURE</p> <p>4. L-METER: ○ TH 2817A</p> <p>5. DIGITAL MINI-OHMMETER: ○ VP2941A</p>																																							
<input type="checkbox"/> L		TEST FREQ		KHZ MHZ																																											
<input type="checkbox"/> Q		TEST FREQ		KHZ MHZ																																											
<input checked="" type="checkbox"/> Z	Z1= 85Ω MIN	KHZ 25 MHZ	Z2= 175Ω MIN	KHZ 100 MHZ																																											
	Z3= /	KHZ MHZ	Z4= /	KHZ MHZ																																											
溫度 TEMP	℃	濕 度 HUMIDITY		%																																											
綫 組 WINDING	Φ0.5x0.5TSx100L(mm)																																														
<p>3. 外觀標準: 依下表對照檢索: THE LIMIT OF BREAKAGE: CHECKED BELOW:</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>OD (mm)</th> <th>0~5</th> <th>5.1~10</th> <th>10.1~15</th> <th>15.1~20</th> <th>20.1~25</th> <th>25.1~30</th> <th>30.1~35</th> <th>35以上</th> </tr> <tr> <td>缺陷面积 Defect area (mm²)</td> <td>≦1</td> <td>≦2</td> <td>≦3</td> <td>≦4</td> <td>≦5</td> <td>≦6</td> <td>≦7</td> <td>≦8</td> </tr> <tr> <td>缺陷个数 Number of defects (≦)</td> <td>1</td> <td>2</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>2</td> <td>2</td> </tr> </table>								OD (mm)	0~5	5.1~10	10.1~15	15.1~20	20.1~25	25.1~30	30.1~35	35以上	缺陷面积 Defect area (mm ²)	≦1	≦2	≦3	≦4	≦5	≦6	≦7	≦8	缺陷个数 Number of defects (≦)	1	2	3	3	3	3	2	2													
OD (mm)	0~5	5.1~10	10.1~15	15.1~20	20.1~25	25.1~30	30.1~35	35以上																																							
缺陷面积 Defect area (mm ²)	≦1	≦2	≦3	≦4	≦5	≦6	≦7	≦8																																							
缺陷个数 Number of defects (≦)	1	2	3	3	3	3	2	2																																							
<p>4. 材質特性 MATERIAL CHARACTERISTICS</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>材料牌號 Material</th> <th>初始磁導率 Initial Permeability</th> <th>比損耗因子 Relative Loss Factor</th> <th>比溫度系數 Relative Temperature Coefficient</th> <th>飽和磁通密度 Saturation Magnetic Flux Density</th> <th>剩磁 Remanence</th> <th>矯頑力 Coercivity</th> <th>居裏溫度 Curie Temperature</th> <th>電阻率 Electrical Resistivity</th> <th>密度 Density</th> </tr> <tr> <th>Unit symbol</th> <th>μ_i</th> <th>$\tan \delta / \mu_i$</th> <th>$\alpha \mu_i \gamma$</th> <th>B_s</th> <th>B_r</th> <th>H_C</th> <th>T_c</th> <th>ρ</th> <th>d</th> </tr> <tr> <th></th> <th>±20%</th> <th>×10⁻⁶</th> <th>×10⁻⁶</th> <th>(MT)</th> <th>(MT)</th> <th>(A/m)</th> <th>(°C)</th> <th>(Ω · m)</th> <th>g/cm³</th> </tr> </thead> <tbody> <tr> <td>F9</td> <td>850</td> <td>16 (0.1MHZ)</td> <td>5 - 10</td> <td>280(1600A/m)</td> <td>200</td> <td>20</td> <td>>130</td> <td>>10⁵</td> <td>4.6</td> </tr> </tbody> </table>								材料牌號 Material	初始磁導率 Initial Permeability	比損耗因子 Relative Loss Factor	比溫度系數 Relative Temperature Coefficient	飽和磁通密度 Saturation Magnetic Flux Density	剩磁 Remanence	矯頑力 Coercivity	居裏溫度 Curie Temperature	電阻率 Electrical Resistivity	密度 Density	Unit symbol	μ_i	$\tan \delta / \mu_i$	$\alpha \mu_i \gamma$	B_s	B_r	H_C	T_c	ρ	d		±20%	×10 ⁻⁶	×10 ⁻⁶	(MT)	(MT)	(A/m)	(°C)	(Ω · m)	g/cm ³	F9	850	16 (0.1MHZ)	5 - 10	280(1600A/m)	200	20	>130	>10 ⁵	4.6
材料牌號 Material	初始磁導率 Initial Permeability	比損耗因子 Relative Loss Factor	比溫度系數 Relative Temperature Coefficient	飽和磁通密度 Saturation Magnetic Flux Density	剩磁 Remanence	矯頑力 Coercivity	居裏溫度 Curie Temperature	電阻率 Electrical Resistivity	密度 Density																																						
Unit symbol	μ_i	$\tan \delta / \mu_i$	$\alpha \mu_i \gamma$	B_s	B_r	H_C	T_c	ρ	d																																						
	±20%	×10 ⁻⁶	×10 ⁻⁶	(MT)	(MT)	(A/m)	(°C)	(Ω · m)	g/cm ³																																						
F9	850	16 (0.1MHZ)	5 - 10	280(1600A/m)	200	20	>130	>10 ⁵	4.6																																						



檢 驗 數 據 INSPECTION DATA


客戶名稱 CUSTOMER				日期 DATE	2020.05.08.		數量 QUANTITY	10PCS					
編號 SERIAL NO.		20050830015		形狀尺寸(單位/毫米): SHAPE & DIMENSION(unit/mm): (Core diameter) 實物圖: The Sample:: 外觀尺寸:  磁芯尺寸: 									
規格 ITEM		SHKJ 1325 0330A											
線組 WINDING		Φ0.5x0.5TSx100L(mm)											
測試頻率 TEST FREQ		Z1= 25 KHZ	Z2= 100 KHZ						Z3= KHZ	Z4= KHZ			
溫度 TEMP		℃	濕度 HUMIDITY			%							
項目 TEST ITEM	電氣性能 ELECTRIC CHARACTERISTICS			尺寸(單位:毫米) DIMENSION(unit:mm)									
	Z1(Ω)	Z2(Ω)	Z3(Ω)	A	B	C	D	E	F	G	H	I	
	85	175		13.0	11.8	3.5	25.2	2.5	10	20	3.5	4.6	
+	/	/		1.0	1.0	0.8	1.0	1.0	0.5	0.6	0.5	0.5	
-	0	0		1.0	1.0	0.8	1.0	1.0	0.5	0.6	0.5	0.5	
1	101.7	218.8		13.06	11.93	3.62	24.78	2.50	10.01	20.11	3.52	4.62	
2	101.8	219.0		13.13	11.92	3.59	24.79	2.60	10.10	20.20	3.45	4.55	
3	102.5	218.7		13.09	11.85	3.58	24.85	2.40	10.06	20.16	3.50	4.60	
4	103.0	219.4		13.08	11.86	3.51	24.88	2.45	10.12	20.15	3.53	4.63	
5	102.5	219.6		13.15	11.88	3.49	24.96	2.52	10.06	20.14	3.42	4.52	
6	103.4	218.5		13.12	11.82	3.60	24.98	2.48	9.95	20.09	3.49	4.59	
7	101.6	219.3		13.17	11.92	3.63	25.20	2.53	9.99	20.00	3.51	4.61	
8	101.2	219.2		13.14	11.96	3.45	25.05	2.47	9.94	19.95	3.58	4.58	
9	102.7	218.6		13.16	11.98	3.64	25.12	2.49	9.89	19.97	3.54	4.64	
10	103.4	218.1		13.11	11.92	3.62	25.09	2.51	9.98	19.99	3.47	4.67	
\bar{X}	102.38	218.92		13.12	11.90	3.57	24.97	2.49	10.01	20.07	3.50	4.60	
Y/N	Y	Y		Y	Y	Y	Y	Y	Y	Y	Y	Y	
測試儀器: TEST INSTRUMENTS: E4991A+16194A								檢 驗 INSPECTED		復 核 CHECKED		確 認 APPROVED	
				李春风		张栋		罗孝金					



阻抗 - 頻率曲綫

IMPEDANCE V.S FREQUENCY (Z-Y)

客戶名稱 CUSTOMER		日期 DATE	2020.05.08.
規格 ITEM	F9 SCRC 35A	編號 SERIAL NO.	20050830015



測試條件：
TESTING CONDITION:

1. 測試儀器：
Testing Equipment: E4991A+16194A
2. 測試頻率區間：
Testing Frequency Range: 1-500MHz
3. 測試綫組：
Testing Coil Specification: Φ0.5x0.5TSx100L(mm)

說明Note:

本承認書在客戶收到7天之內，須簽章返回，逾期視為默認。

The Specification Approval is required to be sent back to the supplier with customer's chop or signature on it within 4 days after receiving it, or we will take it as approved by customer automatically.

測試 TESTED	復核 CHECKED	確認 APPROVED
李春风	张栋	罗孝金

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ferrite Clamp On Cores](#) category:

Click to view products by [SHOU](#) manufacturer:

Other Similar products are found below :

[CS28B0984](#) [CS28B1501](#) [CV28B1642](#) [RA33B4340](#) [IL25B0642K](#) [SA28B0121](#) [SS33B2033](#) [HI28B2039](#) [RA33B2480](#) [TC28B0937](#)
[432703037561](#) [USB28B2034](#) [432202209491](#) [4327 018 21641](#) [CF28B0642](#) [SS33B2035](#) [TC28B2000](#) [CF28B1937](#) [SS20B2037](#) [TC20B1500](#)
[SS25B2032](#) [SS20B2034](#) [PM28B0686](#) [RA20B1729](#) [CS33B4000](#) [TC33B0805](#) [SS33B2040](#) [TC28B1501](#) [AS33B2036](#) [AS25B2032](#)
[TC28B0550](#) [AS25B2036](#) [AS28B2027](#) [F9 SCRC 35B](#) [SHKJ 1325 0330A](#) [CS33B2000](#) [74271111](#) [74271132](#) [74271132S](#) [74271142](#) [74271222](#)
[7427151](#) [74271622S](#) [RRH-100-50-100](#) [RRH-105-55-200](#) [RRH-142-70-285](#) [RRH-175-107-285](#) [RRH-186-102-250](#) [RRH-186-102-286](#) [RRH-259-128-286](#)