



SITOP SEL1400/4X2-10A

SITOP SEL1400 10 A Selectivity module 4-channel with limiting characteristic input: 24 V DC/40 A output: 24 V DC/4x 10 A threshold adjustable 2-10 A with monitoring interface *Ex approval no longer available*

Input	
type of the power supply network	Controlled DC voltage
supply voltage at DC rated value	24 V
input voltage at DC	20.4 ... 30 V
overvoltage overload capability	35 V
input current at rated input voltage 24 V rated value	40 A
Output	
voltage curve at output	controlled DC voltage
formula for output voltage	$V_{in} - \text{approx. } 0.2 \text{ V}$
relative overall tolerance of the voltage note	In accordance with the supplying input voltage
number of outputs	4
output current up to 60 °C per output rated value	10 A
adjustable current response value current of the current-dependent overload release	2 ... 10 A
type of response value setting	via potentiometer
product feature parallel switching of outputs	Yes
type of outputs connection	Connection of all outputs after ramp-up of the supply voltage > 20 V; delay time of 25 ms, 200 ms, 500 ms or "load-optimized" can be set via DIP switch for sequential connection
Efficiency	
efficiency in percent	98 %
power loss [W] at rated output voltage for rated value of the output current typical	10 W
Switch-off characteristic per output	
switching characteristic	<ul style="list-style-type: none"> • of the excess current $I_{out} = 1.0 \dots 1.5 \times \text{set value}$, switch-off after approx. 5 s • of the current limitation $I_{out} = 1.5 \times \text{set value}$, switch-off after typ. 100 ms • of the immediate switch-off $I_{out} > \text{set value}$ and $V_{in} < 20 \text{ V}$, switch-off after approx. 0.5 ms
design of the reset device/resetting mechanism	via sensor per output
remote reset function	Non-electrically isolated 24 V input (signal level "high" at > 15 V)
Protection and monitoring	
fuse protection type at input	15 A per output (not accessible)
display version for normal operation	Three-color LED per output: green LED for "Output switched through"; yellow LED for "Output switched off manually"; red LED for "Output switched off due to overcurrent"
design of the switching contact for signaling function	Floating common signal contact or status signal output (pulse/pause signal that can be evaluated via SIMATIC function block)
Safety	
galvanic isolation between input and output at switch-off	No
standard for safety	according to EN 60950-1 and EN 50178
operating resource protection class	Class III
protection class IP	IP20

Approvals	
certificate of suitability	Yes
<ul style="list-style-type: none"> • CE marking • UL approval 	Yes; UL-Recognized (UL 2367) File E328600; cULus-Listed (UL 508, CSA C22.2 No. 107.1) File E197259
<ul style="list-style-type: none"> • CSA approval • ATEX 	Yes; CSA 22.2 60950-1 No
certificate of suitability	No
<ul style="list-style-type: none"> • IECEX 	No
type of certification CB-certificate	Yes
certificate of suitability	Yes
<ul style="list-style-type: none"> • EAC approval 	Yes
EMC	
standard	
<ul style="list-style-type: none"> • for emitted interference 	EN 61000-6-3
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2
environmental conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation • during transport • during storage 	-25 ... +70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category according to IEC 60721	climate class 3K3, 5 ... 95% without condensation
Mechanics	
type of electrical connection	Push-in
<ul style="list-style-type: none"> • at input • at output • for signaling contact • for auxiliary contacts 	24V1, 24V2: push-in for 0.5 ... 16 mm ² ; 0V1, 0V2: push-in for 0.5 ... 4 mm ² 1 - 4: push-in for 0.5 ... 4 mm ² 13, 14: push-in for 0.2 ... 1.5 mm ² RST: push-in for 0.2 ... 1.5 mm ²
width of the enclosure	45 mm
height of the enclosure	135 mm
depth of the enclosure	125 mm
installation width	45 mm
mounting height	225 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	45 mm 45 mm 0 mm 0 mm
net weight	0.3 kg
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIN Rail Power Supplies](#) category:

Click to view products by [Siemens](#) manufacturer:

Other Similar products are found below :

[PS-3015](#) [DVP01PU-S](#) [DVP06AD-S](#) [DVPPS02](#) [PS9Z-5R1G](#) [PS-C24024](#) [ADNB040-24-1PM-C](#) [SS14011524](#) [PSW-12024](#) [S8T-BUS03](#) [PS-S4024](#) [NTPS-24-1.3](#) [PS-10024](#) [PS-C12024](#) [PSP-480S24](#) [PS-C48024](#) [PS-C480P24](#) [PSC-2024](#) [PSC-4012](#) [PSC-4048](#) [PSC-9615](#) [PSC-15124](#) [PSC-15148](#) [PSC-24148](#) [PSC-48148](#) [PSS18/24/0.75](#) [PSS120/24/5](#) [PSD-A120W12](#) [NDR-7524](#) [NDR-12024](#) [AMED15-48SNZ-B](#) [AMED15-5SNZ-B](#) [AMED120-48SJZ](#) [AMED120-24SJZ](#) [AMED15-24SNZ-B](#) [AMED75-48SJZ](#) [1SVR427043R1200](#) [1110466](#) [50995](#) [50903](#) [50997](#)
[EL50-D](#) [18924-9989](#) [50996](#) [HDN-3024](#) [ISEDR-120-24](#) [1335699](#) [1335698](#) [LWR1601-6ER](#) [1170952](#)