



SIMATIC DP, ET 200ECO PN, 8 DI 24 V DC; 8xM12, Degree of protection IP67

Figure similar

General information	
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	Yes
Input current	
Current consumption, typ.	100 mA
from supply voltage 1L+, max.	4 A
Encoder supply	
Number of outputs	8
24 V encoder supply	
• Short-circuit protection	Yes; Electronic
• Output current, max.	100 mA; per output
Power loss	
Power loss, typ.	4.5 W
Digital inputs	
Number of digital inputs	8
• in groups of	1
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 60 °C, max.	8
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	typically 3 ms
— at "1" to "0", max.	typically 3 ms
Cable length	
• unshielded, max.	30 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes

— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Interfaces</b>	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1
<b>1. Interface</b>	
<b>Interface types</b>	
• M12 port	Yes
• integrated switch	Yes
<b>Interface types</b>	
<b>M12 port</b>	
• Autonegotiation	Yes
• Autocrossing	Yes
• Transmission rate, max.	100 Mbit/s
<b>Protocols</b>	
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No
<b>PROFINET IO Device</b>	
<b>Services</b>	
— IRT with the option "high flexibility"	Yes
— Prioritized startup	Yes
<b>Redundancy mode</b>	
<b>Media redundancy</b>	
— MRP	Yes
<b>Open IE communication</b>	
• TCP/IP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnoses</b>	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes; green "ON" LED
• Wire-break in signal transmitter cable	Yes
• Short-circuit encoder supply	Yes; Per channel group
• Group error	Yes; Red/yellow "SF/MT" LED
<b>Potential separation</b>	
between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
<b>Potential separation channels</b>	
• between the channels	No
<b>Isolation</b>	
<b>tested with</b>	
• 24 V DC circuits	707 V DC (type test)
• Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3
<b>Degree and class of protection</b>	
IP degree of protection	IP65/67
<b>connection method</b>	
Design of electrical connection	4/5-pin M12 circular connectors
<b>Dimensions</b>	
Width	60 mm
Height	175 mm
Depth	49 mm
<b>Weights</b>	

Weight, approx.

910 g

last modified:

8/16/2023 

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [I/O Modules](#) category:*

*Click to view products by [Siemens](#) manufacturer:*

Other Similar products are found below :

[70L-OAC-L](#) [G21960000700](#) [G34960002700](#) [G88104401](#) [IDC-5B](#) [OACU](#) [C4SWOUT](#) [FC6A-T32K3](#) [SNAP-OAC5MA](#) [FC6A-N16B3](#)  
[FC6A-N32B3](#) [FC6A-T16P3](#) [G3TAOD201SDC24](#) [PB32HQ](#) [PB16T](#) [PB8](#) [PB8H](#) [C200H-OD211](#) [GT1-AD04CST](#) [GT1-DA04](#) [70GRCQ24-](#)  
[HS](#) [M-OAC5](#) [G4OAC24AMA](#) [2736505](#) [6202](#) [6402](#) [IL MOD BK DI8 DO4-PAC](#) [FC6A-J2C1](#) [FC6A-KC1C](#) [FC6A-N08A11](#) [FC6A-M24BR1](#)  
[FC6A-K4A1](#) [FC6A-T32P3](#) [9-1393028-2](#) [GP32900003700](#) [641-480-5022](#) [PB16H](#) [WISE-4050/LAN-B](#) [WISE-S614T-A](#) [ADAM-4068-C](#)  
[56475](#) [ADAM-4017+-F](#) [ADAM-4118-C](#) [AMAX-4856-B](#) [WISE-4050-B](#) [ADAM-4051-C](#) [ADAM-4053-F](#) [GT1-AD08MX](#) [TM5SDO6TBFS](#)  
[70Q3446](#)