



SIMATIC ET 200SP, BaseUnit BU15-P16+A0+2D, BU type A0, push-in terminals, without aux. terminals, new load group, WxH: 15x 117 mm

Figure similar

General information	
Product type designation	BU type A0
HW functional status	From FS06
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Mains filter	
<ul style="list-style-type: none"> integrated 	Yes
Current carrying capacity	
For P1 and P2 bus, max.	10 A
For process terminals, max.	2 A
Hardware configuration	
Formation of potential groups	
<ul style="list-style-type: none"> New potential group 	Yes
<ul style="list-style-type: none"> Potential group continued from the left 	No
Slots	
<ul style="list-style-type: none"> Number of slots 	1; Type A0
Potential separation	
between the potential groups	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> horizontal installation, min. 	-30 °C
<ul style="list-style-type: none"> horizontal installation, max. 	60 °C
<ul style="list-style-type: none"> vertical installation, min. 	-30 °C
<ul style="list-style-type: none"> vertical installation, max. 	50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Accessories	
Color coding labels	
<ul style="list-style-type: none"> for process terminals 	CC00 to CC09
<ul style="list-style-type: none"> for AUX terminals 	does not exist
<ul style="list-style-type: none"> for add-on terminals 	does not exist
connection method	
Terminals	
<ul style="list-style-type: none"> Terminal type 	Push-in terminal
<ul style="list-style-type: none"> system-integrated shield connection 	Yes; Optional

• Conductor cross-section, min.	0.14 mm ² ; AWG 26
• Conductor cross-section, max.	2.5 mm ² ; AWG 14
• Number of process terminals to I/O module	16
• Number of terminals to AUX bus	0
• Number of add-on terminals	0
• Number of terminals with connection to P1 and P2 bus	2

Dimensions

Width	15 mm
Height	117 mm
Depth	35 mm

Weights

Weight, approx.	40 g
-----------------	------

last modified:

8/7/2023 

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Controller Accessories](#) category:

Click to view products by [Siemens](#) manufacturer:

Other Similar products are found below :

[G4PB8H](#) [R88A-CAGA003B](#) [AFPG807](#) [AFPX-A21](#) [AFPX-COM2](#) [G4PB16I](#) [G4PB4R](#) [ES100CT022202](#) [DRT2-OD16MLX](#) [E53-COV12](#)
[R88A-CAGA005BR](#) [26546849](#) [50073216-08](#) [50073217-08](#) [89789-16](#) [CP2W-BAT02](#) [V600-H07 2M](#) [CV500-CN624](#) [6ES71936BP000BA0](#)
[6ES71936BP000DA0](#) [AK-CBFA09-50BK](#) [EASY-COM-SWD-C1](#) [BABY ORANGUTAN B-328](#) [SNAP-D12M](#) [018W135P-F](#) [018W140-F](#)
[ORANGUTAN SV-328](#) [CP1W-MAD44](#) [ZUMO SHIELD FOR ARDUINO, V1.2](#) [TRC1800E-F](#) [CP1W-EXT01](#) [2700992](#) [2878599](#) [2900889](#)
[CP1W-BAT01](#) [E53-COV16](#) [CP1W-CIF11](#) [K32-49HC](#) [DCN2-1](#) [2913157](#) [2962463](#) [SNAP-PAC-RCK4](#) [Y92F-74](#) [3G3AX-CUSBM002-E](#)
[IM-T-11A](#) [SNAP-PAC-RCK12](#) [SNAP-PAC-RCK8](#) [Y92A-49N](#) [FC6A-PC1](#) [IM-T-9A](#)