




SIMATIC S7-1200, Relay output SM 1226, F-DQ 2x RLY 5A, PROFIsafe, 70 mm overall width, up to PL E (ISO 13849-1)/ SIL3 (IEC 61508)

| General information | |
|--|--|
| Product type designation | SM 1226, F-DQ 2x relay/5 A |
| Supply voltage | |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| power supply according to NEC Class 2 required | No |
| Input current | |
| from backplane bus 5 V DC, max. | 120 mA |
| Digital outputs | |
| <ul style="list-style-type: none"> from load voltage L+, max. | 300 mA |
| Power loss | |
| Power loss, typ. | 10 W |
| Digital outputs | |
| Number of digital outputs | 2 |
| Short-circuit protection | No |
| Output voltage | |
| <ul style="list-style-type: none"> Rated value (DC) Rated value (AC) | 5 V DC to 30 V DC 5 V AC to 250 V AC |
| Output current | |
| <ul style="list-style-type: none"> for signal "1" permissible range, max. | 5 A maximum per circuit and 10 A maximum of all circuits per module |
| Relay outputs | |
| <ul style="list-style-type: none"> Number of relay outputs | 2; 2 circuits per output |
| Switching capacity of contacts | |
| <ul style="list-style-type: none"> with inductive load, max. with resistive load, max. | 0.1 Hz, accordance with IEC 60947-5-1, DC-13; 2 Hz, accordance with IEC 60947-5-1, AC-15 2 Hz |
| Cable length | |
| <ul style="list-style-type: none"> shielded, max. unshielded, max. | 200 m 200 m |
| Interrupts/diagnostics/status information | |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> for status of the outputs | Yes |
| Degree and class of protection | |
| IP degree of protection | IP20 |
| Standards, approvals, certificates | |
| CE mark | Yes |
| cULus | Yes |
| FM approval | Yes |
| Highest safety class achievable in safety mode | |
| <ul style="list-style-type: none"> Performance level according to ISO 13849-1 | Category 4, PL e |

| | |
|--|---|
| • SIL acc. to IEC 61508 | SIL 3 |
| Probability of failure (for service life of 20 years and repair time of 100 hours) | |
| — Low demand mode: PFDavg in accordance with SIL3 | < 1.00E-05 |
| — High demand/continuous mode: PFH in accordance with SIL3 | < 4.00E-09 |
| Ambient conditions | |
| Free fall | |
| • Fall height, max. | 0.3 m; five times, in product package |
| Ambient temperature during operation | |
| • min. | 0 °C |
| • max. | 55 °C |
| • permissible temperature change | 5°C to 55°C, 3°C / minute |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
| • Storage/transport, min. | 660 hPa |
| • Storage/transport, max. | 1 080 hPa |
| Relative humidity | |
| • Operation at 25 °C without condensation, max. | 95 % |
| Mechanics/material | |
| Enclosure material (front) | |
| • Plastic | Yes |
| Dimensions | |
| Width | 70 mm |
| Height | 100 mm |
| Depth | 75 mm |
| Weights | |
| Weight, approx. | 300 g |
| last modified: | 9/22/2023  |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [PLC Controllers](#) category:

Click to view products by [Siemens](#) manufacturer:

Other Similar products are found below :

[3G2A5PS223E](#) [CJ1M-CPU13](#) [CS1W-CN227](#) [CP1H-Y20DT-D](#) [AFP0RDA4](#) [FC6A-C16R1AE](#) [TM200CE24T](#) [TM200C24R](#) [TMCR2AQ2V](#)
[TM200C40T](#) [TM200C40R](#) [TM200CE32R](#) [EASY-BOX-E4-AC1](#) [TMCR2AM3](#) [TM200CE24R](#) [TM200C16T](#) [TM200C24T](#) [6GK1901-1BB30-0AA0](#) [6ES7193-6BP00-0DA1](#) [6ES7155-6AR00-0AN0](#) [6ES7193-6BP40-0DA1](#) [6ES7972-0BB12-0XA0](#) [6ES7193-6BP40-0BA1](#) [6ES7193-6PA00-0AA0](#) [6ES7972-0BB52-0XA0](#) [6ES7135-6GB00-0BA1](#) [6ES7134-6FF00-0AA1](#) [6ES7132-6BD20-0BA0](#) [6ES7131-6BF01-2BA0](#)
[6ES7522-1BL10-0AA0](#) [6ES7134-6JF00-0CA1](#) [6ES7193-6BP20-0BF0](#) [6ES7521-1BL10-0AA0](#) [6ES7226-6RA32-0XB0](#) [6ES7132-6HD01-0BB1](#) [6ES7193-6BP20-0BB1](#) [6ES7590-1AE80-0AA0](#) [6ES7226-6DA32-0XB0](#) [6ES7392-1AJ00-0AA0](#) [6ES7972-0BA12-0XA0](#) [6ES7522-1BL01-0AB0](#) [6ES7226-6BA32-0XB0](#) [CPM2C10CDT1MD](#) [AFP0RC14RS](#) [2906916](#) [2906920](#) [2906921](#) [CJ2M-MD211](#) [CS1W-OA201](#)
[CJ2M-MD212](#)