



SIMATIC S7-300, Front connector with screw contacts, 40-pole

General information	
Product type designation	Front connector
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Accessories	
belongs to product	S7-300
connection method	
Connection I/O signals	
• Connection method	Screw terminals
• Number of lines per connection	1; Or 2 cables up to 0.75 mm ² (total) in a shared end sleeve
Conductor cross-section in mm ²	
— Connectable cable cross-sections for massive cables, min.	0.14 mm ²
— Connectable cable cross-sections for massive cables, min.	0.75 mm ²
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.14 mm ²
— Connectable cable cross-sections for flexible cables without end sleeve, max.	0.75 mm ²
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.14 mm ²
— Connectable cable cross-sections for flexible cables with end sleeve, max.	0.75 mm ²
Conductor cross-section acc. to AWG	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	19
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	19
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	19
Wire end processing	
— Stripped length of cables, min.	6 mm
— Stripped length of cables, max.	6 mm

- End sleeve acc. to DIN 46228 without plastic sleeve Design A, 5 mm to 7 mm long
- End sleeve acc. to DIN 46228 with plastic sleeve Design E, up to 6 mm long

Mounting

- Tool Screwdriver, conical design, 3 mm to 3.5 mm
- Tightening torque, min. 0.4 N·m
- Tightening torque, max. 0.7 N·m

Dimensions

Width	21.6 mm
Height	125 mm
Depth	40.9 mm

Weights

Weight, approx.	137 g
-----------------	-------

last modified: 8/27/2023 

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [PLC Controllers](#) category:

Click to view products by [Siemens](#) manufacturer:

Other Similar products are found below :

[3G2A5PS223E](#) [CJ1M-CPU13](#) [CS1W-CN227](#) [CP1H-Y20DT-D](#) [AFP0RDA4](#) [FC6A-C16R1AE](#) [TM200CE24T](#) [TM200C24R](#) [TMCR2AQ2V](#)
[TM200C40T](#) [TM200C40R](#) [TM200CE32R](#) [EASY-BOX-E4-AC1](#) [TMCR2AM3](#) [TM200CE24R](#) [TM200C16T](#) [TM200C24T](#) [6GK1901-1BB30-0AA0](#) [6ES7193-6BP00-0DA1](#) [6ES7155-6AR00-0AN0](#) [6ES7193-6BP40-0DA1](#) [6ES7972-0BB12-0XA0](#) [6ES7511-1AK02-0AB0](#) [6ES7193-6BP40-0BA1](#) [6ES7193-6PA00-0AA0](#) [6ES7972-0BB52-0XA0](#) [6ES7135-6GB00-0BA1](#) [6ES7134-6FF00-0AA1](#) [6ES7132-6BD20-0BA0](#) [6ES7131-6BF01-2BA0](#) [6ES7522-1BL10-0AA0](#) [6ES7134-6JF00-0CA1](#) [6ES7193-6BP20-0BF0](#) [6ES7521-1BL10-0AA0](#) [6ES7226-6RA32-0XB0](#) [6ES7132-6HD01-0BB1](#) [6ES7193-6BP20-0BB1](#) [6ES7590-1AE80-0AA0](#) [6ES7226-6DA32-0XB0](#) [6ES7392-1AJ00-0AA0](#) [6ES7972-0BA12-0XA0](#) [6ES7522-1BL01-0AB0](#) [6ES7226-6BA32-0XB0](#) [6ES7392-1AM00-0AA0](#) [6ES7972-0BB42-0XA0](#) [6ES7193-6BP20-0BA0](#) [6ES7131-6BF01-0BA0](#) [6ES7392-1BM01-0AA0](#) [6ES7193-6BP20-0DA0](#) [6ES7193-6UP00-0DP2](#)