





Product Description

A7672X is the LTE Cat 1 module that supports wireless communication modes of LTE/GSM/GPRS/EDGE. It supports maximum 10Mbps downlink rate and 5Mbps uplink rate.

A7672X adopts LCC+LGA form factor and is compatible with SIM7000/SIM7070 series (NB/Cat M modules), and SIM800A/SIM800F series (2G modules), which enables smooth migration from 2G/NB/Cat M products to LTE Cat 1 products, and greatly facilitates more compatible product design for the customer needs.

A7672X supports both multiple built-in network protocols and the drivers for main operation systems (USB driver for Windows, Linux and Android). The software functions, AT commands are compatible with the SIM800 series modules. A7672X also supports BLE* and GNSS* and it integrates abundant industrial standard interfaces with powerful expansibility, such as UART, USB, I2C and GPIO, which makes it perfectly suitable for main IOT applications such as telematics, POS, surveillance devices, industrial routers, and remote diagnostics etc.

Key Benefits

- Compact size with abundant interfaces
- Supports BLE and GNSS functions*
- Abundant software functions: FOTA, LBS, SSL
- Form factor is compatible with the SIM7000/SIM7070 series

Copyright © 2020 SIMCom Wireless Solutions Limited All Rights Reserved SIMCom Headquarters Building, Building 3, No. 289 Linhong Road, Changning District, Shanghai P.R. China Tel: +86 21 31575100 Email: simcom@simcom.com Web: www.simcom.com



Product		A7672S	A7672E	A7672SA
Form Factor		LCC+LGA	LCC+LGA	LCC+LGA
Dimensions(mm)		24.0*24.0*2.4	24.0*24.0*2.4	24.0*24.0*2.4
	LTE-FDD	B1/B3/B5/B8	B1/B3/B5/B7/B8/B20	B1/B2/B3/B4/B5/B7/B8/B28/B66
Frequency Bands	LTE-TDD	B34/B38/B39/B40/B41		
	GSM	900/1800MHz	900/1800MHz	850/900/1800/1900MHz
Temperature		-40°C ~ +85°C	-40°C ~ +85℃	-40°C ~ +85°C
lectrical Featu	ires			
Supply Voltage	(V)	3.4~ 4.2	3.4~ 4.2	3.4~ 4.2
ower	LTE	твр	TBD	TBD
Consumption mA)	GSM,BS_PA_ MFRMS=2	твр	ТВД	TBD
Data Transfer	-			
LTE(Mbps)		10(DL)/5(UL)	10(DL)/5(UL)	10(DL)/5(UL)
GPRS/EDGE(Kbps)		236.8(DL)/236.8(UL)	236.8(DL)/236.8(UL)	236.8(DL)/236.8(UL)
Software Featu				
Protocol		TCP/IP/IPV4/IPV6/Multi-PDP/FTP/ FTPS /HTTP/HTTPS/DNS	TCP/IP/IPV4/IPV6/Multi-PDP/FTP/ FTPS /HTTP/HTTPS/DNS	TCP/IP/IPV4/IPV6/Multi-PDP/FTP/ FTPS /HTTP/HTTPS/DNS
TLS		•	•	•
MQTT		•	•	•
File System		•	•	•
Audio Record/Play		0	0	0
TTS		•	•	•
LBS		•	•	•
FOTA		•	•	•
Android RIL		Android 5.0/6.0/7.0/8.0/9.0	Android 5.0/6.0/7.0/8.0/9.0	Android 5.0/6.0/7.0/8.0/9.0
USB Driver		Microsoft Windows 7/8/10 Linux/Android	Microsoft Windows 7/8/10 Linux/Android	Microsoft Windows 7/8/10 Linux/Android
WWAN (RNDIS)		•	•	•
ECM		•	•	•
Embedded AT		0	0	0
Firmware Upgrade		USB/FOTA	USB/FOTA	USB/FOTA
nterfaces				
SIM Card		1.8V/3.0V	1.8V/3.0V	1.8V/3.0V
UART		•	•	•
USB		•	•	•
PCM		0	0	0
ADC		•	•	•
GPIO		•	•	•
12C		•	•	•
GNSS		0	0	0
BLE		0	0	0
Certification		.		
Certification			CE-RED*/RoHS*/ REACH*	Anatel*/RoHS*/ REACH*

Copyright © 2020 SIMCom Wireless Solutions Limited All Rights Reserved SIMCom Headquarters Building, Building 3, No. 289 Linhong Road, Changning District, Shanghai P.R. China Tel: +86 21 31575100 Email: simcom@simcom.com Web: www.simcom.com

•: support o: optional *: on going

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Simcom manufacturer:

Other Similar products are found below :

S2-1050J-Z0K4J S2-105Y0-Z1E0G S2-10640-Z1G0D S2-10672-Z1L85 S2-10686-Z1L1D S2-106BA-Z1P20 S2-106R4-Z1Q67-Z1Q6Q S2-106R4-Z1Q6F-Z1Q6R S2-106R4-Z1Q6J-Z1Q6Q S2-10716-Z1W4E S2-10732-Z1T61 S2-10768-Z1P20 S2-107DR-Z1Y64 S2-107Y8-Z1T5R S2-108HB-Z2701 S2-108HH S2-108HK-Z30BC S2-108HL-Z30BC S2-108J1 S2-108J8 S2-108R6 S2-108RE S2-108RH S2-108RN S2-1090Y-Z30EL S2-1097C-Z306Y S2-1097D-Z30 S2-1098T S2-109DC-Z30TN S2-109H9 S2-109HN S2-109KK S2-109ZS S2-109ZV S2-109ZX S2-10A00 S2-10A23 S2-10AF6 SIM28ML SIM28M-TE SIM33ELA-TE SIM5215 CONNECTOR SIM548 SIM68M SIM7000E-TE-KIT SIM7020E-SUB-KIT SIM7020G-SUB-KIT SIM7100E-EVM SIM7600E SIM7600E-H