


V: 2021.01 A7672X

SIMCom LTE Cat 1 Module



Product Description

A7672X is the LTE Cat 1 module that supports wireless communication modes of LTE/GSM/GPRS/EDGE. It supports maximum 10Mbps downlink rate and 5Mbps uplink rate.

A7672X adopts LCC+LGA form factor and is compatible with SIM7000/SIM7070 series (NB/Cat M modules), and SIM800A/SIM800F series (2G modules), which enables smooth migration from 2G/NB/Cat M products to LTE Cat 1 products, and greatly facilitates more compatible product design for the customer needs.

A7672X supports both multiple built-in network protocols and the drivers for main operation systems (USB driver for Windows, Linux and Android). The software functions, AT commands are compatible with the SIM800 series modules. A7672X also supports BLE* and GNSS* and it integrates abundant industrial standard interfaces with powerful expansibility, such as UART, USB, I2C and GPIO, which makes it perfectly suitable for main IOT applications such as telematics, POS, surveillance devices, industrial routers, and remote diagnostics etc.

Key Benefits

- Compact size with abundant interfaces
- Supports BLE and GNSS functions*
- Abundant software functions: FOTA, LBS, SSL
- Form factor is compatible with the SIM7000/SIM7070 series



Product		A7672S	A7672E	A7672SA
Form Factor		LCC+LGA	LCC+LGA	LCC+LGA
Dimensions(mm)		24.0*24.0*2.4	24.0*24.0*2.4	24.0*24.0*2.4
Fraguanay	LTE-FDD	B1/B3/B5/B8	B1/B3/B5/B7/B8/B20	B1/B2/B3/B4/B5/B7/B8/B28/B66
Frequency Bands	LTE-TDD	B34/B38/B39/B40/B41		
	GSM	900/1800MHz	900/1800MHz	850/900/1800/1900MHz
Temperature		-40°C ~ +85°C	-40°C ~ +85°C	-40°C ~ +85°C
Electrical Featu	ires			
Supply Voltage	(V)	3.4~ 4.2	3.4~ 4.2	3.4~ 4.2
Power	LTE	TBD	TBD	TBD
Consumption	GSM,BS_PA_	TDD	TDD	TDD
mA)	MFRMS=2	TBD	TBD	TBD
Data Transfer				
LTE(Mbps)		10(DL)/5(UL)	10(DL)/5(UL)	10(DL)/5(UL)
GPRS/EDGE(Kbps)		236.8(DL)/236.8(UL)	236.8(DL)/236.8(UL)	236.8(DL)/236.8(UL)
Software Featu				
Protocol		TCP/IP/IPV4/IPV6/Multi-PDP/FTP/ FTPS /HTTP/HTTPS/DNS	TCP/IP/IPV4/IPV6/Multi-PDP/FTP/ FTPS /HTTP/HTTPS/DNS	TCP/IP/IPV4/IPV6/Multi-PDP/FTP/ FTPS /HTTP/HTTPS/DNS
TLS		•	•	•
MQTT		•	•	•
File System		•	•	•
Audio Record/Play		0	0	0
TTS		•	•	•
LBS		•	•	•
FOTA		•	•	•
Android RIL		Android 5.0/6.0/7.0/8.0/9.0	Android 5.0/6.0/7.0/8.0/9.0	Android 5.0/6.0/7.0/8.0/9.0
USB Driver		Microsoft Windows 7/8/10	Microsoft Windows 7/8/10	Microsoft Windows 7/8/10
		Linux/Android	Linux/Android	Linux/Android
WWAN (RNDIS)		•	•	•
ECM		•	•	•
Embedded AT		0	0	0
Firmware Upgrade		USB/FOTA	USB/FOTA	USB/FOTA
nterfaces				
SIM Card		1.8V/3.0V	1.8V/3.0V	1.8V/3.0V
UART		•	•	•
USB		•	•	•
PCM		0	0	0
ADC		•	•	•
GPIO		•	•	•
I2C				-
GNSS		•	•	•
BLE		0	0	0
		0	0	0
Certification				
Certification			CE-RED*/RoHS*/ REACH*	Anatel*/RoHS*/ REACH*

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Simcom manufacturer:

Other Similar products are found below:

\$2-1050J-Z0K4J \$2-105Y0-Z1E0G \$2-10640-Z1G0D \$2-10672-Z1L85 \$2-10686-Z1L1D \$2-106BA-Z1P20 \$2-106R4-Z1Q67-Z1Q6Q \$2-106R4-Z1Q6F-Z1Q6R \$2-106R4-Z1Q6J-Z1Q6Q \$2-10716-Z1W4E \$2-10732-Z1T61 \$2-10768-Z1P20 \$2-107DR-Z1Y64 \$2-107Y8-Z1T5R \$2-108HB-Z2701 \$2-108HH \$2-108HK-Z30BC \$2-108HL-Z30BC \$2-108J1 \$2-108J8 \$2-108R6 \$2-108RE \$2-108RH \$2-108RN \$2-1090Y-Z30EL \$2-1097C-Z306Y \$2-1097D-Z30 \$2-1098T \$2-109DC-Z30TN \$2-109H9 \$2-109HN \$2-109KK \$2-109ZS \$2-109ZV \$2-109ZX \$2-10A00 \$2-10A23 \$2-10AF6 \$SIM28ML \$SIM28M-TE \$SIM33ELA-TE \$SIM5215 CONNECTOR \$SIM548 \$SIM68M \$SIM7000E-TE-KIT \$SIM7020E-SUB-KIT \$SIM7020G-SUB-KIT \$SIM7100E-EVM \$SIM7600E \$SIM7600E-H\$