

150-2 AC Amp-Clamp Adapters

Amp-Clamp Adapters

Amp-Clamp current probes, used with analog VOMS provide accurate measurements of high AC current found in power systems and related control circuitry.

The Amp-Clamp jaws are closed over a conductor in the circuit and the current load is indicated on the connected meter.

The 150-2 has six ranges (up to 300 ACA) and is available with banana and reverse banana plugs.



Specifications	
AC Amp-Clamp Adapter	
Model	150-2
Ranges	5A, 10A, 50A, 100A, 250A (on 2.5 VAC Meter Range), 6A, 12A, 30A, 60A, 120A, 300A (on 3 VAC Meter Range)
Accuracy	± 3% Full Scale

PHYSICAL

Dimensions: 7.8" x 3" x 1.1"

Weight: 12 oz.

Max. Cable Dimension: 1.125" diameter

Max. Bus Bar Dimensions: 2.38" x 0.38"

Ordering Information	
Amp-Clamp	Catalog No.
150-2 AC Clamp, VOM Banana Plug	00541
150-2 AC Clamp, VOM Reverse Plug	00545
Cable, replacement, reverse banana (used with 00545)	00529
Cable, replacement, banana (used with 00541)	00533

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LAN/Telecom/Cable Testing](#) category:

Click to view products by [Simpson](#) manufacturer:

Other Similar products are found below :

[1673606-1](#) [SEFRAM95](#) [KE7100](#) [KE8000](#) [POECHECK](#) [TCT-1620](#) [TCT-2210](#) [TCT-680](#) [TCT-2690PRO](#) [TESTER-MS6811](#) [TESTER-MS6812](#) [262](#) [N044-000-R](#) [MCT-468](#) [TM-901N](#) [TM-902](#) [TM-903](#) [LAN-1](#) [24-517](#) [CT20](#) [40180](#) [TG20](#) [CLM-1000E](#) [CLM-1000](#) [HDMI-100](#) [TEP-100](#) [KE3100](#) [KE3150](#) [KE501](#) [KE7000](#) [KE801](#) [KE850](#) [VDV500-123](#) [VDV500-820](#) [VDV501211](#) [VDV501212](#) [VDV501213](#) [VDV501214](#) [VDV501215](#) [VDV501216](#) [VDV501217](#) [VDV501218](#) [VDV501220](#) [VDV501221](#) [VDV501222](#) [VDV501-851](#) [VDV501-852](#) [VDV501-853](#) [VDV512-007](#) [VDV512-100](#)