

505 High Voltage Insulation Tester

Measures Insulation Resistances Up To 1 T Ohm

Simpson's Model 505 High Voltage Insulation Tester is capable of measuring insulation resistances from 10 kilohms to 1 teraohm with eight selectable test voltages up to 5000 V.

As a safety feature, the insulation tester acts as an AC/DC voltmeter to measure the absence of voltage in networks up to 2000V.

For added safety, the cables are permanently attached, preventing possible injury that could occur by the accidental removal of the cables.

The Model 505 features automatic discharging capability of capacitive units under test and a lock in test switch, for hands-free operation.



An optional guard cable is available to minimize surface leakage errors. Two LEDs indicate the selected measuring range, and one LED signifies valid measurements.

Each tester comes in a padded carrying case with permanently connected cables and test probes, 2 alligator clips and a plug-in battery module with batteries.

- Eight Test Voltages: 100, 250, 500, 1000, 1500, 2000, 2500, and 5000 VDC
- High Sensitivity, Direct Resistance Reading to 1T Ω (1,000,000 M Ω), no Multipliers
- Voltage Measurement to 2000 V AC/DC
- Battery Powered
- Built in Battery Test and Battery Charge Indicator

| Ordering Information | | |
|------------------------------------|----------------|--|
| Accessories | Catalog Number | |
| 505 High-Voltage Insulation Tester | 12505 | |
| Guard Cable with Alligator Clip | 45065 | |
| Replacement Alligator Clips (pair) | 45066 | |

Rev. 04-15



505 High Voltage Insulation Tester

| Measuring Ranges | } | | | | |
|---------------------------------|--------------------|--------------------|-------------------------|------------------------|--|
| Insulation Resistance | | | | | |
| Nominal/Open-Circuit Voltage | Measuring Range | Nominal Current | Short Circut Current | Intrinsic Error (1) | |
| 100V | | | 1.3 mA | ± 2.5% | |
| 250V | 100KΩ to 100MΩ | 1 mA | | | |
| 500V | | | | | |
| 1000V | | | | | |
| 100V / 1500V | | 0.7 mA | | | |
| 250V / 2000V | 10KΩ to 1 TΩ | 0.5 mA | 1.2 m 1 | . E0/ | |
| 500V / 2500V | | 0.4 mA | 1.3 mA | ± 5% | |
| 1000V / 5000V | | 0.1 mA | | | |
| (1) Referring to scale len | | | | | |

| Direct and Alternating Voltage | | | | |
|--------------------------------|---------------|------------------------|----------------------|------------------------|
| Measuring Range | Frequency | Internal Resistance | Maximum Overload | Intrinsic Error (1) |
| 0 to 2000V AC/DC | 15Hz to 500Hz | 5ΜΏ | 2200V AC/DC max. 10s | ± 5% |
| (1) Referring to scale length | | | | |

Rev. 04-15

2



505 High Voltage Insulation Tester

| Specifications | | | |
|---|---|--|--|
| REFERENCE CONDITIONS | | | |
| Ambient Temperature | 73°F (23°C) ± 4°F (2°C) | | |
| Relative Humidity | 45 to 55% | | |
| Measurement Magnitude Frequency | 60Hz (voltage measurements) | | |
| Line Voltage Waveform | Sine, deviation between effective and rectified value ≈ 1% | | |
| Battery Voltage | 9V ± 1% | | |
| Operating Position | Horizontal | | |
| ELECTROMA CNETIC COMPATIBILITY EN | 10 | | |
| ELECTROMAGNETIC COMPATIBILITY EM | - | | |
| Interference Emission | EN 50081-1: 1992 | | |
| Interference Immunity | EN 50082-1: 1992 | | |
| ELECTRICAL SAFETY | | | |
| Designed to IEC 1010-1 Protection Class | II | | |
| Test Voltage | ≈ 8.5Kv | | |
| Overvoltage Classification | II | | |
| Pollution Degree | 2 | | |
| Protection | IP 52 | | |
| AMBIENT CONDITIONS | | | |
| Operating Temp. Range | 32°F (0°C) to 104°F (40°C) | | |
| Storage Temp. Range | -4°F (-20°C) to 140°F (60°C) (without batteries) | | |
| Relative Humidity | Max. 75%, condensation must be avoided | | |
| Batteries | 6 ea. 1.5V "D" size batteries | | |
| Working Range | 6 to 10V | | |
| Battery Service Life | 100 hours for no-load and intermittent operation, 7500 measurements for test voltage of 1000V with measure resistance of 1M Ω , 15,000 measurements for test voltage of 500V with measure resistance of 500K Ω , measurement of 5 sec pause 25 sec. | | |
| MECHANICAL DESIGN | | | |
| Dimensions | W 11.41" (290mm) x D 9.8" (250mm) x H 5.5" (140mm) | | |
| Weight | 7.5 lbs. (1.6kg) (with batteries) | | |
| Specifications subject to change | without notice | | |

3

Rev. 04-15

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Insulation Testers/Megohmmeters category:

Click to view products by Simpson manufacturer:

Other Similar products are found below:

FLK-1662-US AX-T2200 AX-T2400 BM878 UT511 UT526 UT512 MG320 C.A 6501 C.A 6503 C.A 6524 C.A 6526 UT501B UT502A UT505A UT513A UT522 UT582+ AX-T1220 380260 380363 380395 MG500 1553041 FLUKE-1503 FLUKE-1507 K7GE-MG1 K7GE-MGMD K7GE-MGMA 2730991 BM15 307A 308A 19249 U1452A