

Image may differ from product. See technical specification for details.

SY 504 M

Pillow block housing for insert bearings, cast iron, ISO standards

Pillow (plummer) block housings are designed to accommodate an insert bearing. The cast iron housings are strong, stiff and cost-effective. They are suitable for most applications and can be bolted directly to a support surface.

- Accommodate heavy loads in different directions
- High degree of stiffness
- Narrow design

Overview

Dimensions

| Spherical seating diameter | 47 mm |
|------------------------------------|---------|
| Centre height (pillow block) | 33.3 mm |
| Housing overall width | 32 mm |
| Centre distance between bolt holes | 97 mm |

Logistics


| Product net weight | 0.424 kg |
|--------------------|-------------|
| eClass code | 23-05-08-02 |
| UNSPSC code | 31171536 |


Properties

| Housing type | Pillow block |
|------------------------------------|--------------|
| Number of bolt holes for fasteners | 2 |
| Fastening bolt hole type | Plain |
| Material, housing | Cast iron |
| Coating | Without |
| Relubrication hole | With |
| Grease fitting | With |

Technical specification

Material Cast iron





Dimensions

| Da | 47 mm | Diameter of spherical seat |
|----------------|-------------|--------------------------------------|
| А | 32 mm | Base width |
| A ₁ | 21 mm | Top width |
| A ₅ | 20.5 mm | Standout of end cover |
| Н | 33.3 mm | Height of spherical seat centre |
| H ₁ | 14 mm | Foot height |
| H ₂ | 64.5 mm | Overall height |
| J | 97 mm | Distance between attachment bolts |
| J | max. 106 mm | Distance between attachment bolts |
| J | min. 88 mm | Distance between attachment bolts |
| L | 127 mm | Overall length |
| N | 11.5 mm | Width of attachment bolt hole |
| N ₁ | 20.5 mm | Length of attachment bolt hole |

THREADED HOLE

| R_{G} | 1/4-28 UNF | Housing thread for the grease fitting |
|----------------|------------|--|
| R ₁ | 2 mm | Axial position of the housing thread |
| Rα | 45° | Angular position of the housing thread |

GREASE FITTING

| D _N | 6.5 mm | Diameter of head sphere of grease fitting |
|-----------------|--------|---|
| SW _N | 7 mm | Hexagonal key size for the grease fitting |

DOWEL PINS

| J ₆ | 118 mm | Distance between dowel pins |
|----------------|---------|---|
| J_7 | 11.5 mm | Axial offset of dowel pins |
| N ₄ | 2 mm | Recommended diameter for dowel pins |

Mass

Mass housing 0.41 kg

Mounting information

| Recommended diameter for attachment bolts, mm | G | 10 mm |
|---|---|----------|
| Recommended diameter for attachment bolts, inch | G | 0.375 in |

Associated products

Compatible products

Recommended product

End cover for bearing units ECY 204

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Screws & Fasteners category:

Click to view products by SKF manufacturer:

Other Similar products are found below:

5721-1440-1/4-SS 0098.0094 0098.9206 59781-6 0098.9212 6292-1 690432-1 699161-000 700989 7230-3 72609-02 CAPTIVE JACK

SCREW 73542-02 CAPTIVE SHORT THUMBSCREW 745564-1 7680 809704-1 8700 8860220 9521 992763-3 1-18024-0 A168P1 1
24921-1 125416-1 1301810313 1-306131-6 1301830042 1458 1-59781-3 18029-4 NBX-10953 NUT-16-3P-HEX-NICKEL 20993.45098

21004-1 21009-4 21014-5 21021-2 CA24037A01 22987-4 240632-1 240632-2 89506-9801 2504 9031 9-1393249-2 2.5NZPNBU 26
0048PP 27210-1 27210-8 9318 9520