

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**Applications**

- IEEE802.11b DSSS WLAN
- IEEE802.11g OFDM WLAN
- IEEE802.11a OFDM WLAN
- IEEE802.11n WLAN
- Access Points, PCMCIA, PC cards

**Features**

- All RF ports matched to 50  $\Omega$
- Integrated 2.4 GHz PA, 5 GHz PA, T/R switch, 2.5GHz LNA, 5GHz LNA
- Integrated Power Detector for each TX Chain
- 19 dBm O/P Power, 802.11b, 11 Mbits, ACPR = 35 dBc
- 18 dBm @ 3.0 % EVM, 802.11g, 54 Mbits
- 16 dBm @ 3.0 % EVM, 802.11a, 54 Mbits
- Single supply voltage: 3.3 V  $\pm$  10 %
- Lead free, Halogen free, RoHS compliant, MSL 1
- 4mm x 4mm x 0.9mm, QFN Package

**Ordering Information**

| Part No.    | Package    | Remark         |
|-------------|------------|----------------|
| SE5512L     | 24 pin QFN | Samples        |
| SE5512L-R   | 24 pin QFN | Tape and Reel  |
| SE5512L-EK1 | N/A        | Evaluation kit |

**Product Description**

The SE5512L is a complete 802.11a/b/g/n WLAN RF front-end module providing all the functionality of the power amplifiers, filtering, power detector, T/R switch, diplexers, LNA and associated matching. The SE5512L provides a complete 2.4 GHz and 5 GHz WLAN RF solution from the output of the transceiver to the antenna in an ultra compact form factor.

Designed for ease of use, all RF ports are matched to 50  $\Omega$  to simplify PCB layout and the interface to the transceiver RFIC. The SE5512L also includes a transmit power detector with 20 dB of dynamic range for each transmit chain. Each transmit chain has a separate digital enable control for transmitter power ramp on/off control. The power ramp rise/fall time is less than 0.7  $\mu$ sec.

The device also provides a notch filter from 3.260-3.267 GHz and 3.28-3.89 GHz prior to the input of each 2.4 GHz and 5 GHz power amplifiers, respectively.

The SE5512L packaged in 4mm x 4mm x 0.9mm, Halogen free, Lead free, ROHS compliant, MSL 3 QFN package.

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**Functional Block Diagram**




Figure 1: SE5512L Functional Block Diagram

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**Pin Out Diagram**




Figure 2: SE5512L Pin Out (Top View Through Package)

**Pin Out Description**

| Pin No. | Name | Description                     |
|---------|------|---------------------------------|
| 1       | C0   | Switch Control                  |
| 2       | Rg   | 2.4 GHz RF Receive Output       |
| 3       | Ra   | 5 GHz RF Receive Output         |
| 4       | Tg   | 2.4 GHz RF Transmit Input       |
| 5       | Ta   | 5 GHz RF Transmit Input         |
| 6       | Det  | 2.4/5 GHz Power Detector Output |
| 7       | ENa  | 5 GHz Power Amplifier Enable    |
| 8       | ENg  | 2.4 GHz Power Amplifier Enable  |
| 9       | VCC  | Supply Voltage                  |
| 10      | VCC  | Supply Voltage                  |
| 11      | VCC  | Supply Voltage                  |
| 12      | VCC  | Supply Voltage                  |

| Pin No. | Name | Description    |
|---------|------|----------------|
| 13      | GND  | Ground         |
| 14      | GND  | Ground         |
| 15      | GND  | Ground         |
| 16      | GND  | Ground         |
| 17      | ANT  | Antenna        |
| 18      | GND  | Ground         |
| 19      | GND  | Ground         |
| 20      | GND  | Ground         |
| 21      | GND  | Ground         |
| 22      | GND  | Ground         |
| 23      | VCC  | Supply Voltage |
| 24      | C1   | Switch Control |

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**Absolute Maximum Ratings**

These are stress ratings only. Exposure to stresses beyond these maximum ratings may cause permanent damage to, or affect the reliability of the device. Avoid operating the device outside the recommended operating conditions defined below. This device is ESD sensitive. Handling and assembly of this device should be at ESD protected workstations.

| Symbol             | Definition                                   | Min. | Max.  | Unit |
|--------------------|--|------|-------|------|
| V <sub>CC</sub>    | Supply Voltage                               | -0.3 | 3.6   | V    |
| PU                 | ENa, ENg, C0, C1                             | -0.3 | 3.6   | V    |
| TX <sub>RF</sub>   | Ta, Tg, ANT terminated in 6:1 load or better | -    | 12.0  | dBm  |
| T <sub>A</sub>     | Operating Temperature Range                  | -40  | 85    | °C   |
| T <sub>STG</sub>   | Storage Temperature Range                    | -40  | 150   | °C   |
| ESD <sub>HBM</sub> | JEDEC JESD22-A114 all pins                   | -    | 1,000 | V    |

**Recommended Operating Conditions**

| Symbol          | Parameter           | Min. | Typ. | Max. | Unit |
|-----------------|---------------------|------|------|------|------|
| V <sub>CC</sub> | Supply Voltage      | 3.0  | 3.3  | 3.6  | V    |
| T <sub>A</sub>  | Ambient Temperature | -40  | 25   | 85   | °C   |

**DC Electrical Characteristics**

Conditions: V<sub>CC</sub> = 3.3 V, T<sub>A</sub> = 25 °C, as measured on Skyworks Solutions' SE5512L-EV1 evaluation board (de-embedded to device), all unused ports terminated with 50 ohms, unless otherwise noted

| Symbol              | Parameter                             | Conditions  | Min. | Typ. | Max. | Unit |
|---------------------|---------------------------------------|---|------|------|------|------|
| I <sub>CC-G</sub>   | Total 802.11g Transmit Supply Current | P <sub>OUT</sub> = 18 dBm, 54 Mbps OFDM signal, 64 QAM<br>ENg = 3.3 V, ENa = 0 V,<br>100% duty cycle    | -    | 150  | -    | mA   |
| I <sub>CC-B</sub>   | Total 802.11b Transmit Supply Current | P <sub>OUT</sub> = 19 dBm, 11 Mbps CCK signal, BT = 0.45,<br>ENg = 3.3 V, ENa = 0 V,<br>100% duty cycle | -    | 175  | -    | mA   |
| I <sub>CC-A</sub>   | Total 802.11a Transmit Supply Current | P <sub>OUT</sub> = 16 dBm, 54 Mbps OFDM signal, 64 QAM,<br>ENa = 3.3 V, ENg = 0 V,<br>100% duty cycle   | -    | 210  | -    | mA   |
| I <sub>CC-Rxa</sub> | Total Icc in Rx 5G band               | 5G LNA enabled  | -    | 19   | -    | mA   |
| I <sub>CC-Rxg</sub> | Total Icc in Rx 2G band               | 2G LNA enabled  | -    | 18   | -    | mA   |
| I <sub>CC-OFF</sub> | Total Supply Current                  | No RF, ENg = ENa = 0 V  | -    | 50   | 180  | µA   |

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**PA Logic Characteristics**

Conditions:  $V_{CC} = 3.3\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5512L-EV1 evaluation board (de-embedded to device), all unused ports terminated with 50 ohms, unless otherwise noted.

| Symbol    | Parameter                                   | Conditions             | Min. | Typ. | Max.     | Unit          |
|-----------|---|------------------------|------|------|----------|---------------|
| $V_{ENH}$ | Logic High Voltage for ENg, ENa (Module On) | -                      | 1.8  | -    | $V_{CC}$ | V             |
| $V_{ENL}$ | Logic Low Voltage ENg, ENa (Module Off)     | -                      | 0    | -    | 0.4      | V             |
| $I_{ENH}$ | Input Current Logic High Voltage (ENg, ENa) | -                      | -    | 50   | 100      | $\mu\text{A}$ |
| $I_{ENL}$ | Input Current Logic Low Voltage (ENg, ENa)  | $V_{CC} = 0.4\text{V}$ | -    | 0    | 40       | $\mu\text{A}$ |

**Switch/LNA Logic Characteristics**

Conditions:  $V_{CC} = 3.3\text{ V}$ ,  $V_{EN} = 0\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5512L-EV1 evaluation board (de-embedded to device), all unused ports terminated with 50 ohms, unless otherwise noted.

| Symbol         | Parameter                                | Conditions                                    | Min. | Typ. | Max. | Unit          |
|----------------|--|---|------|------|------|---------------|
| $V_{CTL\_ON}$  | Control Voltage C0, C1 (On State)        | -   | 3.0  | -    | 3.6  | V             |
| $V_{CTL\_OFF}$ | Control Voltage C0, C1 (OFF State)       | -   | 0.0  | -    | 0.4  | V             |
| $I_{CTL\_ON}$  | Switch Control Bias Current (RF Applied) | On pin (TX, RX) being driven high. RF Applied | -    | -    | 400  | $\mu\text{A}$ |
| $I_{CTL\_ON}$  | Switch Control Bias Current (No RF)      | On pin (TX, RX) being driven high. No RF      | -    | -    | 30   | $\mu\text{A}$ |

**Switch & LNA Control Logic Table**

| C0               | C1             | EnG       | EnA       | Tg ↔ ANT  | Ta ↔ ANT  | Rg ↔ ANT      | Ra ↔ ANT      |
|------------------|----------------|-----------|-----------|---|-----------|---------------|---------------|
| $V_{CTL\_OFF}$   | $V_{CTL\_ON}$  | $V_{ENH}$ | $V_{ENL}$ | <b>ON</b>   | OFF       | OFF           | OFF           |
| $V_{CTL\_OFF}$   | $V_{CTL\_OFF}$ | $V_{ENL}$ | $V_{ENH}$ | OFF   | <b>ON</b> | OFF           | OFF           |
| $V_{CTL\_ON}$    | $V_{CTL\_OFF}$ | $V_{ENL}$ | $V_{ENL}$ | OFF   | OFF       | OFF           | <b>LNA ON</b> |
| $V_{CTL\_ON}$    | $V_{CTL\_ON}$  | $V_{ENL}$ | $V_{ENL}$ | OFF   | OFF       | <b>LNA ON</b> | OFF           |
| $V_{CTL\_OFF}$   | $V_{CTL\_OFF}$ | $V_{ENL}$ | $V_{ENL}$ | Stand By Mode, PAs and LNAs OFF – Low Current Consumption |           |               |               |
| All Other States |                |           |           | Not Supported   |           |               |               |

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**2.4 GHz AC Electrical Characteristics**

**2.4 GHz Transmit Characteristics**

Conditions:  $V_{CC} = 3.3\text{ V}$ ,  $ENg = 3.3\text{ V}$ ,  $ENa = C0 = C1 = 0\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5512L-EV1 evaluation board, all unused ports terminated with 50 ohms, unless otherwise noted.

| Symbol           | Parameter                             | Condition   | Min.   | Typ. | Max.  | Unit          |
|------------------|---------------------------------------|---|--|------|-------|---------------|
| $F_{IN}$         | Frequency Range                       | -   | 2400   | -    | 2500  | MHz           |
| $P_{802.11g}$    | Output power                          | 54 Mbps OFDM signal, 64QAM, EVM = 3.0 %   | -  | 18   | -     | dBm           |
| $P_{802.11b}$    | Output power                          | 11 Mbps CCK signal, BT = 0.45<br>ACPR( $\pm 11\text{MHz}$ offset) < -35<br>ACPR( $\pm 22\text{MHz}$ offset) < -56 | -  | 19   | -     | dBm           |
| $P_{1dB}$        | P1dB                                  | -   | 23   | 25.5 | -     | dBm           |
| $S_{21}$         | Small Signal Gain                     | -   | 25   | 28   | 30    | dB            |
| $\Delta S_{21}$  | Small Signal Gain Variation Over Band | -   | -  | 1.0  | 2.0   | dB            |
| $S_{213.2}$      | Gain at Ref-VCO                       | 3200.00 to 3300.00 MHz  | -  | -    | 0     | dB            |
| 2f,3f            | Harmonics                             | $P_{out} \leq 19\text{ dBm}$ , 1Mbps, CCK   | -  | -    | -45.2 | dBm/MHz       |
| $t_r$            | Rise Time                             | 10 % to 90% of final output power level   | -  | -    | 0.5   | $\mu\text{s}$ |
| $t_{dr}, t_{df}$ | Delay and rise/fall Time              | 50 % of $V_{EN}$ edge and 90/10 % of final output power level   | -  | -    | 0.5   | $\mu\text{s}$ |
| $S_{11}$         | Input Return Loss                     | -   | 8  | 10   | -     | dB            |
| STAB             | Stability                             | CW, $P_{OUT} = 19\text{ dBm}$<br>0.1 GHz – 21 GHz<br>Load VSWR = 6:1  | All non-harmonically related outputs less than -42 dBm/MHz |      |       |               |
| $R_u$            | Ruggedness                            | $T_g = 12\text{ dBm}$ , ANT load varies over 6:1 VSWR   | No Irreversible damage                                     |      |       |               |

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**2.4 GHz Receive Characteristics**

Conditions:  $V_{CC} = C0 = C1 = 3.3\text{ V}$ ,  $ENg = ENa = 0\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5512L-EV1 evaluation board, all unused ports terminated with 50 ohms, unless otherwise noted.

| Symbol          | Parameter                  | Condition  | Min. | Typ. | Max. | Unit |
|-----------------|----------------------------|--|------|------|------|------|
| $F_{OUT}$       | Frequency Range            | -  | 2400 | -    | 2500 | MHz  |
| $S_{21}$        | Receive Gain, LNA Enabled. | 2400 – 2485 MHz  | 10   | 15   | -    | dB   |
| $\Delta S_{21}$ | Gain Variation             | 2400 – 2485 MHz, Over any 40MHz band                   | -    | 0.2  | 0.5  | dB   |
| NF              | Noise Figure               | De-embedded to device                                  | -    | 2.5  | 2.8  | dB   |
| INT             | Interferer @1710-1990MHz   | With this input, IIP3 can only degrade by 1dB          | -10  | -    | -    | dBm  |
| $S_{11}$        | Input Return Loss          | -  | -    | 8    | -    | dB   |
| IP1dB           | Input P1dB                 | $C0 = 3.3\text{ V}$                                    | -    | -7   | -    | dBm  |
| $T_{EN}$        | Enable Time                | 10% to 90% of RX RF power, from time that C0 is at 50% | -    | 500  | -    | nsec |

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**5 GHz AC Electrical Characteristics**

**5 GHz Transmit Characteristics**

Conditions:  $V_{CC} = 3.3\text{ V}$ ,  $E_{NA} = 3.3\text{ V}$ ,  $E_{NG} = C_0 = C_1 = 0\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5512L-EV1 evaluation board, all unused ports terminated with 50 ohms, unless otherwise noted.

| Symbol           | Parameter                                       | Condition  | Min.   | Typ. | Max.  | Unit          |
|------------------|---|--|--|------|-------|---------------|
| $F_{IN}$         | Frequency Range                                 | -  | 4900   | -    | 5875  | MHz           |
| $P_{802.11a}$    | Nominal Output Power                            | 54 Mbps OFDM signal, 64 QAM, EVM = 3.0 %                                 | -  | 16   | -     | dBm           |
| $P_{1dB}$        | P1dB  | -  | 21   | 22.5 | -     | dBm           |
| $S_{21}$         | Small Signal Gain                               | -  | 24   | -    | 32    | dB            |
| $\Delta S_{21}$  | Small Signal Gain Variation Over 40 MHz Channel | -  | -  | -    | 0.5   | dB            |
|                  | Small Signal Gain Variation Over sub-bands      | -  | -  | -    | 3     | dB            |
| $S_{213.2}$      | Gain  | 3280 to 3900 MHz   | -  | 3    | 9     | dB            |
| 2f,3f            | Harmonics                                       | $P_{out} \leq 16\text{ dBm typ}$ ,<br>54Mbps, 802.11a OFDM               | -  | -    | -45.2 | dBm/MHz       |
| $t_r$            | Rise Time                                       | 10 % to 90% of final output power level                                  | -  | -    | 0.5   | $\mu\text{s}$ |
| $t_{dr}, t_{df}$ | Delay and rise/fall Time                        | 50 % of $V_{EN}$ edge and 90/10 % of final output power level            | -  | -    | 0.5   | $\mu\text{s}$ |
| $S_{11}$         | Input Return Loss                               | -  | 5  | 7    | -     | dB            |
| STAB             | Stability                                       | 64 QAM, $P_{OUT} = 16\text{ dBm}$<br>0.1 GHz – 21 GHz<br>Load VSWR = 6:1 | All non-harmonically related outputs less than -42 dBm/MHz |      |       |               |
| $R_u$            | Ruggedness                                      | $TX_a = 12\text{ dBm}$ , ANT load varies over 6:1 VSWR                   | No Irreversible damage                                     |      |       |               |



**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**5 GHz Receive Characteristics**

Conditions:  $V_{CC} = C0 = 3.3\text{ V}$ ,  $ENg = ENa = C1 = 0\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5512L-EV1 evaluation board, all unused ports terminated with 50 ohms, unless otherwise noted.

| Symbol          | Parameter       | Condition  | Min. | Typ. | Max. | Unit |
|-----------------|-----------------|--|------|------|------|------|
| $F_{OUT}$       | Frequency Range | -  | 4900 | -    | 5850 | MHz  |
| $S_{21}$        | Receive Gain    | 4900 – 5850 MHz  | 10   | 12   | -    | dB   |
| $\Delta S_{21}$ | Gain Variation  | 4900 – 5850 MHz, Over any 40MHz band                   | -    | 1    | -    | dB   |
| NF              | Noise Figure    | De-embedded to device                                  | -    | 2.8  | 3.0  | dB   |
| $S_{11}$        | Return Loss     | -  | 10   | 15   | -    | dB   |
| IP1dB           | Input P1dB      | $C0 = 3.3\text{ V}$                                    | -6.5 | -    | -    | dBm  |
| $T_{EN}$        | Enable Time     | 10% to 90% of RX RF power, from time that C0 is at 50% | -    | 500  | -    | nsec |

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**2.4 GHz Power Detector Characteristic**

Conditions:  $V_{CC} = 3.3\text{ V}$ ,  $ENg = 3.3\text{ V}$ ,  $ENa = C0 = C1 = 0\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5512L-EV1 evaluation board, all unused ports terminated with 50 ohms, unless otherwise noted.

| Symbol               | Parameter  | Condition                            | Min. | Typ. | Max. | Unit |
|----------------------|--|--------------------------------------|------|------|------|------|
| F <sub>OUT</sub>     | Frequency Range                                    | -                                    | 2400 | -    | 2500 | MHz  |
| PDR                  | Power detect range, peak power                     | Measured at ANT0 or ANT1             | 0    | -    | 22   | dBm  |
| PDZ <sub>OUT</sub>   | DC Output impedance                                | -                                    | -    | 2.7  | 3    | kΩ   |
| PDV <sub>P21</sub>   | Output Voltage, P <sub>OUT</sub> = 21dBm           | -                                    | -    | 0.85 | -    | V    |
| PDV <sub>P18</sub>   | Output Voltage, P <sub>OUT</sub> = 18dBm           | -                                    | -    | 0.65 | -    | V    |
| PDV <sub>pnoRF</sub> | Output Voltage, P <sub>OUT</sub> = No RF           | -                                    | -    | 0.35 | -    | V    |
| LPF <sub>-3dB</sub>  | Power detect low pass filter -3dB corner frequency | Load = high impedance<br>Typ: 500 kΩ | -    | 1500 | -    | kHz  |





Figure 3: SE5512L Power Detector vs. Output Power over Frequency (CW Signal)

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**5 GHz Power Detector Characteristic**

Conditions:  $V_{CC} = 3.3\text{ V}$ ,  $E_{Na} = 3.3\text{ V}$ ,  $E_{Ng} = C0 = C1 = 0\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5512L-EV1 evaluation board, all unused ports terminated with 50 ohms, unless otherwise noted.

| Symbol              | Parameter  | Condition                                    | Min. | Typ. | Max. | Unit       |
|---------------------|--|--|------|------|------|------------|
| F <sub>OUT</sub>    | Frequency Range                                    | -  | 4900 | -    | 5850 | MHz        |
| PDR                 | Power detect range, peak power                     | Measured at ANT                              | 0    | -    | 21   | dBm        |
| PDZ <sub>OUT</sub>  | DC Output impedance                                | -  | -    | 2.7  | 3.0  | k $\Omega$ |
| PDV <sub>p18</sub>  | Output Voltage, P <sub>OUT</sub> = 18dBm           | -  | -    | 0.78 | -    | V          |
| PDV <sub>p16</sub>  | Output Voltage, P <sub>OUT</sub> = 16dBm           | -  | -    | 0.65 | -    | V          |
| PDV <sub>NoRF</sub> | Output Voltage, P <sub>OUT</sub> = No RF           | -  | -    | 0.35 | -    | V          |
| LPF <sub>-3dB</sub> | Power detect low pass filter -3dB corner frequency | Load = high impedance<br>Typ: 500 k $\Omega$ | -    | 1500 | -    | kHz        |



**Figure 4: Preliminary SE5512L Power Detector vs. Output Power over Frequency (CW Signal)**



SKYWORKS®

DATA SHEET  
SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End  
Preliminary Information

Package Drawing





Figure 5: Package Drawing: Topside

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**Recommended Land and Solder Patterns**




**Figure 6: Recommended Land and Solder Patterns**

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**


**Package Handling Information**

Because of its sensitivity to moisture absorption, instructions on the shipping container label must be followed regarding exposure to moisture after the container seal is broken, otherwise, problems related to moisture absorption may occur when the part is subjected to high temperature during solder assembly. The SE5512L is capable of withstanding a Pb free solder reflow. Care must be taken when attaching this product, whether it is done manually or in a production solder reflow environment. If the part is manually attached, precaution should be taken to insure that the device is not subjected to temperatures above its rated peak temperature for an extended period of time. For details on both attachment techniques, precautions, and handling procedures recommended, please refer to:

- “Quad Flat No-Lead Module Solder Reflow & Rework Information”, *Document Number QAD-00045*
- “Handling, Packing, Shipping and Use of Moisture Sensitive QFN”, *Document Number QAD-00044*



**Product Branding**




**Figure 7: SE5512L Branding Information**

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**Tape and Reel Information**

| Parameter        | Value          |
|------------------|----------------|
| Devices Per Reel | 3000           |
| Reel Diameter    | 13 inches      |
| Tape Width       | 12 millimeters |




**Figure 8: Detailed Tape and Reel Information (All dimensions in Millimeters)**

**DATA SHEET**  
**SE5512L: Dual-Band 802.11a/b/g/n Wireless LAN Front-End**  
**Preliminary Information**

**Document Change History**

| Revision | Date         | Notes  |
|----------|--------------|--|
| 1.0      | Aug 10, 2010 | Create   |
| 1.1      | Sep 30, 2010 | Updated 2GHz LNA gain variation over a single channel.<br>Updated EN (high) current limit<br>Updated 5GHz Gain (min) limit |
| 1.2      | Oct 7, 2010  | Added "Stand By" mode setting to switch control logic table  |
| 1.3      | Jan 27, 2011 | Updated MSL rating to MSL1<br>Updated ESD rating to Class 1C   |
| 1.4      | Sep 25, 2011 | Updated recommended operating conditions to Industrial level   |
| 1.5      | Feb 17, 2012 | Updated marking diagram  |
| 1.6      | Apr 03, 2012 | Updated with Skyworks logo and disclaimer statement  |



Copyright © 2012 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks, the Skyworks symbol, and "Breakthrough Simplicity" are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at [www.skyworksinc.com](http://www.skyworksinc.com), are incorporated by reference.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Front End](#) category:*

*Click to view products by [Skyworks](#) manufacturer:*

Other Similar products are found below :

[SE2622L-R](#) [BGM1032N7E6327XUSA1](#) [LX5586LL](#) [SKY85703-11](#) [LX5586HLL](#) [LX5586ALL](#) [SKY66111-21](#) [SKY65728-11](#) [SKY68000-31](#)  
[SKY85308-11](#) [SKY85302-11](#) [SKY65724-11](#) [ADTR1107ACCZ](#) [LMP91051MTX/NOPB](#) [SE5501L-R](#) [QPF4519SR](#) [SE5503A-R](#)  
[ADA8282WBCPZ](#) [ADRF5545ABCPZN](#) [ADRF5545ABCPZN-R7](#) [AD8283WBCPZ](#) [AD8284WCSVZ](#) [ADRF5547BCPZN](#)  
[ADRF5547BCPZN-R7](#) [ADRF5549BCPZN](#) [ADRF5549BCPZN-R7](#) [HV7350K6-G](#) [SE5516A-R](#) [MCP2030-I/SL](#) [MAX2009ETI+](#)  
[MAX2078CTK+](#) [MAX2335ETI+](#) [MAX2678GTB/V+T](#) [MD2131K7-G](#) [MD2134K7-G](#) [RFFM6903TR13](#) [HV7351K6-G](#) [MCP2035-I/ST](#)  
[SE2614BT-R](#) [SE2438T-R](#) [SST12LF02-QXCE](#) [SST12LF09-Q3CE](#) [RFX2401C](#) [RFX2402E](#) [SKY85201-11](#) [RFFM4591FTR7](#) [RFFM8211TR7](#)  
[RFFM4293TR7](#) [RFFM4203TR7](#) [RFFM5765QTR7](#)