

## 20V/2A N-Channel MOSFET

### Features


- Trench Power LV MOSFET technology
- High Power and current handing capability

### Product Summary


$V_{DS}$	$R_{DS(ON)}$ MAX	$I_D$ MAX
20V	70m $\Omega$ @4.5V	2A
	80m $\Omega$ @2.5V	

### Application


- PWM application
- Load switch



Marking and pin assignment



SOT-23 top view




Schematic diagram


Absolute Maximum Ratings (TA=25°C unless otherwise noted)				
Symbol	Parameter		Rating	Unit
<b>Common Ratings (TC=25°C Unless Otherwise Noted)</b>				
$V_{DS}$	Drain-Source Breakdown Voltage		20	V
$V_{GS}$	Gate-Source Voltage		$\pm 8$	V
$T_J$	Maximum Junction Temperature		150	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range		-50 to 155	$^{\circ}\text{C}$
$I_S$	Diode Continuous Forward Current	$T_C=25^{\circ}\text{C}$	2	A
<b>Mounted on Large Heat Sink</b>				
$I_{DM}$	Pulse Drain Current Tested	$T_C=25^{\circ}\text{C}$	8	A
$I_D$	Continuous Drain Current	$T_C=25^{\circ}\text{C}$	2	A
$P_D$	Maximum Power Dissipation	$T_C=25^{\circ}\text{C}$	0.5	W
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient		250	$^{\circ}\text{C}/\text{W}$

<b>Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)</b>						
<b>Symbol</b>	<b>Parameter</b>	<b>Condition</b>	<b>Min</b>	<b>Typ</b>	<b>Max</b>	<b>Unit</b>
<b>Static Electrical Characteristics @ T<sub>J</sub> = 25°C (unless otherwise stated)</b>						
BV <sub>(BR)DSS</sub>	Drain-Source Breakdown Voltage	VGS=0V, ID=250μA	20	--	--	V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	VDS=16V, VGS=0V	--	--	1	μA
I <sub>GSS</sub>	Gate-Body Leakage Current	VGS=±8V, VDS=0V	--	--	±100	nA
V <sub>GS(th)</sub>	Gate Threshold Voltage	VDS=VGS, ID=250μA	0.4	0.7	1.5	V
R <sub>DS(on)</sub>	Drain-Source On-State Resistance	VGS=4.5V, ID=2.0A	--	40	70	mΩ
		VGS=2.5V, ID=1.9A	--	49	80	mΩ
		VGS=1.8V, ID=1.6A	--	80	120	mΩ
<b>Dynamic Electrical Characteristics @ T<sub>J</sub> = 25°C (unless otherwise stated)</b>						
C <sub>ISS</sub>	Input Capacitance	VDS=10V, VGS=0V, f=1MHz	--	222	--	pF
C <sub>OSS</sub>	Output Capacitance		--	35	--	pF
C <sub>RSS</sub>	Reverse Transfer Capacitance		--	25	--	pF
<b>Switching Characteristics</b>						
Q <sub>g</sub>	Total Gate Charge	VDS=10V, ID=2.5A, VGS=10V	--	3.6	--	nC
Q <sub>gs</sub>	Gate Source Charge		--	0.9	--	nC
Q <sub>gd</sub>	Gate Drain Charge		--	0.75	--	nC
t <sub>d(on)</sub>	Turn-on Delay Time	VDD=10V, ID=2.5A, VGS=10V, RG=3Ω	--	6.8	--	nS
t <sub>r</sub>	Turn-on Rise Time		--	57	--	nS
t <sub>d(off)</sub>	Turn-Off Delay Time		--	14	--	nS
t <sub>f</sub>	Turn-Off Fall Time		--	55	--	nS
<b>Source- Drain Diode Characteristics</b>						
V <sub>SD</sub>	Forward on voltage	T <sub>J</sub> =25°C, I <sub>S</sub> =3A,	--	--	1.2	V


## Typical Operating Characteristics




**VDS, Drain-Source Voltage (V)**  
**Fig1. Typical Output Characteristics**




**Qg -Total Gate Charge (nC)**  
**Fig2. Typical Gate Charge Vs. Gate-Source Voltage**




**Tj - Junction Temperature (°C)**  
**Fig3. Normalized On-Resistance Vs. Temperature**



**ID, Drain-Source Current (A)**  
**Fig4. On-Resistance Vs. Drain-Source Current**




**VDS, Drain-Source Voltage (V)**  
**Fig5. Maximum Safe Operating Area**



**VDS, Drain-Source Voltage (V)**  
**Fig6 Typical Capacitance Vs. Drain-Source Voltage**

**SOT-23 Package information**



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E1	2.250	2.550	0.088	0.100
E	1.200	1.400	0.047	0.055
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
$\theta$	0°	8°	0°	8°

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [SLKORMICRO](#) manufacturer:*

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)  
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)  
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#)  
[DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)  
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)  
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)  
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1\\_T0\\_00201](#) [PJMF380N65E1\\_T0\\_00201](#)  
[PJMF280N60E1\\_T0\\_00201](#) [PJMF600N65E1\\_T0\\_00201](#) [PJMF900N65E1\\_T0\\_00201](#)