


PNP Transistors



1.Base
2.Emmitter
3.Collecter

■ Features

- Small Package
- Complementary to MMBT2222AT

■ Simplified outline(SOT-523)



■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbol	Rating	Unit
Collector - Base Voltage	V _{CB0}	-60	V
Collector - Emitter Voltage	V _{CEO}	-60	
Emitter - Base Voltage	V _{EBO}	-5	
Collector Current - Continuous	I _c	-600	mA
Collector Power Dissipation	P _c	150	mW
Thermal Resistance, Junction to Ambient	R _{θJA}	833	°C/W
Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{stg}	-55 to 150	

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector- base breakdown voltage	V _{CB0}	I _c = -100 μA, I _E = 0	-60			V
Collector- emitter breakdown voltage	V _{CEO}	I _c = -10 mA, I _B = 0	-60			
Emitter - base breakdown voltage	V _{EBO}	I _E = -100 μA, I _C = 0	-5			
Collector-base cut-off current	I _{CB0}	V _{CB} = -50 V, I _E = 0			-100	nA
Emitter cut-off current	I _{EBO}	V _{EB} = -5V, I _C =0			-100	
Collector-emitter saturation voltage	V _{CE(sat)}	I _c =-150 mA, I _B =-15mA			-0.4	V
		I _c = -500 mA, I _B = -50mA			-1.6	
Base - emitter saturation voltage	V _{BE(sat)}	I _c =-150 mA, I _B =-15mA			-1.3	
		I _c = -500 mA, I _B = -50mA			-2.6	
DC current gain	h _{FE(1)}	V _{CE} = -10V, I _c =- 0.1mA	75			
	h _{FE(2)}	V _{CE} = -10V, I _c = -1mA	100			
	h _{FE(3)}	V _{CE} = -10V, I _c =- 10mA	100			
	h _{FE(4)}	V _{CE} = -10V, I _c = -150mA	100		300	
	h _{FE(5)}	V _{CE} = -10V, I _c = -500mA	50			
Delay time	t _d	V _{CC} =-30V, I _c =-150mA, I _{B1} =-15mA			10	nS
Rise time	t _r				40	
Storage time	t _s	V _{CC} =6V, I _c =-150mA, I _{B1} =I _{B2} =-15mA			225	
Fall time	t _f				30	
Emitter input capacitance	C _{ib}	V _{EB} = -2V, I _c = 0, f=1MHz			30	pF
Collector output capacitance	C _{ob}	V _{CB} = -10V, I _E = 0, f=1MHz			8	
Transition frequency	f _T	V _{CE} = -20V, I _c = -50mA, f=100MHz	200			MHz

■ SOT-523



DIMENSIONS (mm are the original dimensions)

UNIT	A	A ₁ max	b _p	c	D	E	e	e ₁	H _E	L _p	Q	v	w
mm	0.95 0.60	0.1	0.30 0.15	0.25 0.10	1.8 1.4	0.9 0.7	1	0.5	1.75 1.45	0.45 0.15	0.23 0.13	0.2	0.2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [SLKORMICRO manufacturer](#):

Other Similar products are found below :

[BC559C](#) [MCH4017-TL-H](#) [MMBT-2369-TR](#) [BC546/116](#) [NJVMJD148T4G](#) [NTE16](#) [NTE195A](#) [IMX9T110](#) [2N4401-A](#) [2N6728](#) [2SA1419T-TD-H](#) [2SB1204S-TL-E](#) [2SC5488A-TL-H](#) [FMC5AT148](#) [2N2369ADCSM](#) [2N2907A](#) [2N3904-NS](#) [2N5769](#) [2SC4618TLN](#) [CPH6501-TL-E](#) [BC856BW-13-F](#) [US6T6TR](#) [BAX18/A52R](#) [BC556/112](#) [IMZ2AT108](#) [MMST8098T146](#) [MCH6102-TL-E](#) [2N3879](#) [30A02MH-TL-E](#) [NTE13](#) [NTE282](#) [NTE323](#) [NTE350](#) [NTE81](#) [JANTX2N2920L](#) [JANSR2N2907AUB](#) [CMLT3946EG TR](#) [SNSS40600CF8T1G](#) [CMLT3906EG TR](#) [GRP-DATA-JANS2N2907AUB](#) [GRP-DATA-JANS2N2222AUA](#) [MMDT3946FL3-7](#) [2N4240](#) [JANS2N3019](#) [MSB30KH-13](#) [2N2221AUB](#) [2SD1815T-TL-E](#) [2N6678](#) [2N2907Ae4](#) [JAN2N3507](#)