



Dual PNP Small Signal Transistors

MMDT3906

- ◇ Epoxy meets UL 94 V-0 flammability rating
- ◇ Lead Free Finish/RoHS Compliant
- ◇ For Switching and AF Amplifier Applications
- ◇ Rugged and reliable

Equivalent Circuit



Maximum Ratings ($T_a = 25^\circ\text{C}$)

Symbol	Parameter	Value	Units
V_{CB0}	Collector-Base Voltage	-40	V
V_{CE0}	Collector-Emitter Voltage	-40	V
V_{EB0}	Emitter-Base Voltage	-5	V
P_c	Collector Power Dissipation	200	mW
I_c	Collector Current - Continuous	-200	mA
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature	-55 to 150	$^\circ\text{C}$
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	625	$^\circ\text{C}/\text{W}$

Electrical Characteristics ($T_a = 25^\circ\text{C}$)

Symbol	Parameter	Test Conditions	Min	Max	Units
$V_{(BR)CB0}$	Collector-Base Breakdown Voltage	$I_C = -10\ \mu\text{A}$, $I_E = 0$	-40		V
$V_{(BR)CE0}$	Collector-Emitter Breakdown Voltage	$I_C = -1\text{mA}$, $I_B = 0$	-40		V
$V_{(BR)EB0}$	Emitter-Base Breakdown Voltage	$I_E = -10\ \mu\text{A}$, $I_C = 0$	-5		V
I_{BL}	Base Cutoff Current	$V_{CE} = -30\text{V}$, $V_{BE(OFF)} = -3\text{V}$		-50	nA
I_{CEX}	Collector Cutoff Current	$V_{CE} = -30\text{V}$, $V_{BE(OFF)} = -3\text{V}$		-50	nA
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = -10\text{mA}$, $I_B = -1\text{mA}$		-0.25	V
		$I_C = -50\text{mA}$, $I_B = -5\text{mA}$		-0.4	
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C = -10\text{mA}$, $I_B = -1\text{mA}$	-0.65	-0.85	V
		$I_C = -50\text{mA}$, $I_B = -5\text{mA}$		-0.95	

h_{FE}	DC Current Gain	$V_{CE} = -1V, I_C = -0.1mA$	60		
		$V_{CE} = -1V, I_C = -1mA$	80		
		$V_{CE} = -1V, I_C = -10mA$	100	300	
		$V_{CE} = -1V, I_C = -50mA$	60		
		$V_{CE} = -1V, I_C = -100mA$	30		
f_T	Transition Frequency	$V_{CE} = -20V, I_C = -10mA, f=100MHz$	250		MHz
C_{ob}	Output Capacitance	$V_{CB} = -5V, I_E = 0, f=1MHz$		4.5	pF
t_d	Delay Time	$V_{CC} = -3V, I_C = -10mA, V_{BE(OFF)} = -0.5V, I_{B1} = -1mA$		35	nS
t_r	Rise Time			35	nS
t_s	Storage Time	$V_{CC} = -3V, I_C = -10mA, I_{B1} = -I_{B2} = -1mA$		225	nS
t_f	Fall Time			75	nS

Package Dimensions

Package outline : SOT383-6L

TOP VIEW

SIDE VIEW

SYMBOL	DIMENSIONS IN MILLIMETER	
	MIN	MAX
A	0.900	1.000
A1	0.000	0.100
A2	0.900	1.000
b	0.150	0.350
c	0.100	0.150
D	2.000	2.200
E	1.150	1.350
E1	2.150	2.400
e	0.650 TYP.	
e1	1.200	1.400
L	0.525 REF.	
L1	0.260	0.460
theta	0°	8°


FRONT VIEW

SOLDING PATTERN


Notice:

1. Lead plating: Pb free solder
2. Lead thickness includes solder plating
3. Lead frame: CAC-5
4. Other Tolerance: ±0.05
6. Dimensions are exclusive of Burrs, Mold Flash and Tie Bar extrusions
5. Unit: mm


Typical Characteristics




Static Characteristic




DC Current Gain Characteristics




Collector-Emitter Saturation Voltage Characteristics



Base-Emitter Saturation Voltage Characteristics



Base-Emitter Voltage Characteristics



Collector Power Derating Curve

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [SLKORMICRO manufacturer](#):

Other Similar products are found below :

[BC559C](#) [MCH4017-TL-H](#) [MMBT-2369-TR](#) [BC546/116](#) [NJVMJD148T4G](#) [NTE16](#) [NTE195A](#) [IMX9T110](#) [2N4401-A](#) [2N4403](#) [2N6728](#)
[2SA1419T-TD-H](#) [2SA2126-E](#) [2SB1204S-TL-E](#) [FMC5AT148](#) [2N2369ADCSM](#) [2N2907A](#) [2N3904-NS](#) [2N5769](#) [2SC4618TLN](#) [CPH6501-](#)
[TL-E](#) [MCH4021-TL-E](#) [Jantx2N5416](#) [US6T6TR](#) [BAX18/A52R](#) [BC556/112](#) [IMZ2AT108](#) [MMST8098T146](#) [UMX21NTR](#) [MCH6102-TL-E](#)
[TTA1452B,S4X\(S](#) [2N3879](#) [NTE13](#) [NTE282](#) [NTE323](#) [NTE350](#) [NTE81](#) [JANTX2N2920L](#) [JANTX2N3735](#) [JANSR2N2222AUB](#)
[CMLT3946EG TR](#) [SNSS40600CF8T1G](#) [CMLT3906EG TR](#) [GRP-DATA-JANS2N2907AUB](#) [GRP-DATA-JANS2N2222AUA](#)
[MMDT3946FL3-7](#) [2N4240](#) [MSB30KH-13](#) [2N2221AUB](#) [2SD1815T-TL-E](#)