

## -30V/-10A P-Channel MOSFET

### Features


- Trench Power LV MOSFET technology
- High density cell design for Low  $R_{DS(ON)}$
- High Speed switching

### Product Summary

$V_{DS}$	$R_{DS(ON)} \text{ MAX}$	$I_D \text{ MAX}$
-30V	18mΩ@10V	-10.5A
	30mΩ@4.5V	


### Application

- Battery protection
- Power management
- Load switch




4435: Device code  
XXXXXX : Code

Marking and pin assignment



SOP-8 top view



Schematic diagram

### Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

### Common Ratings (TC=25°C Unless Otherwise Noted)

$V_{DS}$	Drain-Source Breakdown Voltage	-30	V	
$V_{GS}$	Gate-Source Voltage	±20	V	
$T_J$	Maximum Junction Temperature	150	°C	
$T_{STG}$	Storage Temperature Range	-50 to 155	°C	
$I_S$	Diode Continuous Forward Current	Tc=25°C	-10	A

### Mounted on Large Heat Sink

$I_{DM}$	Pulse Drain Current Tested	Tc=25°C	-50	A
$I_D$	Continuous Drain Current@GS=10V	Tc=25°C	-10.5	A
$P_D$	Maximum Power Dissipation	Tc=25°C	3	W
$R_{θJA}$	Thermal Resistance Junction-Ambient(*1 in2 Pad of 2-oz Copper), Max.)		42	°C/W

**Electrical Characteristics (TJ=25°C unless otherwise noted)**

Symbol	Parameter	Condition	Min	Typ	Max	Unit
<b>Static Electrical Characteristics @ TJ = 25°C (unless otherwise stated)</b>						
$BV_{(BR)DSS}$	Drain-Source Breakdown Voltage	$VGS=0V$ , $ID=-250\mu A$	-30	--	--	V
$I_{DSS}$	Zero Gate Voltage Drain Current	$VDS=-30V$ , $VGS=0V$	--	--	-1	$\mu A$
$I_{GSS}$	Gate-Body Leakage Current	$VGS=\pm 20V$ , $VDS=0V$	--	--	$\pm 100$	nA
$V_{GS(th)}$	Gate Threshold Voltage	$VDS=VGS$ , $ID=-250\mu A$	-1	-1.5	-3	V
$R_{DS(on)}$	Drain-Source On-State Resistance	$VGS=-10V$ , $ID=-10A$	--	15	18	$m\Omega$
		$VGS=-4.5V$ , $ID=-8A$	--	22	30	

**Dynamic Electrical Characteristics @ TJ = 25°C (unless otherwise stated)**

$C_{ISS}$	Input Capacitance	$VDS=-15V$ , $VGS=0V$ , $f=1MHz$	--	1500	--	pF
$C_{OSS}$	Output Capacitance		--	180	--	pF
$C_{RSS}$	Reverse Transfer Capacitance		--	150	--	pF

**Switching Characteristics**

$Q_g$	Total Gate Charge	$VDS=-10V$ , $ID=-6A$ , $VGS=-15V$	--	29	--	nC
$Q_{gs}$	Gate Source Charge		--	5.4	--	nC
$Q_{gd}$	Gate Drain Charge		--	5.4	--	nC
$t_{d(on)}$	Turn-on Delay Time		--	10	--	nS
$t_r$	Turn-on Rise Time	$VDD=-15V$ , $ID=-6A$ , $VGS=-10V$ , $RG=2.5\Omega$	--	45	--	nS
$t_{d(off)}$	Turn-Off Delay Time		--	55	--	nS
$t_f$	Turn-Off Fall Time		--	60	--	nS

**Source- Drain Diode Characteristics**

$V_{SD}$	Forward on voltage	$Tj=25^\circ C$ , $Is=-10A$ ,	--	-0.8	-1.2	V
----------	--------------------	-------------------------------	----	------	------	---

## Typical Operating Characteristics




Fig1. Typical Output Characteristics




Fig2. Typical Gate Charge Vs.Gate-Source Voltage




Fig3. Normalized On-Resistance Vs. Temperature




Fig4. On-Resistance Vs. Drain-Source Current




Fig5. Maximum Safe Operating Area






Fig6 Typical Capacitance Vs.Drain-Source Voltage

**SOP-8 Package information**

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.450	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.700	5.100	0.185	0.201
e	1.270 (BSC)		0.050 (BSC)	
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by SLKORMICRO manufacturer:***

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [NTNS3A92PZT5G](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#)  
[AOD464](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#)  
[IPS70R2K0CEAKMA1](#) [BSF024N03LT3 G](#) [PSMN4R2-30MLD](#) [TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#)  
[EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMC2700UDMQ-7](#)  
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#)  
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [IRF40H233XTMA1](#) [IPSA70R950CEAKMA1](#) [IPSA70R2K0CEAKMA1](#) [STU5N65M6](#)  
[C3M0021120D](#)