



CAT IV

600 V

CAT III

1000 V

 **IP40**

 **FORK-STYLE CLAMP**

 **BUILT-IN FLASHLIGHT**

New level of fast measurements

Sonel CMP-200F is an innovative representative of the clamp meter family. It combines simplicity, speed of measurements and versatility. It contains all the necessary functionalities and improvements, such as: built-in flashlight, reading of MAX and MIN values, automatic measurement of AC / DC voltages and many others.

The CMP-200 F is perfect for places where it is difficult to operate the traditional clamp meter e.g. in narrow switchgear. Open measuring clamps make measurements faster and easier. LowZ function eliminates the influence of ghost voltage and ensures accurate readings. The display is always illuminated, ensuring excellent readability in the dark or even in sunny days when the screens of other devices fail.

Technical specifications

Measure functions	Range	Resolution	Precision ±(% m.v. + digits)
AC current	200,0 A	0,1 A	±(3% m.v. + 5 digits)
AC voltage	up to 1000 V	from 0,001 V	from ±(1,2% m.v. + 2 digits)
DC voltage	up to 1000 V	from 0,001 V	from ±(0,9% m.v. + 4 digits)
Low-impedance voltage measurement Low Z	up to 600,0 V	from 0,001 V	±(3,0% m.v. + 40 digits)
Resistance	up to 60,00 MΩ	from 0,1 Ω	from ±(1,0% m.v. + 4 digits)
Capacity	up to 4000 µF	from 0,01 nF	from ±(3,0% m.v. + 5 digits)
Basic characteristics			
Counting		6.000 digits	
HOLD		✓	
Automatic range choice zakresu		✓	
Advanced characteristics			
Open clamp meters		✓	
Contactless voltage gauge		✓	
MIN / MAX		✓ / ✓	
TRMS measurement		✓	
Other characteristics			
Automatic power off		✓	
Low battery indicator		✓	
Built-in flashlight		✓	
Beep		✓	
Display			
Type		segmental LCD, 4 digits	
Display backlight		manual	
Safety and terms of use			
Measurement category acc. to EN 61010		CAT IV 600 V CAT III 1000 V	
Safety level		IP40	
Dimensions		230 x 44 x 66 mm	
Weight		270 g	
Work temperature		5...40°C	
Storage temperature		-20...+60°C	

m.v. - measured value

Standard accessories



**Test leads set
for CMM
CAT IV, M**
WAPRZCMM2



**2x LR6 batte-
ries AA 1,5 V**



Basic case



Manual



**Calibration
certificate**

Optional accessories

+

	Test lead 2 m CAT IV 1000V (banana plugs, fused 10 A) black / blue / green / red / yellow WAPRZ002BLBBF10 WAPRZ002BUBBF10 WAPRZ002GRBBF10 WAPRZ002REBBF10 WAPRZ002YEBBF10
	Pin probe (banana socket) red / blue / yellow / black B1 / black B3 WASONREQGB1 WASONBUQGB1 WASONYEQGB1 WASONBLOGB1 WASONBLOGB3
	Crocodile clip red / blue / yellow / black WAKRORE20K02 WAKROBU20K02 WAKROYE20K02 WAKROBL20K01



**Test leads set
for CMM
CAT IV, S**
WAPRZCMM1



AC-16 line splitter
WAADAAAC16



**Test leads set for
CMM for CMM/CMP**
WAPRZCMP1



Case M-13
WAFUTM13



**Crocodile clip mini,
set, 1 kV 10 A (kpl.)**
WAKROKPL10MINI

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Clamp Multimeters & Accessories category:

Click to view products by Sonel manufacturer:

Other Similar products are found below :

[I800](#) [BK313C](#) [BM035](#) [BM198PV](#) [BK312C](#) [BM031](#) [BM037](#) [BM078](#) [BM088](#) [P 4250](#) [P 4350](#) [WMGBCMP401](#) [KEW105816](#)
[WMGBCMP200](#) [WMGBCMP2000](#) [WMGBCMP3000](#) [WMGBCMP400](#) [FLUKE 377 FC](#) [FLUKE 378 FC](#) [FLUKE 393 FC](#) [MW3035](#) [NC11-](#)
[200M1](#) [NC12-200M1](#) [NC14-100M1](#) [P 1610](#) [P 1615](#) [P 1625](#) [P 1640](#) [P 1650](#) [P 1655](#) [P 1660](#) [P 1665](#) [P 1700](#) [UT202F](#) [UT202R](#) [UT219E](#)
[UT281A](#) [UT281C](#) [DCM140](#) [1000-304](#) [TESTO 770-3](#) [0590](#) [7703](#) [AX-3550](#) [AX-M266C](#) [BM079](#) [BM089](#) [BM197](#) [UT204](#) [KEW2210R](#)
[FLUKE 80I-110S](#) [FLUKE A3002FC](#)