



Cable and underground infrastructure locator **LKZ-1500 / LKZ-1500-LITE**

index: WMGBLKZ1500 / WMGBLKZ1500LITE

LKO-1500 / LKO-1500-LITE

index: WMGBLKO1500 / WMGBLKO1500LITE

LKN-1500


Index: WMGBLKN1500



LKO-1500



LKO-1500



LKO-1500-LITE



LKN-1500

LKO-1500
receiver



LKN-1500
transmitter



LKO-1500-LITE
receiver



LKZ-1500

LKZ-1500-LITE

Underground detectives

Features

The LKZ locator set consists of a LKN transmitter and LKO receiver. It allows for location, identification and tracking of the route of objects buried in the earth. The user will be able to trace:

- power cords and cables, control cables, telecommunications cables,
- underground elements of lightning protection systems, cathodic protection systems,
- water and sewage systems,
- fuel transmission systems (pipelines, gas pipelines)
- heating systems and pre-insulated pipes.

The sets of LKZ series are an invaluable support in earthworks carried out for various industries, including energy, installation, construction, railway, telecommunications, water and sanitary, heating, geodetic and many others.

LKN-1500 transmitter introduces a specific signal to the tracked objects, enabling LKO receivers to route in the active mode. The receivers operate also in a passive mode that uses the network frequencies and telecommunications signals present in the facility.

LKO-1500-LITE receiver is designed according to "intuitive and user-friendly" principle and it is an ideal solution for users entering the world of cable location and routing. **LKO-1500 receiver** is a level higher: it facilitates the work of the user to with many features, including visualization of the cable routing in the tested object or a greater number of frequencies to choose from. It is also distinguished by the option of tracing cable short-to-earth faults with the use of additional accessories.



LKN-1500 transmitter

- Transmission of double frequency signals.
- The mode of limiting the voltage of the transmitted signal.
- Transmitter power: 1 W, 2 W, 5 W, 10 W.
- Operation in direct galvanic or inductive connection mode - internal transmitting antenna.
- Compatible with transmitting clamps.
- Continuous or interval mode of operation that extends battery life.
- Case housing.


LKO-1500-LITE receiver


- **Active mode**
 - » work with LKN-1500 transmitter at the frequencies of 1024 Hz, 8928 Hz, 33 kHz.
- **Passive mode – work at the frequencies of:**
 - » 50 Hz,
 - » RADIO (10...36 kHz),
 - » SB (48 Hz...14 kHz).
- **Location depth up to 6 m.**



LKO-1500 receiver

- **Active mode:**
 - » work with LKN-1500 transmitter at the frequencies of 273 Hz, 526 Hz, 1024 Hz, 8928 Hz, 33 kHz,
 - » work with transmitters other than LKN-1500 at the frequencies of 491 Hz, 512 Hz, 982 Hz, 2000 Hz, 2048, Hz 8440 Hz, 9828 Hz, 10000 Hz.
- **Passive mode – work at the frequencies of:**
 - » 50 Hz, 60 Hz, 100 Hz, 300 Hz, 550 Hz, 1450 Hz,
 - » RADIO (10...36 kHz),
 - » SB (48 Hz...14 kHz).
- **Location depth up to 10 m.**
- **Operation with external probes.**






Sonel LKZ Terminal

The application works with the Sonel LKZ-1500 wire and cable locator. By replacing the external GPS module, it allows the user to define and record the geographic coordinates of the cable route.



The application additionally enables:

- live positioning preview,
- measuring the distance to a specific point on the route,
- export of routes saved in LKO-1500 to the phone's memory,
- reading routes from the phone's memory,
- preview of the saved values of all parameters,
- data export to PC.




Sonel LKO Terminal

A dedicated PC program for handling data stored in Sonel LKO-1500. It allows you to map a route from your location and read the data stored in the receiver. The data includes:



- coordinates of the place of measurement according to GPS information,
- reading the depth of the object and value of current flowing in it,
- the direction of the forced current,
- operating frequency,
- date and local time at the time of measurement according to GPS information,
- export of route data to a file.



Technical specifications

LKN-1500 transmitter

| | |
|-----------------------|--|
| Ingress protection | IP54 |
| Power supply | VRLA (AMG) lead-acid 12 V / 7 Ah |
| Dimensions | 275 x 250 x 180 mm |
| Weight | ca. 4.9 kg |
| Operating temperature | -20...+55°C |
| Storage temperature | -50...+70°C |
| Nominal temperature | 23 ± 2°C |
| Relative humidity | no more than 90% at the temperature of +30°C |

LKO-1500 / 1500-LITE receiver

| | |
|-----------------------|---|
| Ingress protection | IP54 |
| Power supply | Ni-MH 6 V/2000 mAh battery pack 5x AA 1.5 V battery 5x Ni-MH 1.2 V rechargeable battery |
| Dimensions | 700 x 300 x 140 mm |
| Weight | |
| LKO-1500-LITE | ca. 1.7 kg |
| LKO-1500 | ca. 1.8 kg |
| Operating temperature | -20...+55°C |
| Storage temperature | -50...+70°C |
| Nominal temperature | 23 ± 2°C |
| Relative humidity | no more than 95% at the temperature of +30°C |



LKZ-1500 • LKZ-1500-LITE | Standard accessories

| | | | | | |
|---|--|---|--|---|---|
|  | LKN-1500 transmitter |  | LKO-1500 receiver only for LKZ-1500 |  | LKO-1500-LITE receiver only for LKZ-1500-LITE |
|  | Crocodile clip 1 kV 20 A red / blue WAKRORE20K02 WAKROBU20K02 |  | Sun-protecting cover only for LKZ-1500 WAPOZOSL4 | | |
|  | Test lead 5 m 1 kV (banana plugs) red / blue WAPRZ005REBB WAPRZ005BUBB |  | Hanging strap only for LKZ-1500 WAPOZSZE6 | | |
|  | Ground probe 23 cm WASONG23 |  | Bag L13 WAFUTL13 | | |
| | | | |  | Power supply Battery compartment WAPOJ3 Rechargeable battery NiMH 6 V, 2 Ah WAAKU23 Battery charger Z16 WAZASZ16 Battery charger Z17 WAZASZ17 |

LKO-1500 • LKO-1500-LITE | Optional accessories

| | | | | | |
|--|---|--|--|--|--|
|  | Hanging strap only for LKO-1500 WAPOZSZE6 |  | Sun-protecting cover only for LKO-1500 WAPOZOSL4 |  | Power supply Battery compartment WAPOJ3 Rechargeable battery NiMH 6 V, 2 Ah WAAKU23 Battery charger Z17 WAZASZ17 |
|  | Bag L13 WAFUTL13 | | | | |

LKN-1500 | Standard accessories

| | | | | | |
|---|--|---|--|---|-------------------------------------|
|  | Crocodile clip 1 kV 20 A red / blue WAKRORE20K02 WAKROBU20K02 |  | Test lead 5 m 1 kV (banana plugs) red / blue WAPRZ005REBB WAPRZ005BUBB |  | Battery charger Z16 WAZASZ16 |
|  | Ground probe 23 cm WASONG23 | | | | |

LKZ-1500 / 1500-LITE • LKO-1500 • LKN-1500 | Optional accessories

| | | | | | |
|---|--|---|--|---|---|
|  | Transmitting clamps only for • LKZ-1500 / 1500-LITE • LKN-1500 N-1 (fi 52 mm) WACEGN1BB N-4 (fi 110 mm) WACEGN4 N-5 (fi 125 mm) WACEGN5 |  | GPS adapter GT-750 only for • LKZ-1500 • LKO-1500 WAADAGT750 |  | Probes only for • LKZ-1500 • LKO-1500 DKI probe WASONDKI A-frame WAADALKZRA2 |
|---|--|---|--|---|---|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sonel manufacturer:

Other Similar products are found below :

[WMGBP6](#) [WMGBTG1](#) [WMGBCMP3000](#) [WMGLXP2](#) [WMGBMPI506](#) [WMDEMPI535](#) [C-6A](#) [C-7A](#) [N-1](#) [WAPRZ050YEBBSZ](#)
[WAPRZ1X8BLBB](#) [WAPRZCMP1](#) [WASONBUOGB1](#) [WASONYELOB1](#) [WAPOZSZE2](#) [WMGBCMM30](#) [WMGBCMP2000](#)
[WMGLKZ720](#) [WMGBTKF12](#) [AGT-16P](#) [AGT-32P](#) [C-3](#) [F-3A](#) [S-2](#) [WASONG30](#) [WMGBCMM40](#) [WMGBCMM10](#) [WMGBCMP200](#)
[WMGBCMM11](#) [WAPRZ1X2BUBB](#) [WAPRZ1X8REBB](#) [K-01](#) [WMGBP4](#) [WMGBP5](#) [WMGBCMP400](#) [WMGBTKF13](#) [K-02](#)
[WMGBCMP401](#) [WAKROYE20K02](#) [WAPRZ1X2YEBB](#) [WAPRZ1X2REBB](#)