





Basic grounding measurements under all conditions

Earthing resistance measurements

- 3-pole method measurement of earthing systems using auxiliary probes
- 2-pole method

Features

- Resistance of auxiliary electrodes R_u and R_e
- Measurement of interference voltage to 100 V
- Indication of battery state
- Selection of maximum measuring voltage (25 V and 50 V)
- Auto-OFF function

Overview

MRU-10 is a simple meter that allows you to measure grounding by the use of the technical method and to measure grounding resistance by the use of the 2-pole method. The instrument is easy to handle, resistive to interference, and highly accurate.

MRU-10 is a basic device that allows checking the quality of the grounding system on the basis of the received measurement result. Its ergonomic shape, durable and firm housing, as well as big and clear display make this instrument ideal to use both in the field and most working environments. The device is simple to operate and intuitive. It is the best choice for electrical installations contractors, technicians, and professionals dealing with grounding measurements.





page 1/3 sonel.com

Technical specification	n ———				
Measurement functions	Measurement range	Display range	Resolution	Accuracy ±(% m.v. + digits)	
Interference voltage	0 V100 V	0 V100 V	1 V	±(10% m.v. + 1 digit)	
Earth resistance					
2-pole method	0.009999 Ω	0.009999 Ω	from 0.01 Ω	from ±(3% m.v. + 3 digits)	
3-pole method	0.539999 Ω acc. to EN 61557-5	0.009999 Ω	from 0.01 Ω	from ±(3% m.v. + 3 digits)	
auxiliary electrodes resistance	0 Ω19.9 kΩ	0 Ω19.9 kΩ	from 1 Ω	±(5% + 8 digits)	
Safety and work conditions					
Measuring category according to EN 61010		III 300 V			
Ingress protection		IP67			
Type of insulation according to EN 61010-1 and IEC 61557		double			
Dimensions		221 x 102 x 62 mm			
Veight		ca. 660 g			
Operating temperature		-10+50°C			
Storage temperature		-20+60°C			
Humidity	ity		2090%		
Nominal temperature		23 ± 2°C			
Reference humidity		40%60%			
Other information					
Quality standard – development, design and production		ISO 9001			
The product meets the EMC (emission for industrial environment)		EN 61326-1			
requirements according to standards			EN 61326	5-2-2	

page 2 / 3 sonel.com

Standard accessories



Test lead 2.2 m, black, 1 kV (banana plugs)

WAPRZ2X2BLBB



Test lead 15 m, red (banana plugs, on H-frame reel)

WAPRZ015REBBN



Test lead 30 m, yellow (banana plugs, on H-frame reel)

WAPRZ030YEBBN



Crocodile clip, black, 1 kV, 20 A

WAKROBL20K01



4 x alkaline battery 1.5 V AA, LR6



2 x earth contact test probe (rod), 25 cm

WASONG25



M1 hanging straps WAPOZSZE4

M1 hanging hook straps WAPOZUCH1



M6 carrying case

WAFUTM6



Calibration certificate

Optional accessories



Crocodile clip 1 kV 20 A red / blue / yellow

WAKRORF20K02 WAKROBU20K02 WAKROYE20K02



Test lead 1.2 m (banana plugs) black / blue / yellow

WAPRZ1X2BLBB WAPRZ1X2BUBB



Pin probe 1 kV (banana socket) black / blue / yellow

WASONBUOGB1 WASONBLOGB1 WASONYEOGB1



Test lead 25 / 30 m, for MRU (banana plugs, on a reel), red

WAPRZ025REBBSZ WAPRZ030RFRRSZ



Test lead 15 m, for MRU (banana plugs, on a reel), blue

WAPRZ015BUBBSZ



Test lead 50 m for MRU (banana plugs, on a reel), yellow

WAPRZ050YEBBSZ



Test lead on a reel red 75 m / 100 m / 200 m

WAPRZ075REBBSZ WAPRZ100REBBSZ WAPRZ200REBBSZ



Test lead on a reel blue 75 m / 100 m / 200 m

WAPRZ075BUBBSZ WAPRZ100BUBBSZ WAPRZ200BUBBSZ



Test lead on a reel yellow 75 m / 100 m / 200 m

WAPRZ075YEBBSZ WAPRZ100YEBBSZ WAPRZ200YEBBSZ



Cramp with banana socket

WAZACIMA1



Earth contact test probe 30 cm / 80 cm

WASONG30 WASONG80



L3 carrying case for 80 cm rods

WAFUTL3



Test wire reel

WAPOZSZP1



Calibration certificate issued by an accredited laboratory

page 3 / 3 sonel.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Sonel manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS 2837806 4328074 4366444 S-11 382153 700PTP-1 GEO-CABLE-REEL-50M H115 H300 F150-SLC50 TM-192 TM-192D TM-414 EL-P-TC-T-SURFACE UT301C+ HS115 12227021 13123602 13123661 12255930 12983030 30171091 30198712 30198755 30209323 12228657 12229067 12230090 7358958 12231398 12231487 7390674 7390682 12231550 7391840 7391939 7391955 7391972 7391998 7392056 7392099 7395489 7400058 7400394