



CAT II

300 V

IEC

61557

IP40

WiFi

**TOUCH
SCREEN**

**FLASH
TEST**

**QR CODE
SYSTEM**

Take care of Safety of the power tools with Sonel's PAT!

Product features

- advanced measuring unit enabling measurements of:
 - protective conductor resistance
 - of insulation resistance
 - of RCD circuit breaker parameters
 - of equivalent leakage current,
 - of differential leakage current,
 - of touch leakage current
 - of power
 - of power consumption
 - IEC cable test
 - of mains voltage and frequency.
 - flashtest - high voltage test (only PAT-820)
- a very intuitive user interface
- support for label printer and QR code scanner
- have duty housing (with IP67 flap closed)
- clear colour touchscreen



Application

Digital PAT-820 series meters are designed for parameter measurements of all kinds electrical devices, such as power tools, household appliances, etc. The device is dedicated to the facility maintenance departments, companies providing power tool measurement services, hotels and public institutions services. PAT should be used in every place where the safety of using power tools is one of the inseparable elements of taking care of the user's safety against electric shock.



Device capabilities

The PAT-820 series devices thanks to the advanced measuring unit enable comprehensive testing of power tools. Due to the expanded interface, it enables the recording of large amounts of measurement data, and the use of additional functions to facilitate work. Support for QR code scanner, label printer or communication with PC is not a problem. The measurements are carried out in an intuitive and widely configurable manner.



Intuitive operation

The large, touch screen and graphic layout makes work on the device is intuitive and pleasant. The built-in help guides the user when building the correct measurement system. The work related to data records is based on a tree- structure memory that enables the construction of a transparent and extensive database.



Tree-structure memory

Writing to the memory with the initial description of the tested devices, a location of measurements, customer data, assignment of the serial number and index to the tested device, possibility of introducing comments to the tested device.

Have duty housing

Durable case with IP67 protection (with closed lead). It provides reliability during measurement, transport and storage.

Standard accessories



**2x pin probe, red
5 kV
(banana socket)**

WASONREOGB2



**Test lead 1,8 m,
orange, (10 A / 25
A, terminated in
a crocodile clip)**

WAPRZ1X8ORKS



**2x test lead 1,8 m,
red, 11 kV
(banana plugs)**

WAPRZ1X8REBB



**Mains cable with
IEC C19 plug**

WAPRZZAS1



**USB
transmission cable**

WAPRZUSB



**2x fuse 0314 015.
VXP 15 A 250
VAC 6.3x32 mm
Littlefuse**

WAPOZB15PAT

Optional accessories



Three-phase socket adapter 16 A

5P
WAADAPAT16P

5P switchable
WAADAPAT16PR

4P
WAADAPAT16C

4P switchable
WAADAPAT16CPR



Three-phase socket adapter 32 A

5P
WAADAPAT32P

5P switchable
WAADAPAT32PR

4P
WAADAPAT32C

4P switchable
WAADAPAT32CPR



3P industrial socket adapter

16 A
WAADAPAT16F1

32 A
WAADAPAT32F1



IEC test adapter (Shuko)

WAADAPATIEC1



Pin probe, red 1 kV (banana socket)

WASONREOGB1



Crocodile clip 1 kV 20 A

red
WAKRORE20K02
blue
WAKROBU20K02



Kelvin clamp, 1 kV, 25 A

WAKROKELK06



High-current pin probe 1 kV (banana sockets)

WASONSPGB1



Brush probe for PAT testers

WASONSZ1



C-3 current clamps (Φ=52 mm)

WACEGC30KR



Double-wire test lead 2.1 m (IEC C13 / banana plug)

WAPRZ2X1DZIECB



Double-wire test lead 1.5 m (PAT/ banana plug)

WAPRZ1X5DZBB



IEC C6 to C13 adapter

WAADAPATIEC2



Report / barcode printer (USB, portable)

WAADAD2



Accessories for SATO printer

Tape / paper (glued)
WANAKD2

Ink tape
WANAKD2BAR



Barcode scanner 2D (USB)

WAADACK2D



Sonel PAT Analysis

WAPROSONPAT3

Technical specification

Measurement functions	Range	Resolution	Accuracy ±(% m.v. + digits)
Resistance of protective conductor (PE) I = 200 mA / 10 A / 25 A	up to 19.99 Ω	from 1 mΩ	from ±(3% m.v. + 4 digits)
Insulation resistance U _{ISO} = 100 V / 250 V / 500 V	up to 599.9 MΩ	from 1 kΩ	±(5% m.v. + 8 digits)
Visual test		✓	
Continuity check of protective conductor (PE)		✓	
Insulation resistance measurement at three points		✓	
Durability of insulation (Flash Test)		✓	
IEC cable test		✓	
Fuse test		✓	
Functional test			
Apparent power S	up to 3.99 kVA	from 1 VA	from ±(5% m.v. + 3 digits)
Active power P	up to 3.99 kW	from 1 W	from ±(5% m.v. + 3 digits)
Power Factor (PF)	up to 1.00	0.01	±(10% m.v. + 5 digits)
Current consumption for power measurement	up to 15.99 A	0.01 A	±(2% m.v. + 3 digits)
Leakage current measurement			
PE leakage current and differential leakage current	up to 19.9 mA	from 0.01 mA	±(5% m.v. + 2 digits)
Substitute leakage current	up to 19.9 mA	from 0.01 mA	±(5% m.v. + 2 digits)
Touch leakage current	up to 4.999 mA	0.001 mA	±(5% m.v. + 3 digits)
RCD switch test			
Measurement of RCD parameters according to IEC 61557	up to 300 ms	1 ms	±(2% m.v. + 2 digits)
Measurement of RCD tripping current I _A for sinusoidal residual current (AC type)	up to 30 mA	0.1 mA	±5% I _{Δn}
Measurement of power network parameters			
Voltage	up to 265.0 V	0.1 V	±(2% m.v. + 2 digits)
Voltage of PE in power network	up to 59.9 V	0.1 V	±(2% m.v. + 2 digits)
Frequency	up to 55.0 Hz	0.1 Hz	±(2% m.v. + 2 digits)

Technical data

Display	TFT 7" 800 x 480 px
Power supply	195...265 V 50 Hz mains
Load current	max. 16 A (230 V)

Safety and work conditions

Measuring category according to EN 61010	II 300 V
Ingress protection	IP40
Type of insulation according to EN 61010-1 and IEC 61557	double
Dimensions	390 x 308 x 172 mm
Weight	ca. 5.7 kg
Operating temperature	-10...+50°C
Storage temperature	-20...+70°C
Humidity	20...80%
Nominal temperature	+20...+25°C
Reference humidity	40%...60%
Altitude a.s.l.	<2000 m

Memory and communication

Memory of measurement results	min. 4 GB
Data transmission	USB 2.0, Wi-Fi

Other information

Quality standard - development, design and production	ISO 9001
	ISO 14001
	ISO 45001
The product meets the EMC (emission for industrial environment) requirements according to standards	EN 61326-1
	EN 61326-2-2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Digital Multimeters](#) category:

Click to view products by [Sonel](#) manufacturer:

Other Similar products are found below :

[6111-517](#) [FS881](#) [40705X](#) [C.A 6133 LAUNCH KIT](#) [P 1020 A](#) [SEFRAM7303](#) [BS K-CLIP](#) [19290](#) [DM285-FLEX-KIT](#) [IBT6K](#) [GDM-531](#)
[GDM-532](#) [GDM-533](#) [GDM-541](#) [1013-099](#) [1000-219](#) [1001-613](#) [1006-969](#) [1008-221](#) [1012-597](#) [30XR](#) [34XR](#) [35XP](#) [TESTO 745](#) [0590 7450](#)
[TESTO 760-2](#) [0590 7602](#) [TESTO 760-3](#) [0590 7603](#) [440012](#) [AX-155](#) [AX-174](#) [AX-178](#) [AX-18B](#) [AX-190A](#) [AX-503](#) [AX-507B](#) [AX-594](#) [AX-](#)
[LCR42A](#) [AX-MS811](#) [AX-MS8250](#) [AX-PDM01](#) [AX-T520](#) [AX-T901](#) [AX-T903](#) [BAT-250-EUR](#) [BM525S](#) [BM805S](#) [BM807S](#) [BM817S](#)
[BM827S](#) [BM829S](#) [BM857S](#)