






文件编号 File Number	SRD-WI-3652	版本号 Version Number	A	页码 page	1/3
---------------------	-------------	-----------------------	---	------------	-----

### 1、外形尺寸 Dimension :

单位Unit: mm



A	4.5±0.3
B	4.0±0.3
C	3.2±0.3
D	1.4Ref.
E	4.5Ref.
F	1.8Ref.
G	1.5Ref.

### 2、产品品名构成 Product Spec. Model

SR 43 Y F - 2R2 M

a b c d e f

a: 系列名称 Series name

b: 产品尺寸 Product dimensions (A x B x C)

c: 密封方式 Sealing way (L: 冷封 Cold seal Y: 热封 Heat seal)


d: 印字方向 Lettering direction ▶

e: 电感值 Inductance Value

(1R0:1.0uH; 100: 10uH; 101:100uH)

f: 电感公差 Inductance Tolerance (K:10% ; M:20% ; N:30%)

#### ▶ Lettering direction



### 3、结构 Structure



### 4、材料清单 MATERIAL LIST

NO.	PARTS	MATERIAL	UL FILE NO.	TEMP. CLASS
1	CORE	Ni-Zn CORE OR EQUIVALENT	NA	NA
2	WIRE	POLYURETHANE ENAMELLED COPPER WIRE OR EQUIVALENT	E258243	180°C
3	SOLDER	Sn99.3-Cu0.7 OR EQUIVALENT	NA	NA

\*NA:NOT APPLICABLE.

文件编号 File Number	SRD-WI-3652	版本号 Version Number	A	页码 page	2/3
---------------------	-------------	-----------------------	---	------------	-----

## 5、电性能参数表 Electrical Characteristics List

规格型号 Part NO.	电感量 Tolerance( $\mu$ H)	测试频率 Test Freq. (kHz/v)	直流电阻 DCR Max ( $\Omega$ )	饱和电流 Isat (A)
SCD.4532.DYFR33MT00	0.33	100 / 0.25	0.01	4.00
SCD.4532.DYF1R0MT00	1.0	100 / 0.25	0.02	2.60
SCD.4532.DYF2R2MT00	2.2	100 / 0.25	0.04	2.30
SCD.4532.DYF3R3MT00	3.3	100 / 0.25	0.05	2.10
SCD.4532.DYF3R9MT00	3.9	100 / 0.25	0.07	1.90
SCD.4532.DYF4R7MT00	4.7	100 / 0.25	0.08	1.60
SCD.4532.DYF5R6MT00	5.6	100 / 0.25	0.08	1.45
SCD.4532.DYF6R8MT00	6.8	100 / 0.25	0.10	1.35
SCD.4532.DYF8R2MT00	8.2	100 / 0.25	0.12	1.30
SCD.4532.DYF100KT00	10	100 / 0.25	0.15	1.00
SCD.4532.DYF120KT00	12	100 / 0.25	0.16	0.90
SCD.4532.DYF130KT00	13	100 / 0.25	0.17	0.85
SCD.4532.DYF150KT00	15	100 / 0.25	0.20	0.80
SCD.4532.DYF180KT00	18	100 / 0.25	0.23	0.70
SCD.4532.DYF220KT00	22	100 / 0.25	0.27	0.60
SCD.4532.DYF270KT00	27	100 / 0.25	0.331	0.55
SCD.4532.DYF330KT00	33	100 / 0.25	0.35	0.50
SCD.4532.DYF390KT00	39	100 / 0.25	0.40	0.48
SCD.4532.DYF470KT00	47	100 / 0.25	0.53	0.40
SCD.4532.DYF560KT00	56	100 / 0.25	0.60	0.38
SCD.4532.DYF680KT00	68	100 / 0.25	0.74	0.33
SCD.4532.DYF820KT00	82	100 / 0.25	0.88	0.29
SCD.4532.DYF101KT00	100	100 / 0.25	1.20	0.26
SCD.4532.DYF121KT00	120	100 / 0.25	1.25	0.24
SCD.4532.DYF151KT00	150	100 / 0.25	1.60	0.22
SCD.4532.DYF181KT00	180	100 / 0.25	2.00	0.19
SCD.4532.DYF221KT00	220	100 / 0.25	3.08	0.18
SCD.4532.DYF271KT00	270	100 / 0.25	3.25	0.16
SCD.4532.DYF331KT00	330	100 / 0.25	3.55	0.15

※公差Tolerance: N:±30%、M:±20%、K:±10%.

※工作温度Operating temperature rang: -40 °C to +125°C (Including Self-heating)


※储存温度Storage temperature rang: -40 °C to +125°C

Isat电流: 指使电感量比初始值下降10% ( The rated DC current is that which cause at 10% inductance reduction from the initial value ) 。




## 6、产品包装 Packaging

### 1) 载带包装示意图 Tape packing diagram




ITEM	W	A0	B0	K0	P	E	F	D0	P0	P2	T
DIM	12.00	4.90	4.30	3.60	8.00	5.50	1.75	1.50	4.00	2.00	0.40
TOLE	±0.3	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	+0.1	±0.1	±0.1	±0.05

### 2) 卷盘包装示意图 Tape packing diagram



### 3) 剥离强度要求 Peeling required

- ① F 力大小: 20~100g;
- ② 面带剥离角度: 165°~180°。



### 4) 包装数量 Packing quantity

项目	数量 (PCS)	尺寸规格 (mm)
盘	2000	13"
内盒	8000	340mm*340mm*65mm
外箱	16000	360mm*360mm*160mm

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fixed Inductors](#) category:*

*Click to view products by [SOREDE](#) manufacturer:*

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)