

◆ELECTRICAL CHARACTERISTICS:

SH.0406 Series

Part Number	L(uH)	Test Freq. (KHz/V)	DCR Max.(Ω)	IDC Max.(A)
SH.0406.1R0MT00	1.0	1.0/0.25	0.035	2.00
SH.0406.1R2MT00	1.2	1.0/0.25	0.058	1.95
SH.0406.1R5MT00	1.5	1.0/0.25	0.075	1.90
SH.0406.1R8MT00	1.8	1.0/0.25	0.110	1.80
SH.0406.2R2MT00	2.2	1.0/0.25	0.120	1.75
SH.0406.2R7MT00	2.7	1.0/0.25	0.125	1.68
SH.0406.3R3MT00	3.3	1.0/0.25	0.130	1.50
SH.0406.3R9MT00	3.9	1.0/0.25	0.135	1.45
SH.0406.4R7MT00	4.7	1.0/0.25	0.140	1.32
SH.0406.5R6MT00	5.6	1.0/0.25	0.145	1.23
SH.0406.6R8MT00	6.8	1.0/0.25	0.150	1.15
SH.0406.8R2MT00	8.2	1.0/0.25	0.160	1.10
SH.0406.100KT00	10	1.0/0.25	0.230	1.00
SH.0406.120KT00	12	1.0/0.25	0.240	0.97
SH.0406.150KT00	15	1.0/0.25	0.250	0.92
SH.0406.180KT00	18	1.0/0.25	0.330	0.86
SH.0406.220KT00	22	1.0/0.25	0.450	0.80
SH.0406.270KT00	27	1.0/0.25	0.500	0.71
SH.0406.330KT00	33	1.0/0.25	0.700	0.66
SH.0406.390KT00	39	1.0/0.25	0.740	0.60
SH.0406.470KT00	47	1.0/0.25	0.760	0.55
SH.0406.560KT00	56	1.0/0.25	0.800	0.50
SH.0406.680KT00	68	1.0/0.25	0.900	0.47
SH.0406.820KT00	82	1.0/0.25	0.950	0.43
SH.0406.101KT00	100	1.0/0.25	1.000	0.40
SH.0406.121KT00	120	1.0/0.25	1.100	0.37
SH.0406.151KT00	150	1.0/0.25	1.300	0.35
SH.0406.181KT00	180	1.0/0.25	1.500	0.32
SH.0406.221KT00	220	1.0/0.25	1.800	0.30
SH.0406.271KT00	270	1.0/0.25	1.900	0.27
SH.0406.331KT00	330	1.0/0.25	2.200	0.25
SH.0406.391KT00	390	1.0/0.25	2.700	0.22
SH.0406.471KT00	470	1.0/0.25	3.600	0.20
SH.0406.561KT00	560	1.0/0.25	4.200	0.19
SH.0406.681KT00	680	1.0/0.25	4.600	0.17
SH.0406.821KT00	820	1.0/0.25	5.700	0.16

Note:

- 1、Tolerance: N:±30% , M:±20% , K:±10%;
- 2、IDC: DC current at which the inductance drops approximate 10% from its value without current;

◆**ELECTRICAL CHARACTERISTICS:**

SH.0608 Series

Part Number	L(μ H)	Test Freq. (KHz/V)	DCR Max.(Ω)	IDC Max.(A)
SH.0608.3R3MT00	3.3	1.0/0.25	0.016	3.50
SH.0608.4R7MT00	4.7	1.0/0.25	0.020	3.00
SH.0608.6R8MT00	6.8	1.0/0.25	0.022	2.50
SH.0608.100KT00	10	1.0/0.25	0.039	2.00
SH.0608.150KT00	15	1.0/0.25	0.045	1.70
SH.0608.220KT00	22	1.0/0.25	0.062	1.40
SH.0608.330KT00	33	1.0/0.25	0.100	1.10
SH.0608.470KT00	47	1.0/0.25	0.150	0.95
SH.0608.680KT00	68	1.0/0.25	0.220	0.80
SH.0608.101KT00	100	1.0/0.25	0.350	0.65
SH.0608.151KT00	150	1.0/0.25	0.430	0.54
SH.0608.221KT00	220	1.0/0.25	0.900	0.44
SH.0608.331KT00	330	1.0/0.25	1.500	0.36
SH.0608.471KT00	470	1.0/0.25	1.800	0.30
SH.0608.681KT00	680	1.0/0.25	2.500	0.25
SH.0608.102KT00	1000	1.0/0.25	3.200	0.20
SH.0608.122KT00	1200	1.0/0.25	3.500	0.18
SH.0608.152KT00	1500	1.0/0.25	4.500	0.17
SH.0608.182KT00	1800	1.0/0.25	5.000	0.15
SH.0608.222KT00	2200	1.0/0.25	6.800	0.14
SH.0608.272KT00	2700	1.0/0.25	7.200	0.12
SH.0608.332KT00	3300	1.0/0.25	10.500	0.11
SH.0608.392KT00	3900	1.0/0.25	11.700	0.10
SH.0608.472KT00	4700	1.0/0.25	13.600	0.09
SH.0608.562KT00	5600	1.0/0.25	16.600	0.08
SH.0608.682KT00	6800	1.0/0.25	19.600	0.08
SH.0608.822KT00	8200	1.0/0.25	25.200	0.07
SH.0608.103KT00	10000	1.0/0.25	29.500	0.06
SH.0608.123KT00	12000	1.0/0.25	33.800	0.06
SH.0608.153KT00	15000	1.0/0.25	45.400	0.05
SH.0608.183KT00	18000	1.0/0.25	50.400	0.05
SH.0608.223KT00	22000	1.0/0.25	80.000	0.04
SH.0608.273KT00	27000	1.0/0.25	91.500	0.04
SH.0608.333KT00	33000	1.0/0.25	98.500	0.03
SH.0608.393KT00	39000	1.0/0.25	140.000	0.03
SH.0608.473KT00	47000	1.0/0.25	160.000	0.03

Note:

- 1、Tolerance: N: \pm 30% , M: \pm 20% , K: \pm 10%;
- 2、IDC: DC current at which the inductance drops approximate 10% from its value without current;

◆**ELECTRICAL CHARACTERISTICS:**

SH.0810 Series

Part Number	L(uH)	Test Freq. (KHz/V)	DCR Max.(Ω)	IDC Max.(A)
SH.0810.3R3MT00	3.3	1.0/0.25	0.012	5.00
SH.0810.3R9MT00	3.9	1.0/0.25	0.014	4.60
SH.0810.4R7MT00	4.7	1.0/0.25	0.016	4.30
SH.0810.5R6MT00	5.6	1.0/0.25	0.020	3.90
SH.0810.6R8MT00	6.8	1.0/0.25	0.022	3.70
SH.0810.8R2MT00	8.2	1.0/0.25	0.024	3.50
SH.0810.100KT00	10	1.0/0.25	0.025	3.20
SH.0810.120KT00	12	1.0/0.25	0.027	3.00
SH.0810.150KT00	15	1.0/0.25	0.033	2.80
SH.0810.180KT00	18	1.0/0.25	0.039	2.60
SH.0810.220KT00	22	1.0/0.25	0.047	2.40
SH.0810.270KT00	27	1.0/0.25	0.052	2.10
SH.0810.330KT00	33	1.0/0.25	0.075	1.90
SH.0810.390KT00	39	1.0/0.25	0.082	1.70
SH.0810.470KT00	47	1.0/0.25	0.100	1.50
SH.0810.560KT00	56	1.0/0.25	0.150	1.30
SH.0810.680KT00	68	1.0/0.25	0.180	1.20
SH.0810.820KT00	82	1.0/0.25	0.200	1.10
SH.0810.101KT00	100	1.0/0.25	0.210	0.90
SH.0810.121KT00	120	1.0/0.25	0.220	0.80
SH.0810.151KT00	150	1.0/0.25	0.240	0.72
SH.0810.181KT00	180	1.0/0.25	0.280	0.65
SH.0810.221KT00	220	1.0/0.25	0.350	0.60
SH.0810.271KT00	270	1.0/0.25	0.400	0.55
SH.0810.331KT00	330	1.0/0.25	0.470	0.50
SH.0810.391KT00	390	1.0/0.25	0.680	0.46
SH.0810.471KT00	470	1.0/0.25	0.800	0.42
SH.0810.561KT00	560	1.0/0.25	1.000	0.38
SH.0810.681KT00	680	1.0/0.25	1.200	0.35
SH.0810.821KT00	820	1.0/0.25	1.500	0.31
SH.0810.102KT00	1000	1.0/0.25	1.800	0.28
SH.0810.122KT00	1200	1.0/0.25	2.000	0.25
SH.0810.152KT00	1500	1.0/0.25	2.400	0.23
SH.0810.182KT00	1800	1.0/0.25	2.800	0.21
SH.0810.222KT00	2200	1.0/0.25	3.300	0.19
SH.0810.272KT00	2700	1.0/0.25	5.000	0.17

Note:

- 1、Tolerance: N:±30% , M:±20% , K:±10%;
- 2、IDC: DC current at which the inductance drops approximate 10% from its value without current;

◆**ELECTRICAL CHARACTERISTICS:**

SH.0912 Series

Part Number	L(uH)	Test Freq. (KHz/V)	DCR Max.(Ω)	IDC Max.(A)
SH.0912.1R0MT00	1.0	1.0/0.25	0.011	5.00
SH.0912.1R5MT00	1.5	1.0/0.25	0.012	4.80
SH.0912.1R8MT00	1.8	1.0/0.25	0.013	4.70
SH.0912.2R2MT00	2.2	1.0/0.25	0.015	4.60
SH.0912.3R3MT00	3.3	1.0/0.25	0.017	4.50
SH.0912.3R9MT00	3.9	1.0/0.25	0.019	4.30
SH.0912.4R7MT00	4.7	1.0/0.25	0.020	4.00
SH.0912.5R6MT00	5.6	1.0/0.25	0.023	3.80
SH.0912.6R8MT00	6.8	1.0/0.25	0.025	3.50
SH.0912.8R2MT00	8.2	1.0/0.25	0.027	3.00
SH.0912.100KT00	10	1.0/0.25	0.035	2.80
SH.0912.120KT00	12	1.0/0.25	0.040	2.70
SH.0912.150KT00	15	1.0/0.25	0.045	2.30
SH.0912.180KT00	18	1.0/0.25	0.050	2.10
SH.0912.220KT00	22	1.0/0.25	0.060	2.00
SH.0912.270KT00	27	1.0/0.25	0.070	1.70
SH.0912.330KT00	33	1.0/0.25	0.100	1.50
SH.0912.390KT00	39	1.0/0.25	0.120	1.40
SH.0912.470KT00	47	1.0/0.25	0.125	1.30
SH.0912.560KT00	56	1.0/0.25	0.130	1.20
SH.0912.680KT00	68	1.0/0.25	0.140	1.00
SH.0912.820KT00	82	1.0/0.25	0.150	0.90
SH.0912.101KT00	100	1.0/0.25	0.160	0.70
SH.0912.121KT00	120	1.0/0.25	0.250	0.68
SH.0912.151KT00	150	1.0/0.25	0.280	0.65
SH.0912.181KT00	180	1.0/0.25	0.320	0.60
SH.0912.221KT00	220	1.0/0.25	0.470	0.50
SH.0912.271KT00	270	1.0/0.25	0.530	0.45
SH.0912.331KT00	330	1.0/0.25	0.600	0.40
SH.0912.391KT00	390	1.0/0.25	0.850	0.35
SH.0912.471KT00	470	1.0/0.25	0.950	0.33
SH.0912.561KT00	560	1.0/0.25	1.100	0.30
SH.0912.681KT00	680	1.0/0.25	1.200	0.25
SH.0912.821KT00	820	1.0/0.25	1.300	0.20
SH.0912.102KT00	1000	1.0/0.25	1.400	0.18
SH.0912.152KT00	1500	1.0/0.25	2.900	0.15

Note:

- 1、Tolerance: N:±30% , M:±20% , K:±10%;
- 2、IDC: DC current at which the inductance drops approximate 10% from its value without current;

◆**ELECTRICAL CHARACTERISTICS:**

SH.1012 Series

Part Number	L(uH)	Test Freq. (KHz/V)	DCR Max.(Ω)	IDC Max.(A)
SH.1012.1R0MT00	1.0	1.0/0.25	0.010	6.00
SH.1012.1R5MT00	1.5	1.0/0.25	0.012	5.80
SH.1012.1R8MT00	1.8	1.0/0.25	0.014	5.70
SH.1012.2R7MT00	2.7	1.0/0.25	0.015	5.50
SH.1012.3R3MT00	3.3	1.0/0.25	0.018	5.30
SH.1012.3R9MT00	3.9	1.0/0.25	0.020	5.00
SH.1012.4R7MT00	4.7	1.0/0.25	0.023	4.90
SH.1012.5R6MT00	5.6	1.0/0.25	0.025	4.80
SH.1012.6R8MT00	6.8	1.0/0.25	0.027	4.60
SH.1012.8R2MT00	8.2	1.0/0.25	0.029	4.50
SH.1012.100KT00	10	1.0/0.25	0.031	4.40
SH.1012.120KT00	12	1.0/0.25	0.033	4.30
SH.1012.150KT00	15	1.0/0.25	0.035	4.20
SH.1012.180KT00	18	1.0/0.25	0.040	4.00
SH.1012.220KT00	22	1.0/0.25	0.045	3.80
SH.1012.270KT00	27	1.0/0.25	0.050	3.50
SH.1012.330KT00	33	1.0/0.25	0.055	3.00
SH.1012.390KT00	39	1.0/0.25	0.060	2.50
SH.1012.470KT00	47	1.0/0.25	0.080	2.30
SH.1012.560KT00	56	1.0/0.25	0.085	2.00
SH.1012.680KT00	68	1.0/0.25	0.095	1.90
SH.1012.820KT00	82	1.0/0.25	0.110	1.80
SH.1012.101KT00	100	1.0/0.25	0.140	1.70
SH.1012.121KT00	120	1.0/0.25	0.160	1.50
SH.1012.151KT00	150	1.0/0.25	0.180	1.40
SH.1012.181KT00	180	1.0/0.25	0.250	1.30
SH.1012.221KT00	220	1.0/0.25	0.280	1.00
SH.1012.271KT00	270	1.0/0.25	0.420	0.90
SH.1012.331KT00	330	1.0/0.25	0.540	0.80
SH.1012.391KT00	390	1.0/0.25	0.600	0.75
SH.1012.471KT00	470	1.0/0.25	0.660	0.70
SH.1012.561KT00	560	1.0/0.25	0.740	0.60
SH.1012.681KT00	680	1.0/0.25	0.840	0.55
SH.1012.821KT00	820	1.0/0.25	1.080	0.50
SH.1012.102KT00	1000	1.0/0.25	1.390	0.45
SH.1012.103KT00	10000	1.0/0.25	12.000	0.18

Note:

- 1、Tolerance: N:±30% , M:±20% , K:±10%;
- 2、IDC: DC current at which the inductance drops approximate 10% from its value without current;

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [SOREDE](#) manufacturer:

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)