

SPECIFICATION APPROVAL

产品承认书

ENGINEERING LABORATORY SPECIFICATION			ITEM NO	HY
			DATE	2011-9-10
NO	Item	Specifications	Conditions	
1	Part No	GD003		
2	Type	LOUD		
3	Dimension	φ30MM 20MM		
4	Voice Coil Imp	4 ± 15%Ohm	AT 1000 Hz 4.47V	
5	Input Power	Normal Input 3W	Maximum Inpu6W	
6	Resonance F0	530± 30% Hz	Input 1V without A baffle	
7	Output SPL	101±3 dB	At2W ON AXIS CALIBRATION ROM 0.05M MEASVRMENT CRY6125Y LABORATORY FREE FIELD AT 1000 Hz	
8	Response	SPL-10dB FO ~20 K Hz MAX		
9	Polarity	When a positive D.C.current is applied to the voice coil terminal marked to the diaphragm shall move for ward		
10	Operation Test	Must be normal at program Source	4.47V	
11	Buzz Rattle Etc	Must be normal at Sine Wave	4.47V	
12	Load Test	After test meet item White noise	3W 48 Hours	
13	Distortion	7% MAX	AT 1000 Hz3W	
14	Total Weight			
15	Heat Temperature Test	After 55 ± 3 48Hour		
16	Low Temperature Test	After -25 ± 3 48Hour		
17	Humidity Test	After 40 ± 3 90~95%R.H. 48Hour		
Remark:				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [SparkFun Accessories](#) category:

Click to view products by [SparkFun](#) manufacturer:

Other Similar products are found below :

[DEV-17119](#) [SEN-16474](#) [COM-11450](#) [BOB-00495](#) [BOB-00497](#) [PRT-08619](#) [PRT-12702](#) [SEN-13582](#) [TOL-11468](#) [ROB-09065](#) [COM-12999](#)
[COM-12986](#) [COM-11120](#) [ROB-11965](#) [COM-11222](#) [PRT-12845](#) [CAB-13685](#) [PRT-10210](#) [PRT-14490](#) [TOL-10603](#) [COM-09278](#) [PRT-08023](#)
[COM-08033](#) [DEV-14052](#) [PRT-00111](#) [PRT-08432](#) [TOL-09317](#) [TOL-10997](#) [PRT-00743](#) [PRT-14492](#) [TOL-14228](#) [COM-13247](#) [PRT-11026](#)
[CAB-10646](#) [TOL-08964](#) [PRT-00116](#) [PRT-08506](#) [CAB-09741](#) [COM-10800](#) [SEN-14282](#) [DEV-14012](#) [CAB-14043](#) [COM-14452](#) [TOL-14508](#)
[DEV-13814](#) [GPS-00574](#) [PRT-14417](#) [PRT-08231](#) [COM-09939](#) [PRT-13839](#)