

Features:


◆Capacity : 3~200kg


◆Material: aluminum-alloy or alloy steel

◆Type: Parallel beam type ◆Defend grade: IP65

◆Application: Palm scale, kitchen scale, electronic balance, fishing scale, electronic platform scale and other electronic weighing devices.

Electrical connection and Dimensions: (dimension unit: mm)





Specifications:		
capacity	kg	3,5,10,20,25,30,50(aluminum); 80,100,120,200(alloy steel)
safe overload	%FS	120
ultimate overload	%FS	150
rated output	mV/V	1.0 ± 0.15
excitation voltage	Vdc	5 ~ 10
combined error	%FS	± 0.05
zero unbalance	%FS	± 0.1
non-linearity	%FS	± 0.05
hysteresis	%FS	± 0.05
repeatability	%FS	± 0.03
creep	%FS/3min	± 0.05
input resistance	Ω	1000 ± 15
output resistance	Ω	1000 ± 10
insulation resistance	ΜΩ	≥ 2000
operating temperature range	°C	-10 ~ +55
compensated temperature range	℃	-10 ~ +40
temperature coefficient of SPAN	%FS/10°C	± 0.05
temperature coefficient of ZERO	%FS/10°C	± 0.05
Electrical connection	cable	4 color wire (standard)or 4 shielded PVC cable, Ø0.8 × 220 mm

**Ordering code: model-capacity- rated output-accuracy-defend grade- the length of cable

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for SparkFun Accessories category:

Click to view products by SparkFun manufacturer:

Other Similar products are found below:

DEV-17119 SEN-16474 COM-11450 BOB-00495 BOB-00497 PRT-08619 PRT-12702 SEN-13582 TOL-11468 ROB-09065 COM-12999 COM-12986 COM-11120 ROB-11965 COM-11222 PRT-12845 CAB-13685 PRT-10210 PRT-14490 TOL-10603 COM-09278 PRT-08023 COM-08033 DEV-14052 PRT-00111 PRT-08432 TOL-09317 TOL-10997 PRT-00743 PRT-14492 TOL-14228 COM-13247 PRT-11026 CAB-10646 TOL-08964 PRT-00116 PRT-08506 CAB-09741 COM-10800 SEN-14282 DEV-14012 CAB-14043 COM-14452 TOL-14508 DEV-13814 GPS-00574 PRT-14417 PRT-08231 COM-09939 PRT-13839