Datasheet revision 1.3 www.chipquik.com

Liquid Flux No-Clean in 10ml (0.34oz) Pen w/tip

Product Highlights

A liquid flux that is non-flammable
No-Clean
Water-Based, leaves no residues
VOC Free, Halide Free, Rosin Free
Ideal for all rework, solder, and de-solder applications
Excellent wetting
Easily cleaned with isopropyl alcohol (IPA)
Can be used with Leaded and Lead-Free applications
RoHS II and REACH compliant

Specifications

Flux Type: No-Clean Liquid Flux (for Leaded and Lead-Free applications)

Flux Classification: INM0 Packaging: 10ml Pen

Shelf Life: Refrigerated >24 months, Unrefrigerated >24 months

Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

Cleaning

This is a no-clean liquid flux, post-use cleaning is not required.

Conforms to the following Industry Standards:

J-STD-004B, Amendment 1 (Solder Fluxes):

RoHS 2 Directive 2011/65/EU:

Yes

Yes

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for SparkFun Accessories category:

Click to view products by SparkFun manufacturer:

Other Similar products are found below:

DEV-17119 SEN-16474 COM-11450 BOB-00495 BOB-00497 PRT-08619 PRT-12702 SEN-13582 TOL-11468 ROB-09065 COM-12999 COM-12986 COM-11120 ROB-11965 COM-11222 PRT-12845 CAB-13685 PRT-10210 PRT-14490 TOL-10603 COM-09278 PRT-08023 COM-08033 DEV-14052 PRT-00111 PRT-08432 TOL-09317 TOL-10997 PRT-00743 PRT-14492 TOL-14228 COM-13247 PRT-11026 CAB-10646 TOL-08964 PRT-00116 PRT-08506 CAB-09741 COM-10800 SEN-14282 DEV-14012 CAB-14043 COM-14452 TOL-14508 DEV-13814 GPS-00574 PRT-14417 PRT-08231 COM-09939 PRT-13839