



AK 56



AK 56


Small-scale distributors

CUSTOMIZE

315 x 750 x 155 mm
Article number: 73345601

Small-scale distributors - Industrial Quality -, 4-row, 56 distribution units, 150 mm rail spacing, integrated ventilation elements to reduce the formation of condensate water, screwless PE/N terminal rails each with 6 screwable clamping points, 2.5 - 16 mm², elastic entries on top, masking and labelling strips, additional double membrane seals and further accessories

Screwless PE/N terminal rail, each with 6 screw-type clamping units 2.5 - 16 mm², 21 / 2 x 14 screwless clamping points 1.5 mm² - 4 mm²



Technical data

Measures

Width:	315 mm
Length:	750 mm
Height:	155 mm
Inner height:	95 mm
Inner width:	295 mm
Inner length:	730 mm

Material:

Box:	Polycarbonate
Cover:	Polycarbonate
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Highlights

Reliable - The high protection class (IP65) and the robust, halogen-free design ensure reliable operation even in a tough industrial environment.

Certificates



Accessory

- AK3 KBL - Cable cover with document compartment
- AK3 TW - Partition wall
- AK3 NS35-14 - Standard rail
- AK3 NS35-275 - Standard rail
- AK3 ABL-ES - External fixing lugs
- AK3 STD - Schuko mounting socket



SMALL-SCALE DISTRIBUTORS

AK 56

material:	Polycarbonate
Hinged window:	Polycarbonate, transparent

Other attributes

Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
Impact resistance:	IK08
Tackable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Color:	Grey
Rated insulation voltage AC:	1000 V
Rated insulation voltage DC:	1500 V
sealable:	Yes
Functional integrity:	none
Number of distribution units:	56
EMC design:	No
with lock:	No
Cover screw torque:	1.2 N m

AK3 KS M50 - Combination cable gland

AK AS - Masking off strips

AK AS-v - Masking off strips

AK SGA-1 - Lock fittings

AK SGA-2 - Lock fittings

KLS N 35 - Terminal block

KLS PE 35 - Terminal block

KST M25-33 - Combi connector

AK N-SL - Terminal rails

Environmental attributes

Ambient temperature (min.):	-35 °C
Ambient temperature (max.):	80 °C
Ambient temperature (24 h):	60 °C
Max. rel. humidity at 25° C (short term):	90%
Max. rel. humidity at 40° C:	50%

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Electrical Enclosures](#) category:

Click to view products by [Spelsberg](#) manufacturer:

Other Similar products are found below :

[120-902](#) [120-905](#) [120-403](#) [120-475](#) [120-901](#) [127-410](#) [130-007](#) [130-504](#) [130-506](#) [MR-25L+](#) [30-8739](#) [PIP-11774SCREW](#) [30-9715](#) [MR-25LW+](#) [110-407](#) [111-004](#) [111-008](#) [110-402](#) [110-901](#) [110-907](#) [111-002](#) [110-406](#) [110-910](#) [110-404](#) [110-409](#) [110-410](#) [120-405](#) [106-009](#) [106-505](#) [105-401](#) [106-006](#) [104-406](#) [137-002](#) [105-405](#) [111-005](#) [127-909](#) [106-502](#) [130-475](#) [130-503](#) [127-401](#) [106-010](#) [127-455](#) [127-475](#) [110-903](#) [R260-180-300](#) [9511020](#) [9822029](#) [9820014](#) [P61603000P](#) [9823009](#)