



**40V /35A Single N Power MOSFET**
**General Description**

40V /35A Single N Power MOSFET

Very low on-resistance RDS(on) @ VGS=4.5 V

Pb-free lead plating; RoHS compliant

<b>V<sub>DS</sub></b>	40	V
<b>R<sub>D(S(on))</sub>, TYP@VGS=10V</b>	13.3	mΩ
<b>R<sub>D(S(on))</sub>, TYP@VGS=4.5</b>	20.9	mΩ
<b>I<sub>D</sub></b>	35	A



Part ID	Package Type	Marking	Tape and reel infomation
SM4186T9RL	TO-252	35N04	2500


 100% UIS Tested  
100% Rg Tested

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	V <sub>DS</sub>	40	V
Gate-Source Voltage	V <sub>GS</sub>	20	±V
Continuous Drain Current A	I <sub>D</sub>	35.0	A
		27.0	
Pulsed Drain Current B	I <sub>DM</sub>	56.0	
Avalanche Current G	I <sub>AR</sub>	11.2	
Repetitive avalanche energy L=0.1mH G	E <sub>AR</sub>	25.8	mJ
Power Dissipation A	P <sub>D</sub>	50	W
		25*	
Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to 150	°C

**Thermal Characteristics**

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient A	R <sub>θJA</sub>	47	71	°C/W
Maximum Junction-to-Ambient A		95	114	°C/W
Maximum Junction-to-Lead c	R <sub>θJL</sub>	28	45	°C/W

## STATIC PARAMETERS







Symbol	Parameter	Conditions	Min	Typ	Max	Units
$BV_{DSS}$	Drain-Source Breakdown Voltage	$I_D = -250\mu A, V_{GS} = 0V$	40			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=40V, V_{GS}=0V$			1	uA
					5	
$I_{GSS}$	Gate-Body leakage current	$V_{DS} = 0V, V_{GS} = \pm 20V$			$\pm 100$	nA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu A$	1.4	2	2.7	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=10V, I_D=20A$		13.3	19.0	$m\Omega$
		$V_{GS}=4.5V, I_D=20A$		20.9	27.2	
$g_{FS}$	Forward Transconductance	$V_{DS}=5V, I_D=20A$		79		S
$V_{SD}$	Diode Forward Voltage	$I_S=1A, V_{GS}=134V$		0.72	1	V
$I_S$	Maximum Body-Diode Continuous Current				35	A






## DYNAMIC PARAMETERS

Symbol	Parameter	Conditions	Min	Typ	Max	Units
$C_{iss}$	Input Capacitance	$V_{GS}=0V, V_{DS}=15V, f=1MHz$		980	1195	pF
$C_{oss}$	Output Capacitance			130	159	pF
$C_{rss}$	Reverse Transfer Capacitance			80	95	pF
$R_g$	Gate resistance	$V_{GS}=0V, V_{DS}=0V, f=1MHz$			2.25	$\Omega$

## SWITCHING PARAMETERS

Symbol	Parameter	Conditions	Min	Typ	Max	Units
$Q_g(10V)$	Total Gate Charge	$V_{GS}=10V, V_{DS}=15V, I_D=20A$		9		nC
$Q_g 4.5V$	Total Gate Charge			4.5		
$Q_{gs}$	Gate Source Charge			3.15		
$Q_{gd}$	Gate Drain Charge			4.5		
$t_{D(on)}$	Turn-On Delay Time	$V_{GS}=10V, V_{DS}=15V, RL=0.75\Omega, R_{GEN}=3\Omega$		6		ns
$t_r$	Turn-On Rise Time			4.8		
$t_{D(off)}$	Turn-Off Delay Time			16.8		
$t_f$	Turn-Off Fall Time			5.4		
$t_{rr}$	Body Diode Reverse Recovery Time	$I_F=-8A, dI/dt=500A/\mu s$		12		ns
$Q_{rr}$	Body Diode Reverse Recovery Charge	$I_F=18A, dI/dt=500A/\mu s$		31		nC

**ESSENTIAL ELECTRICAL AND THERMAL CHARACTERISTICS**

**Fig 1: On-Region Characteristics (Note E)**

**Figure 2: Transfer Characteristics (Note E)**

**Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)**

**Figure 4: On-Resistance vs. Junction Temperature (Note E)**

**Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)**

**Figure 6: Body-Diode Characteristics (Note E)**

**ESSENTIAL ELECTRICAL AND THERMAL CHARACTERISTICS**

**Figure 7: Gate-Charge Characteristics**

**Figure 8: Capacitance Characteristics**

**Figure 9: Maximum Forward Biased Safe Operating Area (Note F)**

**Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)**

**Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)**

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by SPS manufacturer:***

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)  
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)  
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)  
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)  
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)  
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)