

Model Number: 4G-BA01

PRODUCT SPECIFICATION

I. Main features

*Electrical

No.	Item	Specifications
1	Frequency (MHz)	680-960/1710-2700
2	Gain (Zenith)	6dBi
3	V.S.W.R	<2
4	Impedance	50Ω
5	Max Input Power	50W
6	Lightning protection	DC ground
7	Polarization	V

*Mechanical

No.	Item	Specifications
1	Cable	RG58, 0m/3m/5m or others
2	Connector	Type SMA,N-female, or others
3	Dimensions (cm)	41x21x6,2
4	Weight (kg)	0,5
5	Mounting method	Pole/ Wall mount
6	Plastic Housing	White
7	Working Temperature	-40°C~+85°C
8	Working Humidity	5~95%

II. Appearance

4G-BA01-0



4G-BA01-1



4G-BA01-2



III. Engineering drawing



Unit : mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antennas](#) category:

Click to view products by [SR Passives](#) manufacturer:

Other Similar products are found below :

[GAN30084EU](#) [930-033-R](#) [GW17.07.0250E](#) [1513563-1](#) [EXE902SM](#) [APAMPG-117](#) [MAF94383](#) [W3908B0100](#) [W6102B0100](#) [YE572113-30RSMM](#) [108-00014-50](#) [66089-2406](#) [SPDA17RP918](#) [A09-F8NF-M](#) [A09-F5NF-M](#) [RGFRA1903041A1T](#) [W3593B0100](#) [W3921B0100](#) [SIMNA-868](#) [SIMNA-915](#) [SIMNA-433](#) [W1044](#) [W1049B090](#) [A75-001](#) [WTL2449CQ1-FRSMM](#) [CPL9C](#) [EXB148BN](#) [0600-00060](#) [TRA9020S3PBN-001](#) [GD5W-28P-NF](#) [MA9-7N](#) [GD53-25](#) [GD5W-21P-NF](#) [C37](#) [MAF94051](#) [MA9-5N](#) [EXD420PL](#) [B1322NR](#) [QWFTB120](#) [MAF94300](#) [GPSMB301](#) [FG4403](#) [AO-AGSM-OM54](#) [5200232](#) [MIKROE-2349](#) [WCM.01.0111](#) [MIKROE-2393](#) [MIKROE-2352](#) [MIKROE-2350](#) [5200227](#)