

12965-3R Spare blades 18 mm

- 10 pieces
- for No 12965-3




| Code | g | g | g |
|-----------|----|----|---|
| 7925 1004 | 75 | 10 | |

12967 Wire stripping knife with hooked blade



- for cutting round the outer cable insulation and longitudinal cuts
- accurate, fast and safe stripping of all popular round cables from 4-28 mm ϕ
- no damage to the inner conductors thanks to infinitely variable adjustment of the cutting depth



| Code | g | g | g |
|-----------|----|---|---|
| 776200 10 | 82 | 1 | |

12967R Spare blade for No 12967



| Code | g | g | g |
|-----------|---|---|---|
| 792500 10 | 2 | 1 | |

10554 EURO voltage tester

- built to conform to the new EN standard
- tested to conform to the currently valid VDE GS standard
- with plastic handle
- AC 125-250 V



| Code | a mm | b mm | L mm | g | g |
|----------|------|------|------|----|----|
| 77450001 | 1 | 3.5 | 190 | 37 | 10 |

13000-13003 Hooks and picks

- universally applicable for punching holes in soft materials, fitting and removing small components such as simmerring seals and O-rings, seals, trim strip clips and panelling



| Code | No | L mm | Model | g | g |
|-----------|-------|------|----------|----|---|
| 7710 1000 | 13000 | 155 | straight | 22 | 5 |
| 7710 1001 | 13001 | 155 | 45° | 22 | 5 |
| 7710 1002 | 13002 | 155 | 90° | 22 | 5 |
| 7710 1003 | 13003 | 155 | rounded | 24 | 5 |

13000/4 Set of hooks and picks

- Content: No 13000 (straight), 13001 (45°), 13002 (90°), 13003 (round)
- universally applicable for punching holes in soft materials, fitting and removing small components such as simmerring seals and O-rings, seals, trim strip clips and panelling
- in textile bag



| Code | L mm | g | g |
|-----------|------|-----|---|
| 9672 2802 | 165 | 144 | 1 |

13009 Split-pin puller



| Code | L mm | g | g |
|-----------|------|-----|---|
| 7710 1010 | 265 | 138 | 5 |

13126-1 LED torch

- ex-rated for zone 1
- Certifications: SEV 08 ATEX 0164, II 2G Ex e ib IIC T4, II 2D Ex e ibD 21 T98°C
- powerful, extremely durable 2 watt LEDs
- robust, electrically non-conducting, corrosion-proof housing made of ABS/polycarbonate
- high impact resistance and reduced glare thanks to rubber sheathed bezel
- consistently bright beam throughout 80% of the lifetime of the alkaline batteries due to eLED circuitry
- zoom with a twist of the bezel
- rubberised front pushbutton for continuous or momentary action
- waterproof to IP 68 down to 3 m depth of water
- hydrogen scrubber catalyst, polarised battery contacts and O-psi vent minimize explosive risk from leaking batteries
- battery compartment designed to facilitate rapid battery change
- Brightness: 250 lumen
- Range: 100 m
- Burn time: 5 hrs.
- Batteries: 4 AA/LR06, alkaline, 1.5 V (not supplied)



| Code | Dimensions mm | g | g |
|-----------|---------------|----|---|
| 774900 11 | 170 x 40 x 35 | 79 | 1 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hand Tools](#) category:

Click to view products by [Stahlwille](#) manufacturer:

Other Similar products are found below :

[58284-1](#) [662908-1](#) [68764-0001](#) [690619-6](#) [7-354778-7](#) [768531-1](#) [810131](#) [81541-16](#) [854183-1](#) [854358-1](#) [90855-1](#) [992258-1](#) [1-21046-3](#) [1-22145-3](#) [1-22278-2](#) [1-24954-2](#) [125529-5](#) [1-305579-8](#) [1320846-1](#) [1338618-1](#) [1338968-2](#) [1-354779-0](#) [1-354779-2](#) [1-354779-4](#) [1424443-1](#) [1424266-1](#) [1424289-1](#) [1424444-1](#) [MS24256A16](#) [1-525441-1](#) [1532195-2](#) [1538773-2](#) [1-692134-3](#) [HT-920A-124-HTELE-RPL-KIT](#) [1976923-1](#) [1976969-1](#) [2063794-1](#) [2063795-1](#) [2-21002-1](#) [2-21002-4](#) [2-21002-7](#) [2-21002-9](#) [2-21004-0](#) [229707-1](#) [911737-2](#) [91348-2](#) [925980-R](#) [301185-9](#) [983533-1](#) [1-694433-7](#)