



| Coil Data at 20 °C | Conditions | Min | Typ | Max | Unit |
|--------------------|------------|------|-----|-----|------|
| Coil resistance | | 72 | 80 | 88 | Ohm |
| Coil voltage | | | 5 | | VDC |
| Rated power | | | 313 | | mW |
| Thermal resistance | | | 80 | | K/W |
| Inductance | | | 21 | | mH |
| Pull-In voltage | | | | 3,5 | VDC |
| Drop-Out voltage | | 0,55 | | | VDC |

| Contact Data 85 | Conditions | Min | Typ | Max | Unit |
|------------------------------|---|-----|-----|-------|-------|
| Contact rating | Any DC combination of V & A not to exceed their individual max.'s | | | 100 | W |
| Switching voltage | DC or Peak AC | | | 1.000 | V |
| Switching current | DC or Peak AC | | | 1 | A |
| Carry current | DC or Peak AC 100% Duty Cycle | | | 2,5 | A |
| Contact resistance static | Measured with 40% overdrive | | | 150 | mOhm |
| Contact resistance dynamic | Maximum value 1,5 ms after excitation | | | 200 | mOhm |
| Insulation resistance | RH <45 %, 100 V test voltage | 10 | | | GOhm |
| Breakdown voltage (40-50 AT) | according to EN 60255-5 | 3 | | | kV DC |
| Capacitance | @ 10 kHz across open switch | | 0,5 | | pF |

| Special Product Data | Conditions | Min | Typ | Max | Unit |
|------------------------------------|-------------------------------------|---------------------------|-----|-----|-------|
| Dielectric Strength Coil/Contact | according to EN 60255-5 | 7 | | | kV DC |
| Insulation resistance Coil/Contact | RH <45 %, 200 VDC measuring voltage | 1 | | | TOhm |
| Capacity Coil/Contact | @ 10 kHz | | 1,2 | | pF |
| Housing material | | mineral filled epoxy | | | |
| Approval | | UL-File Nr. NRNT2.E156887 | | | |
| Reach II / RoHS conformity | | yes | | | |



Europe: +49 / 7731 8399 0

| Email: info@standexmeder.com

USA: +1 / 508 295 0771

| Email: salesusa@standexmeder.com

Asia: +852 / 2955 1682

| Email: salesasia@standexmeder.com

Item No.:

9005185400

Item:

KT05-1A-40L-THT

| Environmental data | Conditions | Min | Typ | Max | Unit |
|-----------------------|------------------------------------|--------------|-----|-----|------|
| Shock | 1/2 sine, duration 11ms, in 3 axis | | | 30 | g |
| Vibration | from 10 - 2000 Hz | | | 20 | g |
| Ambient temperature | | -40 | | 100 | °C |
| Storage temperature | | -40 | | 125 | °C |
| Soldering temperature | wave soldering max. 5 sec. | | | 260 | °C |
| Washability | | fully sealed | | | |

| General data | Conditions | Min | Typ | Max | Unit |
|--------------|------------|------------------|-----|-----|------|
| Packaging | | Tube per 15 pcs. | | | |

Modifications in the sense of technical progress are reserved

Designed at: 18.12.10 Designed by: DRUDOLF

Approval at: 27.07.12 Approval by: CRUF

Last Change at: 03.08.15 Last Change by: AAI

Approval at: 06.08.15 Approval by: DSTASTNY

Version: 10

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Reed Relays](#) category:

Click to view products by [Standexmeder](#) manufacturer:

Other Similar products are found below :

[M2C24AH](#) [D1A05HD-3](#) [741A10](#) [8000-0211](#) [8000-0217](#) [836C2](#) [922A06C4C](#) [PRMA1A12C](#) [PRMA1A24B](#) [PRMA1A24C](#) [PRMA1B12C](#)
[PRMA1B24C](#) [PRMA1C05F](#) [PRMA2A24C](#) [R1C5DR](#) [R2A5D](#) [1220-0039](#) [RA30521051](#) [RA31232051](#) [HGS1005](#) [HGS1021](#) [HGS1048](#)
[HGS1088](#) [HGS2MT51111F00](#) [HGS2MT51111M00](#) [HGZM1C24](#) [HGZM2C05](#) [HGZM2C48](#) [DA1A24DWD](#) [DA1A-24V](#) [DA1C05FWD](#)
[DA1C12FW](#) [DA2A-6V](#) [134MPCX-3](#) [MRR1ADS8-12D](#) [MRR1ADS8-24D](#) [MRR1ADS8-5D](#) [MRR1ADSK-12D](#) [159-151-T00](#) [MSS62A05](#)
[MSS71A05](#) [MSS71A05B](#) [MSS71A12](#) [MSS71A24](#) [1804-105](#) [191TE1C2M-5S](#) [191TE2A1-5G](#) [191TE2A1-6G](#) [193RE4C3-24G](#) [HYR2001-1520](#)