

# SOLDER WIRE ALU 1

## PRODUCT DESCRIPTION

ALU 1 is a flux cored solder wire for the soldering on pure aluminium and several aluminium alloys. The flux system ALU 1 does not contain any toxic substances. The flux is based on chemically modified resins and contains no natural rosin. The flux system passed the SIR-tested according to J-STD 004 and is therefore classified as a No-Clean flux.

## CHARACTERISTICS

The solder wire ALU 1 offers the following advantages:

- Flux content 3.5%
- Chemically modified resin, reducing the health risks of using rosin based fluxes
- Leaves just slightly coloured residues
- Does not contain any toxic substances
- Suitable for pure aluminium and several aluminium alloys
- No-Clean residues

## PHYSICAL PROPERTIES AND DATA

GENERAL PROPERTIES	SOLDER WIRE ALU 1	
Flux type:	REM 1 according to J-STD-004	
Flux content:	Standard 3,5% ± 0,3% (by weight)	
Halide content:	0,06%	
Aluminium coorosion:	None	
Copper corrosion effect:	None, according to J-STD-004	
Surface insulation resistance:	7 days @ 85°C / 85% r.H.	>10 <sup>8</sup> Ω
Standard alloys according to ISO 9453:2006	Lead-free (Ecoloy Serie):	
	Ecoloy TC (S-Sn99Cu1)	
Available diameters:	0.7/1.0 mm	
Available reel sizes:	250 g, 500 g, 1 kg	

Other alloys, flux contents and reel sizes are available on request.

## HEALTH & SAFETY

Prior to use, read the material safety data sheet and take all necessary safety precautions.

## NOTICE

The values in this document are typical values and do not constitute a specification. This data sheet has been published for information purposes only. Any verbal or written advise given, including information as regards the potential infringement of patents held by other parties, is not binding, irrespective of whether it was given by a member of staff of STANNOL or one of our sales representatives. It is the responsibility of the user to take all necessary precautions in order to ensure that our product is suitable for the intended purpose and application. Should STANNOL be found liable for damage caused by its product, compensation for damages shall be limited to that for defects in quality.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Solder](#) category:*

*Click to view products by [Stannol](#) manufacturer:*

Other Similar products are found below :

[600YSY](#) [701-2758](#) [707-1746](#) [707-1748](#) [707-1811](#) [707-1813](#) [707-1831](#) [707-1840](#) [707-1850](#) [707-1852](#) [13-217-3-01](#) [P10695](#) [SN63WRAP3-.022-1-LB](#) [DAC-061](#) [701-2089](#) [707-0285](#) [707-0366](#) [707-0441-26](#) [707-1774](#) [707-1810](#) [24-6337-9727](#) [601Y](#) [24-9574-7619](#) [24-4060-2437](#) [14-6040-0125](#) [04-0595-0000](#) [631960](#) [SW02-10](#) [S2626-O-T](#) [8055](#) [5760140](#) [TRWR-204](#) [1152](#) [EC2002M-1](#) [WPT17](#) [WS6016](#) [760-2028](#) [41-096-0202N](#) [41-096-0203N](#) [ART.AGT-030](#) [389289](#) [54068](#) [4900-18G](#) [478103](#) [570203](#) [811020](#) [811035](#) [813022](#) [SAC305 TELECORE HF-850/122 0,5MM 250G](#) [SAC305 TELECORE HF-850/122 1MM 500G](#)