

# EC Safety Data Sheet according to Directive 1907/2006

Trade name: Solder-wire HS10 2510 S-Sn60Pb40

Date of issue: 06.05.2003

Revised on: 23.11.2011

Date of print: 25.11.2011

Page: 1(3)

## 1. Identification of the substance/preparation and of the company/undertaking

### Information on the product

Trade name: **Solder-wire HS10 2510 S-Sn60Pb40**  
Usage of the product / preparation: Solder wire for soft soldering

### Identification of the manufacturer / supplier

Address: Stannol GmbH  
Oskarstr. 3 -7  
42283 Wuppertal  
Phone: 0202 585 0  
Fax: 0202 585 155  
Emergency call: 0202 585 119 (only during trading hour ( 8:00 h – 17:00 h)  
E-mail: werner.kruppa@stannol.de

## 2. Hazards identification

Not a composition for the purposes of the Dangerous Substances Regulations, but nevertheless observe items 4-16

### Additional hazards for human health and environment:

May cause occupational asthma

## 3. Composition/Information on ingredients:

Chemical characterization: Tin/Lead – alloy with flux max.3,5 % (halide activated)

### Composition according to EC 1907/2006:

Contents	CAS No.	EINECS No.	Symbols	R-phrases:	Substance
59,5-60,5%	7440-31-5	231-141-8			Tin
Remainder	7439-92-1	231-131-3			Lead
<3,5%	8050-09-7	232-475-7	Xi	43	Rosin

The wording of the R-phrases stated is indicated in Section 16

## 4. First Aid measures

**General information:** If casualty is unconscious but breathing, place in the recovery position. If breathing has stopped apply artificial resuscitation or give oxygen by mask  
**After inhalation:** Remove patient to fresh air. If irritation persists, obtain medical attention.  
**After skin contact:** If any skin irritation develops seek medical attention  
**After eye contact:** Flush *immediately* with plenty of water. In cases where spitting flux has entered the eye seek medical attention.  
**After ingestion:** Rinse mouth immediately and drink plenty of water. Seek medical advice.  
**Hints for doctors.** Inhalation of the flux fumes given off at soldering temperatures will irritate the nose, throat and respiratory system.  
Repeated or prolonged exposure to flux fumes may cause shortness of breath and cough..

### Physician's information

**Treatment:** Decontamination, treatment of symptoms.

## 5. Fire fighting measures

**Suitable extinguishing media:** Use extinguishing media appropriate to surrounding fire conditions  
**Special protective equipment for fire fighting** Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

## 6. Accidental release measures

Pick up and place in appropriate container

## 7. Handling and storage

The fumes produced during soldering should be extracted away from the breathing zone of the operators. Ensure the area is well ventilated. Wash hands with soap and warm water after handling, particularly before eating, drinking or smoking.

The product should be stored in a cool, dry area.

# EC Safety Data Sheet according to Directive 1907/2006

Trade name: Solder-wire HS10 2510 S-Sn60Pb40

Date of issue: 06.05.2003

Revised on: 23.11.2011

Date of print: 25.11.2011

Page: 2(3)

## 8. Exposure controls and personal protection

### Additional information on system design:

Local exhaust or dilution ventilation and control of process conditions are suitable methods..

### Substances with limit values to be monitored at the working place:

#### Danger to health at the working place:

Peak limit category:

### Working place limit values according to TRGS 900 from Section 2 for Germany:

Product name	CAS No.	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>	Type	Category	Remarks
Tin	7440-31-5		2	MAK (NL)		
Lead	7439-92-1		0,1	MAK (TLV)		

### Working place limit values according to EH40/2005 of the UK:

Product name	CAS No.	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>	8h TWA reference period	15 min STEL reference period
Tin	7440-31-5		2		
Lead	7439-92-1		0,15		
Rosin-based solder flux fume	8050-09-7		0,05		0,15

**BAT-Value**  
Lead/blood level: 700µg/l,  
Women below 45 years: 300µg/l

**Skin resorption / Sensitization: Skin resorption ----**

**Sensitization: S(rosin)**

### General protection and hygiene measures

Avoid direct contact with eyes, the skin and clothing.

### Personal protection

#### Respiratory protection:

If concentrations are over the exposure limit, use a supplied air respirator.

#### Hand protection:

Use heat resistant gloves if required.

#### Eye protection:

Operators should wear goggles

#### Personal protection:

Light protective clothing

## 9. Physical and chemical properties

<b>Form:</b>	Form: Tin-Lead Solder
	Colour:silver
<b>Melting Point:</b>	183 °C
<b>Vapour Pressure:</b>	n.a.
<b>Density(20°C):</b>	7-9 g/cm <sup>3</sup>

## 10. Stability and reactivity

<b>Reaction with substances:</b>	Possible with oxidising agents.
<b>Hazardous combustion or decomposition products:</b>	Lead-oxides possible

## 11. Toxicological information

The toxicological classification of the product is based on the results of the calculation procedure of the general preparation directive 1999/45/EC.

### Acute Effects:

Acute intoxication by ingestion of skin contact with lead is improbable. High doses nevertheless lead to symptoms of poisoning. Inhalation of fumes can irritate the respiratory tract and eyes.. May cause occupational asthma

### All following items refer to pure lead

#### Acute Toxicity

Type	Value in mg/Kg	Form	Species
LD.LO	160	oral	pigeon
LD.LO	1000	ip	rat

LD.LO (oral, pigeon): 160 mg/kg; TD.LO (oral, woman): 450 mg/kg (damage to nervous system); LD.LO (ip., Rat): 1000 mg/kg; TC.LO(inhal., human): 10 mg/m<sup>3</sup> ;

# EC Safety Data Sheet according to Directive 1907/2006

Trade name: Solder-wire HS10 2510 S-Sn60Pb40

Date of issue: 06.05.2003

Revised on: 23.11.2011

Date of print: 25.11.2011

Page: 3(3)

## 12. Ecological information

General information:

Lead and combinations of lead are not biological reducible.

## 13. Disposal considerations

Disposal information

Product:

Contact a licensed professional waste disposal service to dispose of this material.

Further information:

Observe all federal, state and local environmental regulations. Collect metal for recycling

Waste identity number:

Waste identity number EAK-code: 120104

## 14. Transport information

GGVSEB/ADR/RID:

The product is not classified as hazardous for transport

## 15. Regulatory information;

Labelling information:

**The product is classified and labelled according to the EC Directives.**

Water hazard class:

Not subject to current legislation

Classification according to the TA Luft:

WGK 1 (weakly water-endangering)

Organic materials class III; whole-carbon-concentration: Max. acceptable

Emission 50 mg/m<sup>3</sup> (mass-flow-rate  $\geq$  0,5 kg/h)

Ingredients:

Tin, Lead, rosin

## 16. Other information

R-phrases point 3: 43 May cause sensitization by skin contact

n.a. not applicable

n.k. not known

German regulations:

See TRGS 505 "Lead and leaded dangerous compounds"

This statement is based on our current knowledge and offers no assurance of product properties.

Department issuing the data sheet

Stannol GmbH/Quality Assurance/Laboratory

Contact person

Dr. Kruppa

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [stannol](#) manufacturer:*

Other Similar products are found below :

[HS10 2510 1,2MM 250G STANNOL](#) [574114](#) [593311](#) [574007](#) [631946](#) [648111](#) [648110](#) [810843](#) [HS10 FAIR, 1.0MM, 250G](#) [HS10 2510](#)  
[1,0MM 250G](#) [574402](#) [574104](#) [631939](#) [810031](#) [535768](#) [574112](#) [593331](#) [810041](#) [594300](#) [631962](#) [HS10 FAIR, 1.0MM, 5G](#) [594050](#) [810899](#)  
[810812](#) [535759](#) [HS10 2510 0,5MM 500G](#) [593420](#) [574110](#) [594052](#) [810916](#) [631967](#) [574117](#) [810913](#) [593063](#) [631965](#) [810001](#) [535762](#)  
[810863](#) [810044](#) [810904](#) [810793](#) [535775](#) [574612](#) [574400](#) [810045](#) [593003](#) [593032](#) [810792](#) [HS10 2510 1,5MM 500G](#) [574106](#)