



**DESCRIPTION**

The ST1002 is the N-Channel logic enhancement mode power field effect transistor is produce using high cell density, DMOS trench technology. This high-density process is especially tailored to minimize on-state resistance. These device are particularly suited for low voltage application such as cellular phone and notebook computer power management and other battery powered circuits where high side switching.

**PIN CONFIGURATION**  
**SOT-23-3L**



1.Gate 2.Source 3.Drain

**PART MARKING**  
**SOT-23-3L**



Y: Year Code A: Produce Code

**FEATURE**

- 100V/3.0A,  $R_{DS(ON)} = 135m\Omega$   
@ $V_{GS} = 10V$
- 100V/2.5A,  $R_{DS(ON)} = 140m\Omega$   
@ $V_{GS} = 4.5V$
- Super high density cell design for extremely low  $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability
- SOT-23-3L package design





**ST1002**   
Lead-free

N Channel Enhancement Mode MOSFET

3.0A


**ABSOLUTE MAXIMUM RATINGS** (Ta = 25°C Unless otherwise noted )

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V <sub>DSS</sub>	100	V
Gate-Source Voltage	V <sub>GSS</sub>	±20	V
Continuous Drain Current T <sub>J</sub> =150°C	I <sub>D</sub>	T <sub>A</sub> =25°C 5.0	A
		T <sub>A</sub> =70°C 3.0	
Pulsed Drain Current	I <sub>DM</sub>	15	A
Continuous Source Current (Diode Conduction)	I <sub>S</sub>	1.9	A
Power Dissipation	P <sub>D</sub>	T <sub>A</sub> =25°C 2.0	W
		T <sub>A</sub> =70°C 1.2	
Operation Junction Temperature	T <sub>J</sub>	-55/150	°C
Storage Temperature Range	T <sub>STG</sub>	-55/150	°C
Thermal Resistance-Junction to Ambient	R <sub>θJA</sub>	75	°C/W


**ELECTRICAL CHARACTERISTICS** ( Ta = 25°C Unless otherwise noted )

Parameter	Symbol	Condition	Min	Typ	Max	Unit	
<b>Static</b>							
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	100			V	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1		2.5	V	
Gate Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 20V$			$\pm 100$	nA	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=80V, V_{GS}=0V$			1	uA	
		$V_{DS}=80V, V_{GS}=0V$ $T_J=55^\circ C$			10		
Drain-source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=3.0A$ $V_{GS}=4.5V, I_D=2.0A$		128 133	135 140	m $\Omega$	
Diode Forward Voltage	$V_{SD}$	$I_S=1.7A, V_{GS}=0V$			1.0	V	
<b>Dynamic</b>							
Total Gate Charge	$Q_g$	$V_{DS}=50V$ $V_{GS}=10V$ $I_D=2.0A$			45	nC	
Gate-Source Charge	$Q_{gs}$				7.2		
Gate-Drain Charge	$Q_{gd}$				22		
Input Capacitance	$C_{iss}$	$V_{DS}=30V$ $V_{GS}=0V$ $F=1MHz$		640		pF	
Output Capacitance	$C_{oss}$			160			
Reverse Transfer Capacitance	$C_{rss}$			88			
Turn-On Time	$t_{d(on)tr}$	$V_{DD}=30V$ $R_L=30\Omega$ $I_D=1.0A$ $V_{GEN}=10V$ $R_G=6\Omega$		11	21	nS	
Turn-Off Time	$t_{d(off)tf}$				10		19
					24		44
					21		39


**TYPICAL CHARACTERISTICS** (25°C Unless noted)




**Fig 1.** Typical Output Characteristics



**Fig 2.** Typical Output Characteristics







**Fig 3.** Typical Transfer Characteristics



**Fig 4.** Normalized On-Resistance Vs. Temperature

**TYPICAL CHARACTERISTICS** (25°C Unless noted)



TYPICAL CHARACTERISTICS (25°C Unless noted)




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms





Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case

**SOT-23-3L PACKAGE OUTLINE**


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.400	0.012	0.016
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.700REF		0.028REF	
L1	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [STANSON Tech](#) manufacturer:*

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)  
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [SQM120N06-3M5L-GE3](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#)  
[2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#)  
[DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)  
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)  
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)  
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [PJMF280N65E1\\_T0\\_00201](#) [PJMF380N65E1\\_T0\\_00201](#) [PJMF280N60E1\\_T0\\_00201](#)  
[PJMF600N65E1\\_T0\\_00201](#) [PJMF900N65E1\\_T0\\_00201](#) [PJMF900N60E1\\_T0\\_00201](#)