



## **Conductor Colors**

- 1.Blue-White/Blue
- 2.Orange-White/Orange
- 3.Green-White/Green
- 4.Brown-White/Brown

Model # 24-10525

## **SPECIFICATIONS**

Conductor material

Conductors 4 Pair

Bare Copper Solid Conductor Size 24AWG;  $1/0.50 \pm 0.008$  mm

Insulation Material Polyethylene Thickness 0.18±0.02 mm Diameter  $0.89 \pm 0.01 \text{ mm}$ 

Rip Cord Material Nylon

**Jacket Material** PVC (CMR/CMP)

**Jacket Thickness** 0.50 mm(Min. Thichness: 0.45mm)

Jacket Diameter  $5.0 \pm 0.10 \text{ mm}$ 

## **ELECTRICAL PROPERTIES**

Conductor Resistance Max. 93.8 ohms/km at 20 °C Insulation Resistance Min. 5000 mega ohms-km at 20°C Dielectric Test 1000V DC /1 min ; No Breakdown

75°C Temperature Rating Voltage Rating 30V

voltage rtating			00 (					
MHZ	Zin-OS (Ohm)	Fitted Z (Ohm)	SRL (dB)	ATT(PATCH) (dB/100M)	DELAY (ns/100M)	MAX. DELAY SKEW(ns/100M)	NEXT (dB)	PSNEXT (dB)
0.772			19.40	1.8	574.97	45.0	67	64
1			20.00	2	570	45.0	65.3	62.31
4			23.00	4.1	552.00	45.0	56.3	53.28
8			24.50	5.8	546.73	45.0	51.8	48.77
10			25.00	6.5	545.38	45.0	50.3	47.31
16	100±15	100±15	25.00	8.2	543.00	45.0	47.3	44.25
20			25.00	9.3	542.05	45.0	45.8	42.8
25			24.30	10.4	541.20	45.0	44.3	41.35
31.25			23.60	11.7	540.44	45.0	42.9	39.89
62.5			21.50	17	538.55	45.0	38.4	35.38
100			20.10	22	537.60	45.0	35.3	32.31

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for STELLAR LABS manufacturer:

Other Similar products are found below:

24-16410 24-16210 24-10220 555-11700 555-13890 83-9962 24-15418 24-15394 24-16041 24-16135 24-16147 24-1810 24-1830 83-16410 10DV-07203-R 24-15433 24-15434 24-15452 24-15984 24-15989 24-16012 24-833 555-27525 35-6075 24-15375 24-15104 24-15061 24-15053 24-15096 24-15158 24-16052 24-16145 24-1850 24-1855 83-12261 PSG91163 24-12291 24-12307 83-9961 24-15411 24-15436 24-15453 24-15103 24-16040 24-16095 24-10271 83-16413 24-15416 24-15439 24-15399