
life.augmented

EMIF06-HMC02F2

6-line IPAD™, EMI filter including ESD protection

Datasheet - production data



Features

- · 6 lines low-pass-filter
- · High efficiency in EMI filtering
- Very low PCB space consuming: < 4 mm²
- · Lead-free package
- Very thin package: 0.65 mm
- High efficiency in ESD suppression
- · High reliability offered by monolithic integration
- High reducing of parasitic elements through integration and wafer level packaging

Complies with the following standards

- IEC 61000-4-2 level 4 on external pins
 - 15 kV (air discharge)
 - 8 kV (contact discharge)
- MIL STD 883E Method 3015-6 Class 3

Applications

High Speed MultiMediaCard[™]

Description

The EMIF06-HMC02F2 is a highly integrated array designed to suppress EMI / RFI noise for High Speed MultiMediaCard™ port filtering. The EMIF06-HMC02F2 Flip-Chip packaging means the package size is equal to the die size.

Additionally, this filter includes an ESD protection circuitry which prevents the protected device from destruction when subjected to ESD surges up to 15 kV. Compared to EMIF06-HMC01F2, the EMIF06-HMC02F2 has its ground balls connected together internally.

Figure 1. Pin configuration (ball side)

4 3 2 1
O O O A
В
0 0 0 c
O O O D

Figure 2. Basic cell configuration




Table 1. Ball configuration

		_	
A1	cmd	C1	dat2
A2	clk	C2	gnd
А3	Vmmc/Vdd	C3	MMCdat1
A4	MMCclk	C4	MMCdat0
B1	dat1	D1	dat3
B2	dat0	D2	gnd
В3	gnd	D3	MMCdat3
B4	MMCcmd	D4	MMCdat2

TM: IPAD is a trademark of STMicroelectronics.

Electrical characteristics EMIF06-HMC02F2

1 Electrical characteristics

Table 2. Absolute maximum ratings ($T_{amb} = 25 \text{ °C}$)

Symbol	Parameter and test conditions	Value	Unit
V _{PP}	Internal pins (A4, B4, C3, C4, D3, D4): ESD discharge IEC61000-4-2, air discharge ESD discharge IEC61000-4-2, contact discharge External pins (A1, A2, A3, B1, B2, C1, D1): ESD discharge IEC61000-4-2, air discharge ESD discharge IEC61000-4-2, contact discharge	2 2 15 8	kV
T _j	Maximum junction temperature	125	°C
T _{op}	Operating temperature range	- 40 to + 85	°C
T _{stg}	Storage temperature range	- 55 to + 150	°C

Figure 3. Electrical characteristics (definitions)




Table 3. Electrical characteristics (T_{amb} = 25 °C)

Symbol	Test conditions	Tolerance	Min.	Тур.	Max.	Unit
V_{BR}	I _R = 1 mA		6			V
I _{RM}	V _{RM} = 3 V				0.1	μΑ
	$V_{BIAS} = 0 \text{ V}, V_{OSC} = 30 \text{ mV},$ f = 1 MHz				20	pF
$\begin{matrix} R_{2,}R_{3,}R_{4,} \\ R_{5,}R_{6,}R_{7} \end{matrix}$	I = 50 mA	±20%		50		Ω
R ₁₀ , R ₁₁ , R ₁₂ , R ₁₃	Ι = 50 μΑ	±30%		75		kΩ
R ₁₄	Ι = 200 μΑ	±30%		7		kΩ




Figure 5. Analog crosstalk versus frequency 0 X_{Talk}(dB) -10. -20. -30 -40 -50 -60. -70. F(Hz) -80_ 100k 1M 10M 100M 1G Dat0-MMCDat1

Figure 6. ESD response to IEC61000-4-2 (+8 kV contact discharge)





Figure 8. Junction capacitance versus reverse voltage applied (typical values)



Package information EMIF06-HMC02F2

2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK[®] packages, depending on their level of environmental compliance. ECOPACK[®] specifications, grade definitions and product status are available at: www.st.com. ECOPACK[®] is an ST trademark.

2.1 Flip-Chip package information






Figure 9. Flip-Chip package outline

2.2 Packing information

Figure 10. Tape and reel outline





Ordering information EMIF06-HMC02F2

3 Ordering information

Figure 13. Ordering information scheme




Table 4. Ordering information

Order code	Marking	Package	Weight	Base qty	Delivery mode
EMIF06-HMC02F2	LK	Flip chip	5.3 mg	5000	Tape and reel 7"

Note: More information are available in the application notes:

AN1235:"Flip chip: Package description and recommendations for use"

4 Revision history

Table 5. Document revision history

Date	Revision	Changes
02-Mar-2016	1	Initial release.



IMPORTANT NOTICE - PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics - All rights reserved



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for EMI Filter Circuits category:

Click to view products by STMicroelectronics manufacturer:

Other Similar products are found below:

761280-1 SBSGC0500224MXB SBSPP0250104MXT SBSPP0250154MXT SBSPP0500473MXT SBSPP1000102MXT

SBSPP1000153MXB SBSPP1000220MCT SBSPP1000332MXT SBSPP1000470MCT SBSPP1000471MCT SBSPP1000472MXT

SNZF220DFT1G CM1442-06CP EMI8041MUTAG SBSPP0500473MXB SBSPP0500683MXT SBSPP1000101MCT SBSPP1000220MCB

SBSPP1000221MCT EMIF06-USD05F3 EMIF03-SIM03F3 EMI7112FCTAG EMI7403FCTBG EMI2180MTTBG CM1442-08CP

CSPEMI204FCTAG SBSPP1000152MXT SBSGC5000473MXT SBSMC0500474MXT SBSMC1000334MXT EMI8043MUTAG

MEA2010PE360T001 NFA18SL307V1A45L 1-6609037-5 CM1690-06DE EMIF05-SK01F3 EMIF02-USB03F2 BNX022-01L

BNX024H01L BNX025H01L BNX026H01L NFA21SL806X1A48L NFL18SP157X1A3D NFL21SP106X1C3D NFL21SP207X1C3D

NFL21SP307X1C3D NFL21SP506X1C3D NFL21SP706X1C3D NFW31SP207X1E4L