



Data brief

SPC572LADPT80S, SPC572LADPT100S microcontroller premium evaluation boards for SPC572Lx



Features

SPC572LADPT80S, SPC572LADPT100S

- Open top MCU socket
- Flexible MCU clocking options:
 - 40 MHz crystal EVB clock circuit
 - 8 MHz EVB clock oscillator circuit
 - External clock via SMA connector
- · User reset switch with reset status LEDs
- 14-pin standard JTAG connector
- 34-pin connector for Nexus 2 interface
- 10-pin SIPI connector for Serial Interprocessor Interface
- Minimodule dimension: 127 mm X 114 mm
- Standard connectors to SPC58XXMB/SPC57XXMB

SPC58XXMB/SPC57XXMB

- SPC572Lx modular evaluation system
- Single 12 V external power supply
- Four on-board regulators:
 - 5.0 V, 3.3 V and 1.25 V switching regulators
 - 5 V linear regulator for the ADC supplies and references
 - Master power switch and regulator status LEDs
- Two 240-way high-density expansion connectors for MCU daughter cards
- All MCU signals readily accessible at a port-ordered group of 0.1" pitch headers
- RS232/SCI physical interface and standard DB9 female connector
- LINFlexD interface with two different style connectors
- Two high speed CAN-FD channels and two female standard DB9 connectors
- One potentiometer for analog voltage input and four user switches and 4 user LEDs, freely connectable

Product status link

SPC572LADPT80S

SPC572LADPT100S

r roduct summary		
Order code	SPC572LADPT80S	
Reference	Daughter card for SPC572Lx MCU in eTQFP80 package. (1)	
Order code	SPC572LADPT100S	
Reference	Daughter card for SPC572Lx MCU in eTQFP100 package. (1)	
Order code	SPC58XXMB	
Reference	Motherboard for SPC58/ SPC57 family devices.	
Order code	SPC57XXMB	
Reference	Motherboard for SPC58/ SPC57 family devices.	

The MCU is not included, it must be purchased separately. Please contact your sales representative for more details.

Description

The Premium Evaluation Boards System supports the 32-bit SPC572Lx STMicroelectronics' automotive microcontrollers.

The complete system consists of an SPC58XXMB/SPC57XXMB motherboard and an SPC572LADPTx daughter card which plugs into the motherboard. Different daughter cards are available for evaluating the whole family of device in all supported packages. All daughter cards are similar in design and concept.

The evaluation system (motherboard and daughter card) allows full access to the CPU, all the CPU's I/O signals, and the motherboard peripherals (such as CAN, SCI, LIN and FlexRAY). The daughter card itself can be used as a standalone unit when access to the I/O pins or peripherals is not needed. The MCU is not included, it must be purchased separately. Please contact your sales representative for more details.



Revision history

Table 1. Document revision history

Date	Version	Changes
01-Jul-2015	1	Initial release.
13-Dec-2019	2	Updated features. Added product status link table and product summary table. Minor text changes.

DB2624 - Rev 2 page 2/3



IMPORTANT NOTICE - PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics - All rights reserved

DB2624 - Rev 2 page 3/3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Daughter Cards & OEM Boards category:

Click to view products by STMicroelectronics manufacturer:

Other Similar products are found below:

ADZS-21262-1-EZEXT 27911 MPC5777C-416DS KITMPC5744DBEVM SPC56ELADPT144S TMDXRM46CNCD DM160216

MPC5777M-416DS EV-ADUCM350GPIOTHZ EV-ADUCM350-BIO3Z ATSTK521 1130 MA160015 MA180033 MA240013 MA240026

MA320014 MA330014 MA330017 TLK10034SMAEVM TMDSCNCD28054MISO MIKROE-2152 MIKROE-2154 MIKROE-2381

TSSOP20EV DEV-11723 MIKROE-1108 MIKROE-1516 SPS-READER-GEVK AC244049 AC244050 AC320004-3 2077

ATSMARTCARD-XPRO EIC - Q600 -230 ATZB-212B-XPRO SPC560PADPT100S SPC560BADPT64S MA180018 EIC - Q600 -220

AC164134-1 BOB-12035 BB-BONE-BATT-01 STM8/128-D/RAIS AC164127-6 AC164127-4 AC164134-3 AC164156 MA320021

MA320024