

SPC572L-DISP

SPC572L-DISP Discovery+ board

Data brief



Features

- SPC572L64E3 is 32-bit Power Architecture®VLE Compliant CPU core, single issue, single-precision floating-point operations. 1568 KB on-chip RWW flash memory. Supporting EEPROM emulation (32 KB). 64 KB general-purpose data SRAM. System Memory Protection Unit (SMPU) Integrated programmer - debugger.
- Board Supply: 12V (ext PSU) and USB
- Integrated programmer debugger.
- JTAG interface: standard 7x2 male 0.1" connector
- Mini JTAG connector: 2x5 0,05"
- 1 CAN port with transceiver
- 1 KLine with transceiver
- 1 USB virtual COM Port
- 3 LEDs for user purpose
- 20 MHz crystal
- The GIPOs and pins accesible by a 4x37 0.1" pin grid array
- Board size 153 x 102mm

Description

The SPC572L-DISP board helps the user to discover the SPC572L64E3 microcontroller with full access to CPUs, GPI/O's and peripherals such as CAN, FlexRay, LIN, UART at budget price. The discovery board includes a PLS debugger-programmer, two JTAG ports (2x7 -0.1" and 2x5 0.05") and an extension headers array (4x37 pins) to connect prototyping boards or additional modules. UDE software is available for free download and includes a perpetual 256 Kbyte debugging/programming license. Free ready-to-run application firmware examples are available inside SPC5Studio (www.st.com/spc5studio) to support quick evaluation and development. SPC5Studio includes visual configurable code generation engine, board support package (BSP), startup routines, interrupt services. SPC5Studio is available for free download.

An ST Community is available on ST WEB

Table 1.	Device	summary
----------	--------	---------

Order Code	Reference
SPC572L-DISP	SPC572L Discovery with SPC572L64E3

November 2018

1/4

For further information contact your local STMicroelectronics sales office.

1 System requirements, HW and SW resources

1.1 System requirements

- Windows PC
- USB cable: Type-A to mini-B
- PSU:12V, 2A (100÷240 Vac, EU plug)

1.2 Development toolchain

SPC5Studio.

1.3 Demonstration software

Demonstration software is preloaded in the MCU Flash memory for easy demonstration of the SPC572L-DISP in stand-alone mode.



2 Revision history

Table 2	. Document	revision	history
---------	------------	----------	---------

Date	Revision	Changes
19-Nov-2018	1	Initial release.



IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved

DB3708 Rev 1



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hardware Debuggers category:

Click to view products by STMicroelectronics manufacturer:

Other Similar products are found below :

 CWH-CTP-VSPA-YE
 IJET-RISCV
 410-251
 1550
 AC244028
 AC244045
 DV164045
 AC244036
 DB40
 LPC_DEBUG_2
 ATATMEL-ICE

 ATATMEL-ICE-BASIC
 76002055
 IJET
 AC162051
 AC162062
 AC162064
 AC162074
 AC162079
 AC162087
 AC162088

 AC244024
 AC244026
 AC244027
 AC244033
 AC244034
 AC244035
 AC244044
 AC244047
 AC244048
 AC244051
 AC244053

 AC244054
 AC320202
 DV164131
 DV164232
 PG164100
 ARM-USB-OCD-H
 ARM-USB-TINY-H
 32115
 ACC-DEBUG
 114991786

 8.07.10
 8.08.28
 8.18.00
 8.19.00
 8.19.28
 8.20.00