



# STH260N6F6-2

N-channel 60 V, 1.7 mΩ typ., 180 A STripFET™ VI DeepGATE™ Power MOSFET in H<sup>2</sup>PAK-2 package

Datasheet — production data

## Features

| Order code   | V <sub>DSS</sub> | R <sub>DS(on)</sub> max | I <sub>D</sub> |
|--------------|------------------|-------------------------|----------------|
| STH260N6F6-2 | 60 V             | < 2.4 mΩ                | 180 A          |

- Low gate charge
- Very low on-resistance
- High avalanche ruggedness

## Applications

- Switching applications

## Description

This device is an N-channel Power MOSFET developed using the 6<sup>th</sup> generation of STripFET™ DeepGATE™ technology, with a new gate structure. The resulting Power MOSFET exhibits the lowest R<sub>DS(on)</sub> in all packages.




Figure 1. Internal schematic diagram




Table 1. Device summary

| Order code   | Marking | Package              | Packaging     |
|--------------|---------|----------------------|---------------|
| STH260N6F6-2 | 260N6F6 | H <sup>2</sup> PAK-2 | Tape and reel |

# Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Electrical ratings</b> .....               | <b>3</b>  |
| <b>2</b> | <b>Electrical characteristics</b> .....       | <b>4</b>  |
|          | 2.1 Electrical characteristics (curves) ..... | 6         |
| <b>3</b> | <b>Test circuits</b> .....                    | <b>8</b>  |
| <b>4</b> | <b>Package mechanical data</b> .....          | <b>9</b>  |
| <b>5</b> | <b>Revision history</b> .....                 | <b>13</b> |

# 1 Electrical ratings

**Table 2. Absolute maximum ratings**

| Symbol         | Parameter   | Value       | Unit                |
|----------------|---|-------------|---------------------|
| $V_{DS}$       | Drain-source voltage  | 60          | V                   |
| $V_{GS}$       | Gate-source voltage   | $\pm 20$    | V                   |
| $I_D$          | Drain current (continuous) at $T_C = 25\text{ }^\circ\text{C}$  | 180         | A                   |
| $I_D$          | Drain current (continuous) at $T_C = 100\text{ }^\circ\text{C}$ | 180         | A                   |
| $I_{DM}^{(1)}$ | Drain current (pulsed)  | 720         | A                   |
| $P_{TOT}$      | Total dissipation at $T_C = 25\text{ }^\circ\text{C}$           | 300         | W                   |
|                | Derating factor   | 2           | W/ $^\circ\text{C}$ |
| $T_{stg}$      | Storage temperature   | - 55 to 175 | $^\circ\text{C}$    |
| $T_j$          | Operating junction temperature                                  |             |                     |

1. Current limited by package.

**Table 3. Thermal data**

| Symbol              | Parameter                                      | Value | Unit                      |
|---------------------|--|-------|---------------------------|
| $R_{thj-case}$      | Thermal resistance junction-case max           | 0.5   | $^\circ\text{C}/\text{W}$ |
| $R_{thj-pcb}^{(1)}$ | Thermal resistance junction-pcb max            | 35    | $^\circ\text{C}/\text{W}$ |
| $T_l$               | Maximum lead temperature for soldering purpose | 300   | $^\circ\text{C}$          |

1. When mounted on FR-4 board of 1 inch<sup>2</sup>, 2 oz Cu.

## 2 Electrical characteristics

( $T_{CASE} = 25\text{ °C}$  unless otherwise specified)

**Table 4. On/off states**

| Symbol        | Parameter  | Test conditions   | Min. | Typ. | Max.      | Unit               |
|---------------|--|---|------|------|-----------|--------------------|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage ( $V_{GS} = 0$ )  | $I_D = 250\ \mu A$  | 60   |      |           | V                  |
| $I_{DSS}$     | Zero gate voltage Drain current ( $V_{GS} = 0$ ) | $V_{DS} = 60\text{ V}$<br>$V_{DS} = 60\text{ V}, T_C = 125\text{ °C}$ |      |      | 1<br>100  | $\mu A$<br>$\mu A$ |
| $I_{GSS}$     | Gate-body leakage current ( $V_{DS} = 0$ )       | $V_{GS} = \pm 20\text{ V}$  |      |      | $\pm 100$ | nA                 |
| $V_{GS(th)}$  | Gate threshold voltage                           | $V_{DS} = V_{GS}, I_D = 250\ \mu A$                                   | 2    |      | 4         | V                  |
| $R_{DS(on)}$  | Static drain-source on-resistance                | $V_{GS} = 10\text{ V}, I_D = 60\text{ A}$                             |      | 1.7  | 2.4       | m $\Omega$         |

**Table 5. Dynamic**

| Symbol    | Parameter                    | Test conditions   | Min. | Typ.  | Max. | Unit |
|-----------|------------------------------|---|------|-------|------|------|
| $C_{iss}$ | Input capacitance            |   |      | 11800 |      | pF   |
| $C_{oss}$ | Output capacitance           | $V_{DS} = 25\text{ V}, f = 1\text{ MHz},$<br>$V_{GS} = 0$                                       | -    | 1235  | -    | pF   |
| $C_{rss}$ | Reverse transfer capacitance |   |      | 488   |      | pF   |
| $Q_g$     | Total gate charge            | $V_{DD} = 30\text{ V}, I_D = 120\text{ A},$<br>$V_{GS} = 10\text{ V}$<br><i>(see Figure 14)</i> |      | 183   |      | nC   |
| $Q_{gs}$  | Gate-source charge           |   | -    | 53    | -    | nC   |
| $Q_{gd}$  | Gate-drain charge            |   |      | 41    |      | nC   |

**Table 6. Switching times**

| Symbol       | Parameter           | Test conditions  | Min. | Typ.  | Max. | Unit |
|--------------|---------------------|--|------|-------|------|------|
| $t_{d(on)}$  | Turn-on delay time  | $V_{DD} = 30\text{ V}, I_D = 60\text{ A}$<br>$R_G = 4.7\ \Omega, V_{GS} = 10\text{ V}$<br><i>(see Figure 13)</i> | -    | 31.4  | -    | ns   |
| $t_r$        | Rise time           |  |      | 165   |      |      |
| $t_{d(off)}$ | Turn-off-delay time | <i>(see Figure 13)</i>   | -    | 144.4 | -    | ns   |
| $t_f$        | Fall time           |  |      | 62.6  |      |      |

**Table 7. Source drain diode**

| Symbol          | Parameter                     | Test conditions   | Min. | Typ. | Max. | Unit |
|-----------------|-------------------------------|---|------|------|------|------|
| $I_{SD}$        | Source-drain current          |   |      |      | 180  | A    |
| $I_{SDM}^{(1)}$ | Source-drain current (pulsed) |   |      |      | 720  | A    |
| $V_{SD}^{(2)}$  | Forward on voltage            | $I_{SD} = 180 \text{ A}, V_{GS} = 0$  |      |      | 1.1  | V    |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 120 \text{ A}, V_{DD} = 48 \text{ V}$<br>$di/dt = 100 \text{ A}/\mu\text{s},$<br>$T_j = 150 \text{ }^\circ\text{C}$<br><i>(see Figure 15)</i> | -    | 55.6 |      | ns   |
| $Q_{rr}$        | Reverse recovery charge       |   |      | 116  |      | nC   |
| $I_{RRM}$       | Reverse recovery current      |   |      | 3.8  |      | A    |

1. Current limited by package.
2. Pulsed: pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%

## 2.1 Electrical characteristics (curves)

Figure 2. Safe operating area




Figure 3. Thermal impedance




Figure 4. Output characteristics




Figure 5. Transfer characteristics




Figure 6. Normalized  $B_{V_{DS}}$  vs. temperature







Figure 7. Static drain-source on-resistance




**Figure 8. Gate charge vs. gate-source voltage**




**Figure 9. Capacitance variations**




**Figure 10. Normalized gate threshold voltage vs. temperature**



**Figure 11. Normalized on-resistance vs. temperature**



**Figure 12. Source-drain diode forward characteristics**



### 3 Test circuits

**Figure 13. Switching times test circuit for resistive load**



AM01468v1

**Figure 14. Gate charge test circuit**



AM01469v1

**Figure 15. Test circuit for inductive load switching and diode recovery times**




AM01470v1

**Figure 16. Unclamped inductive load test circuit**




AM01471v1

**Figure 17. Unclamped inductive waveform**



AM01472v1

**Figure 18. Switching time waveform**



AM01473v1



## 4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK<sup>®</sup> packages, depending on their level of environmental compliance. ECOPACK<sup>®</sup> specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

Table 8. H<sup>2</sup>PAK 2 leads mechanical data

| Dim. | mm    |      |       |
|------|-------|------|-------|
|      | Min.  | Typ. | Max.  |
| A    | 4.30  |      | 4.80  |
| A1   | 0.03  |      | 0.20  |
| C    | 1.17  |      | 1.37  |
| e    | 4.98  |      | 5.18  |
| E    | 0.50  |      | 0.90  |
| F    | 0.78  |      | 0.85  |
| H    | 10.00 |      | 10.40 |
| H1   | 7.40  |      | 7.80  |
| L    | 15.30 |      | 15.80 |
| L1   | 1.27  |      | 1.40  |
| L2   | 4.93  |      | 5.23  |
| L3   | 6.85  |      | 7.25  |
| L4   | 1.5   |      | 1.7   |
| M    | 2.6   |      | 2.9   |
| R    | 0.20  |      | 0.60  |
| V    | 0°    |      | 8°    |

Figure 19. H<sup>2</sup>PAK 2 leads drawing





Figure 20. H<sup>2</sup>PAK 2 recommended footprint



## 5 Revision history

**Table 9. Document revision history**

| Date        | Revision | Changes   |
|-------------|----------|---|
| 31-May-2011 | 1        | First release.  |
| 25-Aug-2011 | 2        | Updated mechanical data.  |
| 01-Feb-2012 | 3        | Updated <i>Table 2: Absolute maximum ratings</i> .<br>Minor text changes. |
| 06-Jul-2012 | 4        | <i>Section 2.1: Electrical characteristics (curves)</i> has been added.   |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [STMicroelectronics](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [TPCC8103,L1Q\(CM](#)  
[MIC4420CM-TR](#) [VN1206L](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BUK954R8-60E](#)  
[DMN3404LQ-7](#) [NTE6400](#) [SQJ402EP-T1-GE3](#) [2SK2614\(TE16L1,Q\)](#) [2N7002KW-FAI](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-](#)  
[TL-W](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#)  
[NTE2967](#) [NTE2969](#) [NTE2976](#) [NTE455](#) [NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [DMN2080UCB4-7](#) [TK10A80W,S4X\(S](#)  
[SSM6P69NU,LF](#) [DMP22D4UFO-7B](#)