


## 30 V, 2 A low drop power Schottky rectifier



### Features

- Low forward voltage drop for less power dissipation
- Optimized conduction/reverse losses trade-off which lead to the highest efficiency in the applications
- Surface mount miniature package
- Avalanche rated
- ECOPACK<sup>2</sup> component

### Applications

- Cordless appliance
- SSD
- Battery charger
- Telecom power
- DC / DC converter

### Description

Single chip Schottky rectifiers designed for high frequency miniature switched mode power supplies such as adaptors and on board DC/DC converters.

Packaged in SMA, SMA Flat, SMA Flat Notch and SMB Flat, the STPS2L30 is ideal for use in parallel with MOSFETs in synchronous rectification.

| Product status       |         |
|----------------------|---------|
| STPS2L30             |         |
|                      |         |
| Product summary      |         |
| Symbol               | Value   |
| I <sub>F(AV)</sub>   | 2 A     |
| V <sub>RRM</sub>     | 30 V    |
| T <sub>j(max.)</sub> | 150 °C  |
| V <sub>F(typ.)</sub> | 0.325 V |

## 1 Characteristics

**Table 1.** Absolute ratings (limiting values at 25 °C, unless otherwise specified)

| Symbol      | Parameter                                             |                          | Value                         | Unit           |
|-------------|-------------------------------------------------------|--------------------------|-------------------------------|----------------|
| $V_{RRM}$   | Repetitive peak reverse voltage                       |                          | 30                            | V              |
| $I_{F(AV)}$ | Average forward current, $\delta = 0.5$ , square wave | SMA                      | $T_L = 120$ °C                | 2              |
|             |                                                       | SMA Flat, SMA Flat Notch | $T_L = 130$ °C                |                |
|             |                                                       | SMB Flat                 | $T_L = 135$ °C                |                |
| $I_{FSM}$   | Surge non repetitive forward current                  |                          | $t_p = 10$ ms sinusoidal      | 75             |
| $P_{ARM}$   | Repetitive peak avalanche power                       |                          | $t_p = 10$ µs, $T_j = 125$ °C | 108            |
| $T_{stg}$   | Storage temperature range                             |                          |                               | -65 to +150 °C |
| $T_j$       | Maximum operating junction temperature <sup>(1)</sup> |                          |                               | +150 °C        |

1.  $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$  condition to avoid thermal runaway for a diode on its own heatsink.

**Table 2.** Thermal resistance parameter

| Symbol        | Parameter        |                          | Max. value | Unit |
|---------------|------------------|--------------------------|------------|------|
| $R_{th(j-l)}$ | Junction to lead | SMA                      | 30         | °C/W |
|               |                  | SMA Flat, SMA Flat Notch | 20         |      |
|               |                  | SMB Flat                 | 15         |      |

For more information, please refer to the following application note :

- AN5088 : Rectifiers thermal management, handling and mounting recommendations

**Table 3.** Static electrical characteristics

| Symbol      | Parameter               | Test conditions |                 | Min. | Typ.  | Max.  | Unit |
|-------------|-------------------------|-----------------|-----------------|------|-------|-------|------|
| $I_R^{(1)}$ | Reverse leakage current | $T_j = 25$ °C   | $V_R = V_{RRM}$ | -    |       | 200   | µA   |
|             |                         | $T_j = 100$ °C  |                 | -    | 6     | 15    | mA   |
| $V_F^{(1)}$ | Forward voltage drop    | $T_j = 25$ °C   | $I_F = 2$ A     | -    |       | 0.45  | V    |
|             |                         | $T_j = 125$ °C  |                 | -    | 0.325 | 0.375 |      |
|             |                         | $T_j = 25$ °C   | $I_F = 4$ A     | -    |       | 0.53  |      |
|             |                         | $T_j = 125$ °C  |                 | -    | 0.43  | 0.51  |      |

1. Pulse test:  $t_p = 380$  µs,  $\delta < 2\%$

To evaluate the conduction losses, use the following equation:


$$P = 0.24 \times I_{F(AV)} + 0.068 \times I_F^2(\text{RMS})$$

For more information, please refer to the following application notes related to the power losses :


- AN604: Calculation of conduction losses in a power rectifier
- AN4021: Calculation of reverse losses on a power diode

## 1.1 Characteristics (curves)


**Figure 1. Average forward power dissipation versus average forward current**




**Figure 2. Average forward current versus ambient temperature ( $\delta = 0.5$ ) SMA**




**Figure 3. Average forward current versus ambient temperature ( $\delta = 0.5$ , SMB Flat)**




**Figure 4. Average forward current versus ambient temperature ( $\delta = 0.5$ , SMA Flat, SMA Flat Notch)**




**Figure 5. Normalized avalanche power derating versus pulse duration ( $T_j = 125^\circ\text{C}$ )**




**Figure 6. Relative variation of thermal impedance junction to ambient versus pulse duration (SMA)**




**Figure 7. Relative variation of thermal impedance junction to lead versus pulse duration (SMB Flat)**




**Figure 8. Relative variation of thermal impedance junction to ambient versus pulse duration (SMA Flat, SMA Flat Notch)**




**Figure 9. Reverse leakage current versus reverse voltage applied (typical values)**




**Figure 10. Junction capacitance versus reverse voltage applied (maximum values)**




**Figure 11. Forward voltage drop versus forward current (high level)**




**Figure 12. Forward voltage drop versus forward current (low level)**




**Figure 13. Thermal resistance junction to ambient versus copper surface under each lead (SMA)**



**Figure 14. Thermal resistance junction to ambient versus copper surface under each lead (SMA Flat, SMA Flat Notch)**



**Figure 15. Thermal resistance junction to ambient versus copper surface under each lead (SMB Flat)**



## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

### 2.1 SMA package information

- Epoxy meets UL94, V0
- Cooling method : by conduction (C)

Figure 16. SMA package outline





Table 4. SMA package mechanical data

| Ref. | Dimensions  |      |                             |       |
|------|-------------|------|-----------------------------|-------|
|      | Millimeters |      | Inches (for reference only) |       |
|      | Min.        | Max. | Min.                        | Max.  |
| A1   | 1.90        | 2.45 | 0.074                       | 0.097 |
| A2   | 0.05        | 0.20 | 0.001                       | 0.008 |
| b    | 1.25        | 1.65 | 0.049                       | 0.065 |
| c    | 0.15        | 0.40 | 0.005                       | 0.016 |
| D    | 2.25        | 2.90 | 0.088                       | 0.115 |
| E    | 4.80        | 5.35 | 0.188                       | 0.211 |
| E1   | 3.95        | 4.60 | 0.155                       | 0.182 |
| L    | 0.75        | 1.50 | 0.029                       | 0.060 |

**Figure 17. SMA recommended footprint in mm (inches)**



## 2.2 SMA Flat package information

- Epoxy meets UL94, V0
- Lead-free package

Figure 18. SMA Flat package outline





Table 5. SMA Flat package mechanical data

| Ref. | Dimensions  |      |      |                             |       |       |
|------|-------------|------|------|-----------------------------|-------|-------|
|      | Millimeters |      |      | Inches (for reference only) |       |       |
|      | Min.        | Typ. | Max. | Min.                        | Typ.  | Max.  |
| A    | 0.90        |      | 1.10 | 0.035                       |       | 0.044 |
| b    | 1.25        |      | 1.65 | 0.049                       |       | 0.065 |
| c    | 0.15        |      | 0.40 | 0.005                       |       | 0.016 |
| D    | 2.25        |      | 2.95 | 0.088                       |       | 0.117 |
| E    | 4.80        |      | 5.60 | 0.188                       |       | 0.221 |
| E1   | 3.95        |      | 4.60 | 0.155                       |       | 0.182 |
| L    | 0.75        |      | 1.50 | 0.029                       |       | 0.060 |
| L1   |             | 0.50 |      |                             | 0.020 |       |
| L2   |             | 0.50 |      |                             | 0.020 |       |


**Figure 19. SMA Flat recommended footprint in mm (inches)**



## 2.3 SMA Flat Notch package information

- Epoxy meets UL94, V0
- Cooling method: by conduction (C)
- Band indicates cathode


**Figure 20.** SMA Flat Notch package outline



**Table 6.** SMA Flat Notch package mechanical data

| Ref. | Dimensions  |      |      |                             |       |       |
|------|-------------|------|------|-----------------------------|-------|-------|
|      | Millimeters |      |      | Inches (for reference only) |       |       |
|      | Min.        | Typ. | Max. | Min.                        | Typ.  | Max.  |
| A1   | 0.90        |      | 1.10 | 0.035                       |       | 0.044 |
| A1   |             | 0.05 |      |                             | 0.002 |       |
| b    | 1.25        |      | 1.65 | 0.049                       |       | 0.065 |
| C    | 0.15        |      | 0.40 | 0.005                       |       | 0.016 |
| D    | 2.25        |      | 2.90 | 0.088                       |       | 0.115 |
| E    | 5.00        |      | 5.35 | 0.196                       |       | 0.211 |
| E1   | 3.95        |      | 4.60 | 0.155                       |       | 0.182 |
| G    |             | 2.00 |      |                             | 0.079 |       |
| G1   |             | 0.85 |      |                             | 0.033 |       |
| L    | 0.75        |      | 1.20 | 0.029                       |       |       |
| L1   |             | 0.45 |      |                             | 0.018 |       |
| L2   |             | 0.45 |      |                             | 0.018 |       |
| L3   |             | 0.05 |      |                             | 0.002 |       |
| V    |             |      | 8°   |                             |       | 8°    |
| V1   |             |      | 8°   |                             |       | 8°    |

**Figure 21. SMA Flat Notch recommended footprint in mm (inches)**



## 2.4 SMB Flat package information

- Epoxy meets UL94, V0
- Lead-free package

Figure 22. SMB Flat package outline





Table 7. SMB Flat mechanical data

| Ref. | Dimensions  |      |      |                             |       |       |
|------|-------------|------|------|-----------------------------|-------|-------|
|      | Millimeters |      |      | Inches (for reference only) |       |       |
|      | Min.        | Typ. | Max. | Min.                        | Typ.  | Max.  |
| A    | 0.90        |      | 1.10 | 0.035                       |       | 0.043 |
| b    | 1.95        |      | 2.20 | 0.077                       |       | 0.087 |
| c    | 0.15        |      | 0.40 | 0.006                       |       | 0.016 |
| D    | 3.30        |      | 3.95 | 0.130                       |       | 0.156 |
| E    | 5.10        |      | 5.60 | 0.201                       |       | 0.220 |
| E1   | 4.05        |      | 4.60 | 0.159                       |       | 0.181 |
| L    | 0.75        |      | 1.50 | 0.030                       |       | 0.059 |
| L1   |             | 0.40 |      |                             | 0.016 |       |
| L2   |             | 0.60 |      |                             | 0.024 |       |

Figure 23. Footprint recommendations, dimensions in mm (inches)



### 3 Ordering information

**Table 8. Ordering information**

| Order code  | Marking | Package        | Weight  | Base qty. | Delivery mode |
|-------------|---------|----------------|---------|-----------|---------------|
| STPS2L30A   | G30     | SMA            | 0.068 g | 5000      | Tape and reel |
| STPS2L30UF  | FG30    | SMB Flat       | 0.050 g | 5000      | Tape and reel |
| STPS2L30AFN | A23     | SMA Flat Notch | 0.039 g | 10 000    | Tape and reel |
| STPS2L30AF  | F30     | SMA Flat       | 0.035 g | 10000     | Tape and reel |

## Revision history

**Table 9. Document revision history**

| Date        | Version | Changes                                                                                                                                                                                                                     |
|-------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Jul-2003    | 3A      | Last update.                                                                                                                                                                                                                |
| Aug-2004    | 4       | SMA package dimensions update. Reference A1 max. changed from 2.70mm (0.106inc.) to 2.03mm (0.080).                                                                                                                         |
| 31-Jan-2007 | 5       | Reformatted to current standard. Added ECOPACK statement. Added SMB flat package.                                                                                                                                           |
| 23-Apr-2008 | 6       | Reformatted to current standards. Added SMA flat package.                                                                                                                                                                   |
| 30-Nov-2018 | 7       | Updated <a href="#">Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified)</a> and <a href="#">Figure 5. Normalized avalanche power derating versus pulse duration (T<sub>j</sub> = 125 °C)</a> . |
| 26-Sep-2019 | 8       | Added <a href="#">Section 2.3 SMA Flat Notch package information</a> .                                                                                                                                                      |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics – All rights reserved

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Schottky Diodes & Rectifiers category:***

***Click to view products by STMicroelectronics manufacturer:***

Other Similar products are found below :

[MA4E2039](#) [D1FH3-5063](#) [MBR0530L-TP](#) [MBR10100CT-BP](#) [MBR1545CT](#) [MMBD301M3T5G](#) [RB160M-50TR](#) [RB551V-30](#)  
[BAS16E6433HTMA1](#) [BAT 54-02LRH E6327](#) [NSR05F40QNXT5G](#) [NTE555](#) [JANS1N6640](#) [SB07-03C-TB-H](#) [SB1003M3-TL-W](#) [SK310-T](#)  
[SK32A-LTP](#) [SK33A-TP](#) [SK34B-TP](#) [SS3003CH-TL-E](#) [GA01SHT18](#) [CRS10I30A\(TE85L,QM](#) [MA4E2501L-1290](#) [MBRB30H30CT-1G](#)  
[SB007-03C-TB-E](#) [SK32A-TP](#) [SK33B-TP](#) [SK35A-TP](#) [SK38B-TP](#) [NRVBM120LT1G](#) [NTE505](#) [NTSB30U100CT-1G](#) [SS15E-TP](#) [VS-6CWQ10FNHM3](#) [ACDBA1100LR-HF](#) [ACDBA1200-HF](#) [ACDBA140-HF](#) [ACDBA2100-HF](#) [ACDBA3100-HF](#) [CDBQC0530L-HF](#)  
[CDBQC0240LR-HF](#) [ACDBA340-HF](#) [ACDBA260LR-HF](#) [ACDBA1100-HF](#) [SK310B-TP](#) [MA4E2502L-1246](#) [MA4E2502H-1246](#)  
[NRVBM120ET1G](#) [NSR01L30MXT5G](#) [NTE573](#)