


**HIGH EFFICIENCY ULTRAFAST DIODE**
**MAIN PRODUCT CHARACTERISTICS**

<b>I<sub>F(AV)</sub></b>	<b>3A</b>
<b>V<sub>RRM</sub></b>	<b>200 V</b>
<b>T<sub>j</sub> (max)</b>	<b>175 °C</b>
<b>V<sub>F</sub> (max)</b>	<b>0.75 V</b>
<b>t<sub>rr</sub> (max)</b>	<b>35 ns</b>

**FEATURES AND BENEFITS**

- Very low conduction losses
- Negligible switching losses
- Low forward and reverse recovery times
- High junction temperature


**DESCRIPTION**

The STTH302S, which is using ST's new 200V planar technology, is specially suited for switching mode base drive & transistor circuits.

The device is also intended for use as a free wheeling diode in power supplies and other power switching applications.

**ABSOLUTE RATINGS** (limiting values)

<b>Symbol</b>	<b>Parameter</b>		<b>Value</b>	<b>Unit</b>
V <sub>RRM</sub>	Repetitive peak reverse voltage		200	V
I <sub>F(AV)</sub>	Average forward current	T <sub>I</sub> = 107°C δ = 0.5	3	A
I <sub>FSM</sub>	Surge non repetitive forward current	t <sub>p</sub> = 10 ms Sinusoidal	100	A
T <sub>stg</sub>	Storage temperature range		- 65 + 175	°C
T <sub>j</sub>	Maximum operating junction temperature		175	°C

**THERMAL PARAMETERS**

<b>Symbol</b>	<b>Parameter</b>	<b>Maximum</b>	<b>Unit</b>
R <sub>th(j-l)</sub>	Junction to lead	20	°C/W

## STTH302S

### STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
$I_R^*$	Reverse leakage current	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$			3	$\mu\text{A}$
		$T_j = 125^\circ\text{C}$			4	75	
$V_F^{**}$	Forward voltage drop	$T_j = 25^\circ\text{C}$	$I_F = 3\text{ A}$			0.95	V
		$T_j = 125^\circ\text{C}$	$I_F = 3\text{ A}$		0.66	0.75	

Pulse test: \*  $t_p = 5\text{ms}$ ,  $\delta < 2\%$

\*\*  $t_p = 380\mu\text{s}$ ,  $\delta < 2\%$


To evaluate the maximum conduction losses use the following equation :

$$P = 0.60 \times I_{F(AV)} + 0.05 I_{F(RMS)}^2$$


### DYNAMIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
$t_{rr}$	Reverse recovery time	$T_j = 25^\circ\text{C}$	$I_F = 1\text{ A}$ $I_{rr} = -50\text{ A}/\mu\text{s}$ $V_R = 30\text{V}$			35	ns
$t_{fr}$	Forward recovery time	$T_j = 25^\circ\text{C}$	$I_F = 3\text{ A}$ $dI_F/dt = 50\text{ A}/\mu\text{s}$ $V_{FR} = 1.1 \times V_{Fmax}$		70		ns
$V_{FP}$	Forward recovery voltage	$T_j = 25^\circ\text{C}$	$I_F = 3\text{ A}$ $dI_F/dt = 50\text{ A}/\mu\text{s}$		1.6		V


**Fig. 1:** Average forward power dissipation versus average forward current.




**Fig. 2:** Average forward current versus ambient temperature ( $\delta = 0.5$ ).




**Fig. 3:** Relative variation of thermal impedance junction ambient versus pulse duration (Printed circuit board epoxy FR4).




**Fig. 4:** Forward voltage drop versus forward current.




**Fig. 5:** Junction capacitance versus reverse voltage applied (typical values).




**Fig. 6:** Reverse recovery time versus  $di_F/dt$  (90% confidence).




**Fig. 7:** Peak reverse recovery current versus  $di_F/dt$  (90% confidence).




**Fig. 8:** Reverse recovery charges versus  $di_F/dt$  (90% confidence).



**Fig. 9:** Relative variations of dynamic parameters versus junction temperature.




**Fig. 10:** Thermal resistance junction to ambient versus copper surface under each lead (epoxy FR4,  $e = 35\mu\text{m}$ ).



**PACKAGE MECHANICAL DATA**  
**SMC**

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	2.90	3.2	0.114	0.126
c	0.15	0.41	0.006	0.016
E	7.75	8.15	0.305	0.321
E1	6.60	7.15	0.260	0.281
E2	4.40	4.70	0.173	0.185
D	5.55	6.25	0.218	0.246
L	0.75	1.60	0.030	0.063

**FOOTPRINT**


Ordering code	Marking	Package	Weight	Base qty	Delivery mode
STTH302S	U32	SMC	0.245 g	2500	Tape & reel

- Epoxy meets UL 94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany  
 Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore  
 Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Rectifiers](#) category:*

*Click to view products by [STMicroelectronics](#) manufacturer:*

Other Similar products are found below :

[70HFR40](#) [RL252-TP](#) [150KR30A](#) [1N5397](#) [NTE5841](#) [NTE6038](#) [SCF5000](#) [1N4002G](#) [1N4005-TR](#) [JANS1N6640US](#) [481235F](#)  
[RRE02VS6SGTR](#) [067907F](#) [MS306](#) [70HF40](#) [T85HFL60S02](#) [US2JFL-TP](#) [A1N5404G-G](#) [CRS04\(T5L,TEMQ\)](#) [ACGRA4007-HF](#)  
[ACGRB207-HF](#) [CLH03\(TE16L,Q\)](#) [ACGRC307-HF](#) [ACEFC304-HF](#) [NTE6356](#) [NTE6359](#) [NTE6002](#) [NTE6023](#) [NTE6039](#) [NTE6077](#)  
[85HFR60](#) [40HFR60](#) [70HF120](#) [85HFR80](#) [D126A45C](#) [SCF7500](#) [D251N08B](#) [SCHJ22.5K](#) [SM100](#) [SCPA2](#) [SCH10000](#) [SDHD5K](#) [VS-](#)  
[12FL100S10](#) [ACGRA4001-HF](#) [D1821SH45T PR](#) [D1251S45T](#) [NTE5990](#) [NTE6358](#) [NTE6162](#) [NTE5850](#)