


12 A Snubberless™ Triac

Datasheet -production data



Features

- High static dV/dt
- High dynamic turn-off commutation (dI/dt)c
- 150 °C maximum T_j
- Three quadrants
- Surge capability V_{DSM} , $V_{RSM} = 900$ V

Benefits

- High immunity to turn-on thanks to high static dV/dt
- Better turn-off in high temperature environments thanks to (dI/dt)c
- Increase of thermal margin due to extended working T_j up to 150 °C
- Good thermal resistance due to non-insulated tab

Applications

- General purpose AC line load switching
- Motor control circuits
- Home appliances
- Heating
- Lighting
- Inrush current limiting circuits
- Overvoltage crowbar protection

Description

Available in SMD, the T1235T-8G Triac can be used for the on/off or phase angle control function in general purpose AC switching where high commutation capability is required. This device can be used without a snubber RC circuit when the limits defined are respected.

D²PAK package is UL94-V0 flammability resin compliance.

Package environmentally friendly Ecopack®2 graded (RoHS and Halogen Free compliance).

Snubberless™ is a trademark of STMicroelectronics.

Figure 1: Functional diagram




Table 1: Device summary

Symbol	Value	Unit
$I_{T(RMS)}$	12	A
V_{DRM}/V_{RRM}	800	V
V_{DSM}/V_{RSM}	900	V
I_{GT}	35	mA

1 Characteristics

Table 2: Absolute maximum ratings (limiting values)

Symbol	Parameter		Value	Unit	
$I_{T(RMS)}$	RMS on-state current (full sine wave)	$T_c = 124^\circ C$	12	A	
I_{TSM}	Non repetitive surge peak on-state current, T_j initial = 25 °C	$t_p = 16.7 \text{ ms}$	95	A	
		$t_p = 20 \text{ ms}$	90		
I^2t	I^2t value for fusing	T_j initial = 25 °C	54	A^2s	
dl/dt	Critical rate of rise of on-state current, $I_G = 2 \times I_{GT}$, $t_r \leq 100 \text{ ns}$	$f = 100 \text{ Hz}$	100	$\text{A}/\mu\text{s}$	
V_{DRM}/V_{RRM}	Repetitive peak off-state voltage	$T_j = 150^\circ C$	600	V	
		$T_j = 125^\circ C$	800	V	
V_{DSM}/V_{RSM}	Non Repetitive peak off-state voltage	$t_p = 10 \text{ ms}$	900	V	
I_{GM}	Peak gate current	$t_p = 20 \mu\text{s}$	$T_j = 150^\circ C$	4	A
$P_{G(AV)}$	Average gate power dissipation		$T_j = 150^\circ C$	1	W
T_{stg}	Storage junction temperature range			-40 to +150	°C
T_j	Operating junction temperature range			-40 to +150	°C

Table 3: Electrical characteristics ($T_j = 25^\circ C$, unless otherwise specified)

Symbol	Test conditions	Quadrants; T_j		Value	Unit
I_{GT}	$V_D = 12 \text{ V}$, $R_L = 33 \Omega$	I - II - III	Min.	1.75	mA
	$V_D = 12 \text{ V}$, $R_L = 33 \Omega$	I - II - III	Max.	35	mA
V_{GT}	$V_D = 12 \text{ V}$, $R_L = 33 \Omega$	I - II - III	Max.	1.3	V
V_{GD}	$V_D = V_{DRM}$, $R_L = 3.3 \text{ k}\Omega$, $T_j = 150^\circ C$	I - II - III	Min.	0.2	V
I_L	$I_G = 1.2 \times I_{GT}$	I - III	Max.	60	mA
	$I_G = 1.2 \times I_{GT}$	II	Max.	80	mA
$I_H^{(1)}$	$I_T = 500 \text{ mA}$, gate open		Max.	40	mA
$dV/dt^{(1)}$	$V_D = 536 \text{ V}$, gate open	$T_j = 125^\circ C$	Min.	2000	$\text{V}/\mu\text{s}$
	$V_D = 402 \text{ V}$, gate open	$T_j = 150^\circ C$	Min.	1000	$\text{V}/\mu\text{s}$
$(dl/dt)c^{(1)}$	Without snubber, $(dV/dt)c > 20 \text{ V}/\mu\text{s}$	$T_j = 125^\circ C$	Min.	12	A/ms
		$T_j = 150^\circ C$	Min.	6	A/ms

Notes:

(1)For both polarities of A2 referenced to A1.

Table 4: Static characteristics

Symbol	Test conditions	T _j		Value	Unit
V _{TM⁽¹⁾}	I _T = 17 A, t _p = 380 µs	25 °C	Max.	1.6	V
V _{TO⁽¹⁾}	Threshold on-state voltage	150 °C	Max.	0.85	V
R _{D⁽¹⁾}	Dynamic resistance	150 °C	Max.	50	mΩ
I _{DRM} /I _{RRM}	V _{DRM} = V _{RRM} = 800 V	25 °C	Max.	5	µA
		125°C		1	mA
	V _{DRM} = V _{RRM} = 600 V	150 °C	Max.	3.1	mA

Notes:

(1)For both polarities of A2 referenced to A1.

Table 5: Thermal resistance

Symbol	Parameter		Value	Unit
R _{th(j-c)}	Junction to case (AC)	D ² PAK	Max.	1.6 °C/W

1.1 Characteristics (curves)

Figure 2: Maximum power dissipation versus on-state RMS current




Figure 3: On-state RMS current versus case temperature




Figure 4: On-state RMS current versus ambient temperature (free air convection)




Figure 5: Relative variation of thermal impedance versus pulse duration




Figure 6: Relative variation of gate trigger voltage and current versus junction temperature (typical values)




Figure 7: Relative variation of holding current and latching current versus junction temperature (typical values)










Figure 8: Surge peak on-state current versus number of cycles**Figure 9: Non repetitive surge peak on-state current for a sinusoidal pulse with width tp < 10 ms****Figure 10: On-state characteristics (maximum values)****Figure 11: Relative variation of critical rate of decrease of main current versus junction temperature****Figure 12: Relative variation of static dV/dt immunity versus junction temperature****Figure 13: Relative variation of leakage current versus junction temperature for different values of blocking voltage**

2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

- ECOPACK®2 compliant
- Lead-free package leads finishing
- Molding compound resin is halogen-free and meets UL standard level V0

2.1 D²PAK package information

Figure 14: D²PAK package outline






Table 6: D²PAK package mechanical data

Ref.	Dimensions					
	Millimeters			Inches ⁽¹⁾		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.30		4.60	0.1693		0.1811
A1	2.49		2.69	0.0980		0.1059
A2	0.03		0.23	0.0012		0.0091
A3		0.25			0.0098	
b	0.70		0.93	0.0276		0.0366
b2	1.25		1.7	0.0492		0.0669
c	0.45		0.60	0.0177		0.0236
c2	1.21		1.36	0.0476		0.0535
D	8.95		9.35	0.3524		0.3681
D1	7.50		8.00	0.2953		0.3150
D2	1.30		1.70	0.0512		0.0669
e	2.54			0.1		
E	10.00		10.28	0.3937		0.4047
E1	8.30		8.70	0.3268		0.3425
E2	6.85		7.25	0.2697		0.2854
G	4.88		5.28	0.1921		0.2079
H	15		15.85	0.5906		0.6240
L	1.78		2.28	0.0701		0.0898
L2	1.27		1.40	0.0500		0.0551
L3	1.40		1.75	0.0551		0.0689
R		0.40			0.0157	
V2	0°		8°	0°		8°

Notes:

(1) Dimensions in inches are given for reference only

Figure 15: D²PAK recommended footprint (dimensions are in mm)**Figure 16: D²PAK stencil definitions (dimensions are in mm)**

3 Ordering information

Figure 17: Ordering information scheme




Table 7: Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
T1235T-8G-TR	T1235T-8G	D ² PAK	1.38 g	1000	Tape and reel
T1235T-8G				50	Tube

4 Revision history

Table 8: Document revision history

Date	Revision	Changes
19-Dec-2017	1	Initial release.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Triacs](#) category:

Click to view products by [STMicroelectronics](#) manufacturer:

Other Similar products are found below :

[CTA08-1000CW](#) [CTB24-800BW](#) [CTA08-1000C](#) [CTA12-800BWPT](#) [CTA16-1000B](#) [CTB24-800B](#) [BT137-600-0Q](#) [5615](#) [OT415Q](#) [2N6075A](#)
[NTE5629](#) [NTE5688](#) [CTB08-400CW](#) [D31410](#) [T2535T-8I](#) [BTA204-600D,127](#) [BTA425Z-800BTQ](#) [KS100N12](#) [TOPT16-800C0,127](#)
[OT408,135](#) [BT134-800E](#) [BT136D](#) [BTB16Q-600BW](#) [Z0409MF](#) [BTA06-600BRG](#) [BTA06-800BWRG](#) [BTA08-600BRG](#) [BTA08-800B](#)
[BT136-600,127](#) [MAC97A6,116](#) [BT137-600E,127](#) [BTB16-600CW3G](#) [BTB16-600CW3G](#) [Z0109MN,135](#) [T825T-6I](#) [T1220T-6I](#) [NTE5638](#)
[ACST1235-8FP](#) [BT136X-600E,127](#) [MAC4DLM-1G](#) [BT134-600D,127](#) [BTA08-600BW3G](#) [NTE56008](#) [NTE56017](#) [NTE56018](#) [NTE56059](#)
[NTE5608](#) [NTE5609](#) [NTE5656](#) [NTE56020](#)