



## 16 A logic level (sensitive) Triac



## Features

- High static  $dV/dt$
- High dynamic turn-off commutation  $(dI/dt)_c$
- 150 °C maximum junction temperature
- Three quadrants
- Surge capability  $V_{DSM}, V_{RSM} = 900\text{ V}$
- Benefits:
  - High immunity to false turn-on thanks to high static  $dV/dt$
  - Better turn-off in high temperature environments thanks to  $(dI/dt)_c$
  - Increase of thermal margin due to extended working  $T_j$  up to 150 °C
  - Good thermal resistance due to non-insulated tab.

## Applications

- General purpose AC line load switching
- Motor control circuits
- Home appliances
- Heating
- Lighting
- Inrush current limiting circuits
- Overvoltage crowbar protection

## Product status link

T1610T-8G

## Product summary

|                   |       |
|-------------------|-------|
| $I_{T(RMS)}$      | 16 A  |
| $V_{DRM}/V_{RRM}$ | 800 V |
| $V_{DSM}/V_{RSM}$ | 900 V |
| $I_{GT}$          | 10 mA |

## Description

Available in SMD, the T1610T-8G Triac can be used for the on/off or phase angle control function in general purpose AC switching where high commutation capability is required. This device can be used without a snubber RC circuit when the limits defined are respected.

D<sup>2</sup>PAK Package is UL-94,V0 flammability resin compliance.

Package environmentally friendly Ecopack<sup>®</sup>2 graded (RoHS and Halogen Free compliance).

Snubberless<sup>™</sup> is a trademark of STMicroelectronics.

# 1 Characteristics

**Table 1. Absolute maximum ratings (limiting values),  $T_j = 25\text{ °C}$  unless otherwise specified**

| Symbol            | Parameter   | Value  | Unit        |             |
|-------------------|---|--|-------------|-------------|
| $V_{DRM}/V_{RRM}$ | Repetitive peak off-state voltage (50-60 Hz)  | $T_j = 125\text{ °C}$                        | 800         | V           |
|                   |   | $T_j = 150\text{ °C}$                        | 600         | V           |
| $V_{DSM}/V_{RSM}$ | Non Repetitive peak off-state voltage   | $t_p = 10\text{ ms}, T_j = 25\text{ °C}$     | 900         | V           |
| $I_{T(RMS)}$      | RMS on-state current (full sine wave)   | $T_c = 126\text{ °C}$                        | 16          | A           |
| $I_{TSM}$         | Non repetitive surge peak on-state current (full cycle, $T_j$ initial = $25\text{ °C}$ )      | $t = 16.7\text{ ms}$                         | 126         | A           |
|                   |   | $t = 20\text{ ms}$                           | 120         |             |
| $I^2t$            | $I^2t$ value for fusing   | $t_p = 10\text{ ms}$                         | 95          | $A^2s$      |
| $di/dt$           | Critical rate of rise of on-state current, $I_G = 2 \times I_{GT}$ , $t_r \leq 100\text{ ns}$ | $f = 100\text{ Hz}$                          | 100         | $A/\mu s$   |
| $I_{GM}$          | Peak gate current   | $t_p = 20\text{ }\mu s, T_j = 150\text{ °C}$ | 4           | A           |
| $V_{GM}$          | Peak Gate Voltage   |  | 5           | V           |
| $P_{G(AV)}$       | Average gate power dissipation  | $T_j = 150\text{ °C}$                        | 1           | W           |
| $T_{stg}$         | Storage junction temperature range  |  | -40 to +150 | $^{\circ}C$ |
| $T_j$             | Operating junction temperature range  |  | -40 to +150 | $^{\circ}C$ |

**Table 2. Electrical characteristics ( $T_j = 25\text{ °C}$ , unless otherwise specified)**

| Symbol            | Test conditions  | Quadrants; $T_j$      | Value    | Unit      |
|-------------------|--|-----------------------|----------|-----------|
| $I_{GT}^{(1)}$    | $V_D = 12\text{ V}, R_L = 30\text{ }\Omega$                            | I - II - III          | Max. 10  | mA        |
| $V_{GT}$          | $V_D = 12\text{ V}, R_L = 30\text{ }\Omega$                            | I - II - III          | Max. 1.3 | V         |
| $V_{GD}$          | $V_D = 800\text{ V}, R_L = 3.3\text{ k}\Omega$ , $T_j = 125\text{ °C}$ | I - II - III          | Min. 0.2 | V         |
| $I_L$             | $I_G = 1.2 \times I_{GT}$  | I - III               | Max. 20  | mA        |
|                   | $I_G = 1.2 \times I_{GT}$  | II                    | Max. 30  | mA        |
| $I_H^{(2)}$       | $I_T = 500\text{ mA}$ , gate open                                      |                       | Max. 25  | mA        |
| $dV/dt^{(2)}$     | $V_D = 536\text{ V}$ , gate open                                       | $T_j = 125\text{ °C}$ | Min. 100 | $V/\mu s$ |
|                   | $V_D = 402\text{ V}$ , gate open                                       | $T_j = 150\text{ °C}$ | Min. 50  | $V/\mu s$ |
| $(di/dt)_c^{(2)}$ | $(dV/dt)_c = 0.1\text{ V}/\mu s$                                       | $T_j = 125\text{ °C}$ | Min. 9   | A/ms      |
|                   |  | $T_j = 150\text{ °C}$ |          |           |
|                   | $(dV/dt)_c = 10\text{ V}/\mu s$  | $T_j = 125\text{ °C}$ | Min. 3   | A/ms      |
|                   |  | $T_j = 150\text{ °C}$ |          |           |

1. Minimum  $I_{GT}$  is guaranteed at 5% of  $I_{GT\text{ max}}$

2. For both polarities of A2 referenced to A1.

**Table 3. Static characteristics**

| Symbol            | Test conditions   | $T_j$  |      | Value | Unit |
|-------------------|---|--------|------|-------|------|
| $V_{TM}^{(1)}$    | $I_T = 22.6 \text{ A}$ , $t_p = 380 \text{ } \mu\text{s}$ | 25 °C  | Max. | 1.55  | V    |
| $V_{TO}^{(1)}$    | Threshold on-state voltage                                | 150 °C | Max. | 0.85  | V    |
| $R_D^{(1)}$       | Dynamic resistance  | 150 °C | Max. | 34    | mΩ   |
| $I_{DRM}/I_{RRM}$ | $V_{DRM} = V_{RRM} = 800 \text{ V}$                       | 25 °C  | Max. | 5     | μA   |
|                   |   | 125 °C |      | 1.0   | mA   |
|                   | $V_{DRM} = V_{RRM} = 600 \text{ V}$                       | 150 °C | Max. | 3.6   | mA   |


1. For both polarities of A2 referenced to A1.

**Table 4. Thermal resistance**


| Symbol        | Parameter             |                    | Value | Unit      |
|---------------|-----------------------|--------------------|-------|-----------|
| $R_{th(j-c)}$ | Junction to case (AC) | D <sup>2</sup> PAK | Max.  | 1.15 °C/W |

## 1.2 Characteristics (curves)


**Figure 1. Maximum power dissipation versus on-state RMS current**




**Figure 2. On-state RMS current versus case temperature**




**Figure 3. On-state RMS current versus ambient temperature (free air convection)**




**Figure 4. Relative variation of thermal impedance versus pulse duration**




**Figure 5. Relative variation of gate trigger voltage and current versus junction temperature (typical values)**




**Figure 6. Relative variation of holding current and latching current versus junction temperature (typical values)**




**Figure 7. Surge peak on-state current versus number of cycles**




**Figure 8. Non repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10$  ms**




**Figure 9. On-state characteristics (maximum values)**




**Figure 10. Relative variation of critical rate of decrease of main voltage versus junction temperature**



**Figure 11. Relative variation of critical rate of decrease of main current versus junction temperature (typical values)**




**Figure 12. Relative variation of leakage current versus junction temperature for different values of blocking voltage**



## 2 Ordering information

**Figure 13. Ordering information scheme**



**Table 5. Ordering information**

| Order code   | Marking   | Package            | Weight | Base qty. | Delivery mode |
|--------------|-----------|--------------------|--------|-----------|---------------|
| T1610T-8G-TR | T1610T-8G | D <sup>2</sup> PAK | 1.38 g | 1000      | Tape and reel |
| T1610T-8G    |           |                    |        | 50        | Tube          |

### 3 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

#### 3.1 D<sup>2</sup>PAK package information

- ECOPACK2® compliant
- Lead-free package leads finishing
- Molding compound resin is halogen-free and meets UL standard level V0

Figure 14. D<sup>2</sup>PAK package outline




Table 6. D<sup>2</sup>PAK package mechanical data

| Ref. | Dimensions  |      |       |                     |        |        |
|------|-------------|------|-------|---------------------|--------|--------|
|      | Millimeters |      |       | Inches <sup>1</sup> |        |        |
|      | Min.        | Typ. | Max.  | Min.                | Typ.   | Max.   |
| A    | 4.30        |      | 4.60  | 0.1693              |        | 0.1811 |
| A1   | 2.49        |      | 2.69  | 0.0980              |        | 0.1059 |
| A2   | 0.03        |      | 0.23  | 0.0012              |        | 0.0091 |
| A3   |             | 0.25 |       |                     | 0.0098 |        |
| b    | 0.70        |      | 0.93  | 0.0276              |        | 0.0366 |
| b2   | 1.25        |      | 1.7   | 0.0492              |        | 0.0669 |
| c    | 0.45        |      | 0.60  | 0.0177              |        | 0.0236 |
| c2   | 1.21        |      | 1.36  | 0.0476              |        | 0.0535 |
| D    | 8.95        |      | 9.35  | 0.3524              |        | 0.3681 |
| D1   | 7.50        |      | 8.00  | 0.2953              |        | 0.3150 |
| D2   | 1.30        |      | 1.70  | 0.0512              |        | 0.0669 |
| e    |             | 2.54 |       |                     | 0.1    |        |
| E    | 10.00       |      | 10.28 | 0.3937              |        | 0.4047 |
| E1   | 8.30        |      | 8.70  | 0.3268              |        | 0.3425 |
| E2   | 6.85        |      | 7.25  | 0.2697              |        | 0.2854 |
| G    | 4.88        |      | 5.28  | 0.1921              |        | 0.2079 |
| H    | 15          |      | 15.85 | 0.5906              |        | 0.6240 |
| L    | 1.78        |      | 2.28  | 0.0701              |        | 0.0898 |
| L2   | 1.27        |      | 1.40  | 0.0500              |        | 0.0551 |
| L3   | 1.40        |      | 1.75  | 0.0551              |        | 0.0689 |
| R    |             | 0.40 |       |                     | 0.0157 |        |
| V22  | 0°          |      | 8°    | 0°                  |        | 8°     |

1. Dimensions in inches are given for reference only
2. Degrees



Figure 15. D<sup>2</sup>PAK recommended footprint (dimensions are in mm)





Figure 16. D<sup>2</sup>PAK stencil definitions (dimensions are in mm)



## Revision history

**Table 7. Document revision history**

| Date        | Version | Changes   |
|-------------|---------|---|
| 03-Apr-2018 | 1       | Initial release.  |
| 17-Jul-2018 | 2       | Updated <a href="#">Table 2. Electrical characteristics</a> ( $T_j = 25\text{ °C}$ , unless otherwise specified). |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Triacs](#) category:*

*Click to view products by [STMicroelectronics](#) manufacturer:*

Other Similar products are found below :

[T2035H-6G](#) [BT137-600-0Q](#) [Z0409MF0AA2](#) [Z0109NA 2AL2](#) [ACST1635T-8FP](#) [BCR20RM-30LA#B00](#) [CMA60MT1600NHR](#) [NTE5611](#)  
[NTE5612](#) [NTE5613](#) [NTE5621](#) [NTE5623](#) [NTE5629](#) [NTE5638-08](#) [NTE5688](#) [NTE5689](#) [NTE5690](#) [T1235T-8I](#) [BTA312-600CT.127](#) [T1210T-](#)  
[8G-TR](#) [Z0109NN0,135](#) [T2535T-8I](#) [T2535T-8T](#) [TN4050-12WL](#) [MAC4DLM-1G](#) [BT137-600E,127](#) [BT137X-600D](#) [BT148W-600R,115](#)  
[BT258-500R,127](#) [BTA08-800BW3G](#) [BTA140-800,127](#) [BTA30-600CW3G](#) [BTA30-600CW3G](#) [BTB08-800BW3G](#) [BTB16-600CW3G](#)  
[BTB16-600CW3G](#) [Z0410MF0AA2](#) [Z0109MN,135](#) [T825T-6I](#) [T1635T-6I](#) [T1220T-6I](#) [NTE5638](#) [TYN612MRG](#) [TYN1225RG](#) [TPDV840RG](#)  
[ACST1235-8FP](#) [ACS302-6T3-TR](#) [BT134-600D,127](#) [BT134-600G,127](#) [BT136X-600E,127](#)