

storm 2210 Series keyboards



Compact format, vandal resistant keyboards for exposed public environments

- Vandal resistant (20J BS EN 60068-2-75: 1997)
- Weather resistant (IP65)
- Integral PS2/USB Interface (switchable)
- Optional PC connection cables (sold separately)
- Optional fixing kit for under panel installation (sold separately) or adapter kit for benchtop use (also sold separately)
- RFI / EMI Protection in accordance with current European and U.S. directives
- Operational life of more than 4 million cycles per key
- Resistant to most commonly used cleaning agents
- 61 keys
- Compact format: 289.5 mm x 118.5 mm x 32.8 mm



www.storm-interface.com

Storm Interface products include technology protected by international patents and design registration. All rights reserved.




2210 Series keyboards for public environments

STORM 2210 keyboards are constructed to survive in exposed, unsupervised, public environments. Their responsive key action ensures rapid, reliable and responsive data entry in tough, wet or hostile conditions. A hardened stainless steel front plate and captive, cast metal or high impact polymer keys ensure the keyboard's resistance to hard use, abuse and vandalism.



Overall Dimensions




Keyboard Weight:	
with cast metal keytops	1.71 kg
with polymer keytops	1.05 kg
Underpanel cut out aperture	280.5 x 109.5mm (11.0 x 4.3 in.)
Max panel thickness	2mm

View showing rear of panel with dimensions of stud positions and panel cut out details

All dimensions in mm.

M3 x 20mm long steel weld studs or equivalent



Options

Build Style	Vandal resistant (stainless steel top plate)
Keytops	Cast metal keytops, chrome plated Black keytops, laser marked white
Encoder	PS2/USB selectable
Languages	English UK, English USA, French, Spanish, German

Electrical

EMC Emissions	EN55022 : 1998 Class B Limit
EMC Immunity to ESD	EN55024 : 1998
EMC Immunity to Radiated Fields	EN55024 : 1998
Electrical Safety	EN60950, UL60950
Communication	Industry Standard PS2 or USB Interface
Supply requirements – voltage	+5V nominal (5.5V to 4.75V)
Supply requirements – current	60mA (with 2 LEDs illuminated)

Environmental

Sealing – Water / Particulates	EN60529 (sealing to IP65)
Temperature	-20°C to +60°C operating (dry)

Mechanical

Impact Resistance	20 Joules via 50mm dia steel striker
Key Pitch	19mm
Size	11mm square
Travel	1.5mm nominal
Actuation Force	130g nominal

Accessories

Description	Stock Code
2200 Underpanel Fixing Kit – contains clips	2210-MK000[x]
2200 Foot Kit – required for benchtop use	2200-FK000[x]
Keyboard PS2 Cable – straight 2.5m long	1200-00100[x]
Keyboard USB Cable – straight 2.5m long	1200-00200[x]

Whilst every effort is made to ensure details are correct at time of print, specifications are subject to change without notice.



Storm is a trademark of Keymat Technology Ltd
Storm Interface is a trading name of Keymat Technology Ltd
Storm Interface products include technology protected by international patents and design registration. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Storm Interface](#) manufacturer:

Other Similar products are found below :

[1605-330013](#) [1K041103](#) [1K042101](#) [1K042103](#) [1K120101](#) [1K120103](#) [1K12T101](#) [1K12T103](#) [1K160101](#) [1K160103](#) [1K16T101](#) [1K16T103](#)
[2200-000301](#) [2200-002003](#) [2200-003003](#) [2200-FK0003](#) [2K041103](#) [2K042103](#) [2K120103](#) [2K12T103](#) [2K160103](#) [2K16T103](#) [3K041103](#)
[3K042103](#) [3K120103](#) [3K12T103](#) [3K160103](#) [3K16T103](#) [3KLW160103](#) [4200-003](#) [4200-103](#) [4500-003](#) [4500-013](#) [4500-103](#) [5001-200103](#)
[5001-200203](#) [5100-0103](#) [5100-FK03](#) [5103-0003](#) [5103-0103](#) [6000-MK003](#) [70040101](#) [70040103](#) [70040203](#) [7004CL03](#) [70120103](#) [70120203](#)
[70160101](#) [70160103](#) [70160201](#)