

Suitable for use with Storm USB Keypad Encoder (4500-00)

Robust, polymer cased, steel-backed keypads

Ideal for use in a wide range of industrial and commercial applications.

These keypads are suitable for wet, dirty & exposed environments. They feature a steel backplate for additional impact resistance.



Contact Bounce Contact Resistance Insulation Resistance Breakdown Voltage Operating Voltage Operating Current

5ms (max) 100 ohms (max) 50 Mohms (min) 500V AC (max 60 secs.) 24V DC (max) 50mA (max)



Electrical

Operational Life . Keytop Travel Actuation Force Connector

4 million cycles (min) per key 1.4mm nominal 180gms nominal 0.1" pitch, gold plated square pin, male connector

Environmental

Water / Dust Sealed IP65 (when fixed to a suitable enclosure) **Operational Temperature** -25°C to +85°C (Dry)

Material

Casing Keytops Backplate Contact Circuit

High Impact Polymer (black) High Impact Polymer (translucent) Steel (corrosion protected) Gold on Nickel Plated FR4




For more information & to order:














F key format

2000 Series Part Numbers

2K04210

Accessories USB Encoder 4500-00 RS-232 Encoder 4200-00




You





Designed & produced by NIK Design







www.storm-interface.com



FM 39602



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Input Devices category:

Click to view products by Storm Interface manufacturer:

Other Similar products are found below:

80260-00 81485-28 81521-08 FKB4720-103 84250-26 84980-04 84S-AC1-000 JD-0700EU-2 JM-0800-2 JW-T0100 89498-13 89758-05 89886-26 89941-00 G80-3000LSCEU-2 MJ0FGGRY JM-0800-0 84S-BB1-004 81601-26 UL21KMZQ G8011900LPMUS0 G84-4700LUCUS-0 81485-26 84105-13 V400-W24 5M V400-W23 5M G84-5200LCMEU-2 DT2257X20V00GRY 84Z2029-78 84Z2029-79 V400-W23P 5M VW3A8151R20U V400-W24 15M LT1332D V400-W24 10M V400-W24P 15M V400-WM0 1M V400-W24P 10M V400-W23P 10M TCS-14920P V400-W23 3M LT1372D LP1007EXXH00R DT2253X20V00BLK 100133BX EZ08-230013 81248-04 89887-26 90215-00 HB110C3NWBNA