


Suitable for use with Storm USB Keypad Encoder (4500-00)



Robust, polymer cased keypads

These responsive keypads are robust, reliable and splash resistant.

They are suitable for most industrial and semi-sheltered outdoor applications





Contact Bounce

5ms (max) 100 ohms (max) 50 Mohms (min) 500V AC (max 60 secs.) 24V DC (max) 50mA (max)

Mechanical

Electrical

Contact Resistance Insulation Resistance

Operational Life . Keytop Travel Actuation Force Connector

2 million cycles (min) per key 1.4mm nominal 180gms nominal 0.1" pitch, gold plated square pin, male connector

Environmental

Water / Dust Sealed IP54 (when fixed to a suitable enclosure) **Operational Temperature** -10°C to +85°C (Dry)

Material

Casing General Service Polymer (black) Keytops **General Service Polymer (translucent)** Contact Circuit Gold on Nickel Plated FR4



For more information & to order:



Designed & produced by NIK Design





www.storm-interface.com





3K August 2013

FM 39602



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Input Devices category:

Click to view products by Storm Interface manufacturer:

Other Similar products are found below:

80260-00 81485-28 81521-08 FKB4720-103 84250-26 84980-04 84S-AC1-000 JD-0700EU-2 JM-0800-2 JW-T0100 89498-13 89758-05 89886-26 89941-00 G80-3000LSCEU-2 MJ0FGGRY JM-0800-0 84S-BB1-004 81601-26 UL21KMZQ G8011900LPMUS0 G84-4700LUCUS-0 81485-26 84105-13 V400-W24 5M V400-W23 5M G84-5200LCMEU-2 DT2257X20V00GRY 84Z2029-78 84Z2029-79 V400-W23P 5M VW3A8151R20U V400-W24 15M LT1332D V400-W24 10M V400-W24P 15M V400-WM0 1M V400-W24P 10M V400-W23P 10M TCS-14920P V400-W23 3M LT1372D LP1007EXXH00R DT2253X20V00BLK 100133BX EZ08-230013 81248-04 89887-26 90215-00 HB110C3NWBNA