

REV.	ECN NO.	DATE
1.0	RELEASED	05/25/01
2.0	REVISED P/N	03/04/04
3.0	UPDATE TOL.	12/16/04

SPECIFICATIONS

CURRENT RATING: 3 AMPS

INSULATOR RESISTANCE: 5000 MEGOHMS MIN. CONTACT RESISTANCE: 20 MILLIOHMS MAX. DIELECTRIC WITHSTANDING: AC 500V

MAX PROCESSING TEMP: 230°C FOR 30 ~ 60 SECONDS

(260°C FOR 10 SECONDS)

OPERATING TEMPERATURE : -40°C ~ +125°C CONTACT MATERIAL: PHOSPHOR BRONZE. INSULATOR MATERIAL: NYLON, UL 94V-0

*CONTACT PLATING: P=OVERALL GOLD FLASH; T=OVERALL TIN

ORDERING INFORMATION:

- 1. Replace "*" with plating code
- 2. Replace "xx" with number of positions (Pins)

SCALE	3:1	DRAW	JFW	Sullins Electronics
UNIT	MM	CHECK	AJT	San Marcos, CA Tel: 760 744-0125 www.SullinsElectronics.com
TOLERANCE		AP"E		NAME: FEMALE HEADER, 2.54mm SPACING
.0=±0.35 .00=±0.2 ANG=±5*		PROJECTION	\(\phi\)	7.1mm PROFILE, SMT
				(PART NO) PP_Cxx1KFXC
				(DRAW NO) 7012

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for sullins manufacturer:

Other Similar products are found below:

PEC36DGAN PPPC062LFBN-RC PBC36DADN PBC36DGAN GEC36SABN-M30 PREC006DFBN-RC PZC04DBAN NPPN082AFCN-RC RBB60DHBS PPTC022LFBN-RC PPTC041LGBN-RC RCA44DRSD-S888 EBC25DCWN LPPB031NFFN-RC GEC36DBAN EZM25DRXH NPTC042KFMS-RC TCC03DKSN-S1713 ECC18DCCN NPPN081BFCN-RC FMC05DRTN-S1682 EBC35DCWN SBH21-NBPN-D07-SM-BK WCT001-MCT NPPN041BFLC-RC PBC36DFAN SFH11-PBPC-D20-RA-BK NRTJ052TKEN-RC SPC02SVGN-RC PBC04DAAN PBC08DAGN MPP-1100-05-DS-4GR(S1402) PPTC042LFBN-RC PBC36DBCN PEC36SAGN PPPC142LJBN-RC PEC36DAHN PBC06DAAN PEC36DFCN PEC36DGBN PPTC162LFBN-RC PEC36DBEN PBC01DAAN PBC36SFEN SBH41-NBPB-D05-SM-BK PBC36SAGN PEC36SFEN PEC07DAAN GRPB121VWVN-RC AMC02SXNN-S328