


# SMD Power Inductor CD75/T125





## Description

- Ferrite drum core construction.
- Magnetically unshielded.
- L × W × H: 8.1 × 7.3 × 5.5mm Max.
- Product weight: 0.76g(Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Qualification to AEC-Q200.

## Dimension - [mm]



## Land pattern and Schematics - [mm]



## Environmental Data

- Operating temperature range: -40°C ~ +125°C (including coil's self temperature rise)
- Storage temperature range: -40°C ~ +125°C
- Solder reflow temperature: 260 °C peak.

## Packaging

- Carrier tape and reel packaging.
- 13" diameter reel
- 500pcs per reel

## Applications

- Automotive and other high temperature, high reliability application.



### Electrical Characteristics

Part No.	Stamp	Inductance [Within] ※1	D.C.R. ( $\Omega$ ) [Max.] (at 20°C)	Saturation current (A) (at 20°C) ※2	Temperature rise current (A) ※3
CD75T125NP-100KC	100K	10 $\mu$ H $\pm$ 10%	0.07	2.80	3.18
CD75T125NP-120KC	120K	12 $\mu$ H $\pm$ 10%	0.08	2.45	3.15
CD75T125NP-150KC	150K	15 $\mu$ H $\pm$ 10%	0.09	2.16	3.02
CD75T125NP-180KC	180K	18 $\mu$ H $\pm$ 10%	0.10	2.00	2.80
CD75T125NP-220KC	220K	22 $\mu$ H $\pm$ 10%	0.11	1.80	2.63
CD75T125NP-270KC	270K	27 $\mu$ H $\pm$ 10%	0.12	1.66	2.46
CD75T125NP-330KC	330K	33 $\mu$ H $\pm$ 10%	0.13	1.51	2.35
CD75T125NP-390KC	390K	39 $\mu$ H $\pm$ 10%	0.16	1.39	2.05
CD75T125NP-470KC	470K	47 $\mu$ H $\pm$ 10%	0.18	1.26	1.95
CD75T125NP-560KC	560K	56 $\mu$ H $\pm$ 10%	0.24	1.22	1.72
CD75T125NP-680KC	680K	68 $\mu$ H $\pm$ 10%	0.28	1.06	1.48
CD75T125NP-820KC	820K	82 $\mu$ H $\pm$ 10%	0.37	0.95	1.34
CD75T125NP-101KC	101K	100 $\mu$ H $\pm$ 10%	0.43	0.90	1.29
CD75T125NP-121KC	121K	120 $\mu$ H $\pm$ 10%	0.47	0.87	1.17
CD75T125NP-151KC	151K	150 $\mu$ H $\pm$ 10%	0.64	0.73	0.96
CD75T125NP-181KC	181K	180 $\mu$ H $\pm$ 10%	0.71	0.63	0.93
CD75T125NP-221KC	221K	220 $\mu$ H $\pm$ 10%	0.96	0.61	0.80
CD75T125NP-271KC	271K	270 $\mu$ H $\pm$ 10%	1.11	0.54	0.74
CD75T125NP-331KC	331K	330 $\mu$ H $\pm$ 10%	1.26	0.51	0.72
CD75T125NP-391KC	391K	390 $\mu$ H $\pm$ 10%	1.77	0.47	0.64
CD75T125NP-471KC	471K	470 $\mu$ H $\pm$ 10%	1.96	0.43	0.60

※1 Measuring frequency 10 $\mu$ H ~ 82 $\mu$ H ; at 2.52 MHz  
100 $\mu$ H ~ 820 $\mu$ H ; at 1 kHz

※2 Saturation current: This indicates the actual value of D.C. current when the inductance becomes 10% lower than its initial value.(Ta=20°C)













※3 Temperature rise current: The actual value of D.C. current when the temperature of coil becomes  $\Delta T=40^\circ\text{C}$  (Ta=20°C).

# SMD Power Inductor CD75/T125



## Saturation Current & Temperature Rise Graph

— L (20°C) — L (105°C) —  $\Delta T$












# SMD Power Inductor CD75/T125



## Saturation Current & Temperature Rise Graph

— L (20°C) — L (105°C) —  $\Delta T$




# SMD Power Inductor CD75/T125




## Solder Reflow Condition

Heat Endurance



Temperature Chart



Please refer to the sales offices on our website - <http://www.sumida.com>

### Hong Kong

Tel.+852-2880-6781  
FAX.+852-2565-9600  
[sales@hk.sumida.com](mailto:sales@hk.sumida.com)

### Saitama(Japan)

Tel.+81-48-691-7300  
FAX.+81-48-691-7340  
[sales@jp.sumida.com](mailto:sales@jp.sumida.com)

### Chicago

Tel.+1-847-545-6700  
FAX. +1-847-545-6720  
[sales@us.sumida.com](mailto:sales@us.sumida.com)

### Shanghai

Tel.+86-21-5836-3299  
FAX.+86-21-5836-3266  
[shanghai.sales@cn.sumida.com](mailto:shanghai.sales@cn.sumida.com)

### Seoul

Tel.+82-2-6237-0777  
FAX.+82-2-6237-0778  
[sales@kr.sumida.com](mailto:sales@kr.sumida.com)

### Obernzell

Tel.+49-8591-937-0  
FAX. +49-8591-937-103  
[contact@eu.sumida.com](mailto:contact@eu.sumida.com)

### Shenzhen

Tel.+86-755-8291-0228  
FAX.+86-755-8291-0338  
[shenzhen.sales@cn.sumida.com](mailto:shenzhen.sales@cn.sumida.com)

### Singapore

Tel.+65-6296-3388  
FAX.+65-6841-4426  
[sales@sg.sumida.com](mailto:sales@sg.sumida.com)

### Neumarkt

Tel.+49-9181-4509-110  
FAX. +49-9181-4509-310  
[infocomp@eu.sumida.com](mailto:infocomp@eu.sumida.com)

### Taipei

Tel.+886-2-8751-2737  
FAX.+886-2-8751-2738  
[sales@tw.sumida.com](mailto:sales@tw.sumida.com)

### San Jose

Tel.+1-408-321-9660  
FAX.+1-408-321-9308  
[sales@us.sumida.com](mailto:sales@us.sumida.com)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fixed Inductors](#) category:*

*Click to view products by [Sumida](#) manufacturer:*

Other Similar products are found below :

[CR32NP-100KC](#) [CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#)