

SMD Power Inductor

CDRH60D45B/T150



Recommended Type

Description

- Magnetically shielded
- LxWxH: 6.3x6.6xH4.8 mm Max.
- Qualified AEC-Q200



Environmental Data

- Operating Temperature: -55°C to +150°C (including self-heating)


Packaging

- Carrier tape and reel packaging


Applications

- High temp and high reliability automotive applications


Dimension - [mm]



Recommended Land pattern - [mm]



Wire Connection



SMD Power Inductor

CDRH60D45B/T150



Electrical Characteristics

Part Number	Inductance [Within] (μ H) ※1	D.C.R. at 20°C Max.(Typ.) (m Ω)	Saturation Current (A) Max.(Typ.) ※2	Temperature Rise Current (A) Max.(Typ.) ※3
CDRH60D45BT150NP-1R0NC	1.00 \pm 30%	14.30 (11.00)	6.70 (8.50)	4.20 (4.80)
CDRH60D45BT150NP-1R5NC	1.50 \pm 30%	16.90 (13.00)	5.50 (7.20)	4.00 (4.50)
CDRH60D45BT150NP-2R2NC	2.20 \pm 30%	19.50 (15.00)	4.20 (5.70)	3.85 (4.10)
CDRH60D45BT150NP-3R3NC	3.30 \pm 30%	23.40 (18.00)	3.50 (5.00)	3.40 (3.70)
CDRH60D45BT150NP-4R7NC	4.70 \pm 30%	29.90 (23.00)	3.10 (4.10)	3.00 (3.40)
CDRH60D45BT150NP-6R8NC	6.80 \pm 30%	35.10 (27.00)	2.50 (3.60)	2.60 (3.10)
CDRH60D45BT150NP-100MC	10.00 \pm 20%	45.60 (38.00)	2.10 (2.80)	2.40 (2.60)
CDRH60D45BT150NP-150MC	15.00 \pm 20%	76.80 (64.00)	1.70 (2.30)	1.50 (2.00)
CDRH60D45BT150NP-220MC	22.00 \pm 20%	98.40 (82.00)	1.40 (1.90)	1.40 (1.70)
CDRH60D45BT150NP-330MC	33.00 \pm 20%	126 (105)	1.10 (1.56)	1.30 (1.60)
CDRH60D45BT150NP-470MC	47.00 \pm 20%	156 (130)	0.97 (1.28)	1.10 (1.40)
CDRH60D45BT150NP-680MC	68.00 \pm 20%	252 (210)	0.81 (1.07)	0.85 (1.10)
CDRH60D45BT150NP-101MC	100 \pm 20%	408 (340)	0.61 (0.90)	0.72 (0.86)
CDRH60D45BT150NP-151MC	150 \pm 20%	576 (480)	0.53 (0.74)	0.60 (0.72)
CDRH60D45BT150NP-221MC	220 \pm 20%	864 (720)	0.47 (0.62)	0.48 (0.57)
CDRH60D45BT150NP-331MC	330 \pm 20%	1164 (970)	0.36 (0.50)	0.40 (0.49)
CDRH60D45BT150NP-471MC	470 \pm 20%	1728 (1440)	0.28 (0.39)	0.38 (0.46)

※ Measuring frequency inductance at 100kHz,1V.

※ Saturation current: DC current which becomes inductance value drop by 30% from the nominal value.

※ Temperature rise current: The value of D.C. current when the temperature of coil becomes $\Delta T=40^{\circ}\text{C}$ ($T_a=20^{\circ}\text{C}$).



SMD Power Inductor

CDRH60D45B/T150



Recommended Type

Solder Reflow Condition



SMD Power Inductor

CDRH60D45B/T150




Recommended Type

Saturation Current & Temperature Rise Graph


— L (20°C) — L (150°C) — ΔT

1. CDRH60D45BT150NP-1R0NC




DC(A)

2. CDRH60D45BT150NP-1R5NC




DC(A)

3. CDRH60D45BT150NP-2R2NC




DC(A)

4. CDRH60D45BT150NP-3R3NC




DC(A)

5. CDRH60D45BT150NP-4R7NC




DC(A)

6. CDRH60D45BT150NP-6R8NC




DC(A)

7. CDRH60D45BT150NP-100MC




DC(A)

8. CDRH60D45BT150NP-150MC



DC(A)

9. CDRH60D45BT150NP-220MC



DC(A)


Note: This specification is subject to change without notice. Please contact your nearest sales office for updated information when placing an order.

SMD Power Inductor

CDRH60D45B/T150




10. CDRH60D45BT150NP-330MC




DC(A)

11. CDRH60D45BT150NP-470MC




DC(A)

12. CDRH60D45BT150NP-680MC




DC(A)

13. CDRH60D45BT150NP-101MC




DC(A)

14. CDRH60D45BT150NP-151MC




DC(A)

15. CDRH60D45BT150NP-221MC




DC(A)

16. CDRH60D45BT150NP-331MC



DC(A)

17. CDRH60D45BT150NP-471MC



DC(A)



For sales office information, please [click here](#) to visit our website.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Power Inductors - SMD category](#):

Click to view products by [Sumida manufacturer](#):

Other Similar products are found below :

[SPD62R-472M](#) [LLQPB201214T1R0M](#) [LLXND3030QKT470MNG](#) [LLQPB160807T4R7M](#) [LLAPB2016KKTR33M](#)
[LBXND4040TKL330MDG](#) [LLXNE3030KKT4R7MN](#) [LSQEA201212T100M](#) [IHLP5050CEER4R7M06](#) [LVS505020-1R0T-N](#) [LVS505040-1R2T-N](#) [LVS606020-1R5M-N](#) [LVS606028-6R8M-N](#) [LVS606045-102M-N](#) [LVS606045-150M-N](#) [LVS606045-1R8M-N](#) [LVS606045-6R8M-N](#) [LVS808040-2R0M-N](#) [LVS808040-330M-N](#) [LVS808040-4R7M-N](#) [MHCI06030-R56M-R8](#) [SCD0403T-470M-N](#) [SCD0403T-6R8K-N](#) [SCD0504T-101M-N](#) [SCD0504T-120M-N](#) [SCD0504T-221M-N](#) [SCD0504T-470M-N](#) [SCD0504T-471M-N](#) [SCD0705T-180M-N](#) [SCD0705T-221M-N](#) [SCD0705T-470M-N](#) [SCD1005T-101M-N](#) [SCD1005T-221M-N](#) [SCD1005T-470M-N](#) [SSL1306T-101M-N](#) [LQB15NNR27K10D](#) [201610CDMCDDS-R47MC](#) [201610CDMCDDS-1R0MC](#) [201610CDMCDDS-R68MC](#) [LSQPB201210T220M](#) [LBCNF2012KKTR24MA](#) [LSQEA201212T220K](#) [LSENC2016KKT1R0M](#) [LSQNB160808T470M](#) [LSBHB1608KKT2R2MG](#) [LSQPB160807T2R2M](#) [LSQEA201212T101K](#) [LCXND4040MKL4R7MDG](#) [DEM8045Z-5R6N=P3](#) [LCXNH8080YKL101MJG](#)